



# LED GLOBE LIGHT



## SCHEMATICS:



## DESCRIPTION:

'Mini Marquee' flexible light strip offering LED efficiency and field cuttability. Bulb sockets located 12" on center contain replaceable 0.5 watt LED lamps. LED rated at 60,000 hour average life and are offered in Warm White and Cool White. Maximum single run of 200 globes consumes only 100 watts. ETL listed for indoor and outdoor applications. See instructions for complete specifications and installation details.

## APPLICATIONS

- ▶ Roof outline
- ▶ Building outline
- ▶ Architectural accents
- ▶ Stage border
- ▶ Retail windows
- ▶ Holiday lighting

## FEATURES

- ▶ Flexible 16AWG listed supply wire
- ▶ Field cuttable
- ▶ Bulb sockets 12" on center
- ▶ Maximum single run of 200 ft. (200 globes)
- ▶ 0.5 watt replaceable LED bulbs
- ▶ 60,000 hour average LED life
- ▶ Offered in warm white and cool white LED colors
- ▶ ETL listed for indoor and outdoor use

## ORDERING LOGIC:

LEDGL-XX-YY

### XX = LENGTH

Example: 12 = 12 ft.

### YY = LED COLOR

WW = Warm white

CW = Cool white

## SPECIFICATIONS:

<b>Voltage</b>	12V. Use TR-12-150/300 transformer. See instructions
<b>Fixture Energy Rating</b>	0.5 watt four-chip LED
<b>Average LED Life</b>	60,000 hours
<b>LED Spacing</b>	1 foot (12") on center (+/- 1/4")
<b>LED Color</b>	Warm White (3000K), Cool White (6400K)
<b>Globe Color</b>	Clear
<b>Cuttability</b>	Anywhere!
<b>LED Connection</b>	Parallel wired to UL listed STP-2 AWG #16 wire
<b>LED Socket and Wire Color</b>	Black
<b>Maximum Single Run</b>	200 globes (100 watts, 8.33 amps)
<b>Energy Usage</b>	0.5 watts per globe
<b>Dimming</b>	Not for use with dimmers
<b>Agency Approval</b>	ETL listed for indoor and outdoor use



<b>PROJECT:</b>	<b>TYPE:</b>
<b>NOTES:</b>	