

Thin-Line LED Down Light



DIMMABLE

[] []

4", 11 watts High Power Thin-line LED Down Light. Designed for retrofit and new construction, damp location rated. Thin Line Downlights are a versatile and affordable choice for countless applications.

1" 25 mm Ø4.75" Ø121 mm Ø4.75" Ø121 mm			
E sture		Specif	ications
Features		· · · · · · · · · · · · · · · · · · ·	
 Energy Star rated - up to 80% energy savings Dimmable to 5% with most standard dimmers Available in standard power and high power versions 		LED Color CTT	White WW (3000K) NW (4000K)
• 120° beam spread		Input Voltage	100 - 120V, 60Hz
Warm White and Neutral White colr temperatures		Output Power(W)	11 Watts
• Two spring loaded clips to attach to any ceiling material		No. SMD2835 LEDs	72
Standard Power suitable for damp location		Lumen (Im)	1068(WW) 1072(NW)
No IC can required, for direct contact with insulation		CRI	>80
and combustible materials		Luminous Efficacy	97lm/w (WW)
Connects directly to 120V power supply		(Im/W)	97lm/w (NW)
 Optional 347V Step-Down Transformer 		Approved Location	Damp
• 50,000 hour life		Dimmable	Yes
• 5 year limited warranty		Life Span	> 50,000 hrs
Airtight cETLus and Energy Star listed		Appearance Size	4.75" W x 1" D (121mm W x 25mm D)
		Installation Hole Size	4.25" (108mm)
Ordering Code: LED Color			
LVLDL-HP-04 -	•	• WH - R	
WW (Warm White 3000K) NW (Natural White 4000K)			
Project	Туре		
Date	Contact		
Notes			



800-527-4358