

Thin-Line LED Down Light



DIMMABLE

[] []

8", 25 watts High Power Thin-line LED Down Light. Designed for retrofit and new construction, damp location rated. Thin Line Downlights are a versatile and affordable choice for countless applications.

1" 25 mm Ø9.01" Ø229 mm Ø229 mm Ø9.01" Ø229 mm			
Factures	Spec	Specifications	
Features	-		
Energy Star rated - up to 80% energy savings	LED Color	White	
Dimmable to 5% with most standard dimmers	СТТ	WW (3000K)	
Available in standard power and high power versions		NW (4000K)	
120° beam spread	Input Voltage	100 - 120V, 60Hz	
Warm White and Neutral White color temperatures	Output Power(W)	25 Watts	
 Two spring loaded clips to attach to any ceiling material 	No. SMD2835 LEDs	192	
 Standard Power suitable for damp location 	Lumen (Im)	2575(WW) 2973(NW)	
 No IC can required, for direct contact with insulation 	CRI	>80	
and combustible materials	Luminous Efficacy	103lm/w (WW)	
 Connects directly to 120V power supply 	(Im/W)	106lm/w (NW)	
Optional 347V Step-Down Transformer	Approved Location	Damp	
• 50,000 hour life	Dimmable	Yes	
 5 year limited warranty 	Life Span	> 50,000 hrs	
 Airtight cETLus and Energy Star listed 	Appearance Size	9.01" W x 1" D (229mm W x 25mm D)	
	Installation Hole Size	8.07" (205mm)	
Ordering Code:			
LVLDL-HP-08 - LED Color WW (Warm White 3000K) WW (Natural White 4000K)			
Project	Туре		
Date Co	ontact		

Notes



