NATIONAL SPECIALTY LIGHTING 24V LED Globe Light is a Marquee weather condition.	ED Globe Light Style decorative string light designed		DIMMABLE of			
		Speci	fications			
		Electrical	24V DC, .5W			
1.77"	' (45mm)	LED Life	50,000 hours			
		LED Colours	Cool White 6000K Warm White 2700K Red, Blue, Green, Amber "Colors available upon request.			
		Lumens	50 lumens			
		Efficacy	100lm/w			
		Cable	PVC Black SF			
			16AWG outdo			
	Operating	-25°C to 65°C	;			
(—) / 2.76" (70mm)		Temperature	(= 0) ((= 0) ()			
$\mathbf{\lambda}$		Maximum length	150' (45.6M)	100 1		
			Not to exceed			
		Wiring	Directly wired to class 2, 24V power supply			
		Dower Supplie				
		Power Supplie				
		Dimmable Indoor/C	outdoor	Max # of Globes		
		TRE24L40DC	40 Watts	80		
	↓	TRE24L96DC	96 Watts	180		
		Non Dimmable Inde	oor/Outdoor			
		LEDDR-24-120W	120 Watts	180*		
Features Applications		*180 on a single tap or 200 on combined two secondary taps Accessories				
Low power consumption	Building outlinesString across patios, walk	MGEC				
 Safe class 2, 24V power supply Field cuttable 	End cap for wire (Bags of 10)					
Multiple lamp spacing available	MGNC Wood nail mounting clip					
Durable construction for indoor	° .					
and outdoor use	MGWC Tie wrap for mounting to wire					
 Available in Cool White and 				ST16W		
Warm White• Window decorations• Optional Red, Blue, Green, & Amber• Deck and patios• Deck and patios• Deck and patios		Outdoor rated cable for DYI mounting				
		MGTP				
are also available.		Double sided tape (bag of 50 pieces)				
Ordering Code:	Globe Light spare lamp code:	Outdoor Rated Cable				
Spacing 12" Standard Color MGST - 12 - WW - Warm White CW - Cool White R - Red BL - Blue G - Green	Color MGST - Color WW - Warm White CW - Cool White R - Red BL - Blue G - Green	ST16W for attached Globe Light Lamp Assemblies				
AM - Amber	AM - Amber					
Project Type						
Date	Contact					
Notes						
National Specialty Lighting www.nslusa.com 🕿 800-527-4358 📑 800-527-4358 🔀 nslsales@nslusa.com						