

A 3D perspective diagram of a square frame. The frame is composed of two concentric square outlines. The outer square has a side length of 12 inches, indicated by a dimension line at the bottom right. The inner square is smaller, creating a channel. The height of the frame, shown on the right side, is 1 inch, indicated by a vertical dimension line.

**Specifications and dimensions subject to change without notice.*

- Driver on Board Technology, provides a 120V alternating current source and eliminates the need for traditional LED driver
- Quick & easy to install on standard junction box, ceiling mount with mounting plate
- Die-cast aluminum housing
- Smooth and continuous dimming, dimmable with most standard dimmers
- Rated for 50,000 hours
- No light bulbs to replace or dispose
- Instant full brightness (including in sub-zero temperatures)
- 80+ CRI
- cETLus listed for wet locations
- 5 year limited warranty are powder coat painted and available in the following finishes: White Gloss Enamel (WH), Bronze (BZ), Brushed Nickel (BN) and Black (BK)

Electrical	Input: AC 100 – 120V 22W
Power Factor	0.95
LEDs	Epistar
LED Life	50,000 hours
Lumen Output WW = Warm White NW = Neutral White	1800 WW, 1850 NW
Lumen Efficacy (LPW) WW = Warm White NW = Neutral White	82 WW, 84 NW
Color Temperature	Warm White 3000K Neutral White 4000K
CRI	≥80
Appearance Size (L x W x H)	12" x 12" x 1" (305mm x 305mm x 25mm)
Approvals	cETLus listed for wet locations, Energy Star rated

LVLDL - SS - 12 - LED Color Trim Finish
 WW = Warm White (3000K) WH = White
 NW = Neutral White (4000K) BK = Black
 BN = Brushed Nickel

Project		Type	
Date		Contact	
Notes			