



**Product
Catalog**
2024

Product Categories at a Glance

Linear Lighting

Strip Series
120V eStrip
eStrip
Neon Flex
String Lights
Wall Washer

Under Cabinet Lighting

Landscape Lighting

Flood and Spot Lights
Pathway Lights
Wall and Deck Lights
In Ground Lights
Transformers and Accessories

Down Lighting

Thin Lines
Regressed
Gimbal
Surface Mount / Decorative
T-Edge Lights
Fire Rated

Industrial Lighting

Drivers and Controllers

Looking for something specific? Click the NSL logo in the top right corner to access the [Appendix](#) for a detailed category breakdown and item locations.











Why NSL?

At National Specialty Lighting (NSL), we’ve built a foundation of trust and innovation over the past 35 years, dedicated to illuminating spaces with state-of-the-art lighting technology.

Here’s how we make a difference:

- **Your Needs First:** Our product catalog has grown over the years to better cater to your diverse lighting requirements, ensuring you always find what you need.
- **Unmatched Value:** We pride ourselves on offering competitive prices without compromising quality, providing exceptional value for your investment.
- **Peace of Mind:** Our products are backed by substantial warranty support, giving you a seamless and worry-free lighting experience.
- **Custom Displays:** With a variety of [POP display options](#), we make it easy for you to highlight your lighting selections effectively.

Featured Logos/Symbols

 Intertek’s ETL Certified	 Energy Star Certified	 CCT
 cULus Certified	 Wet Location Listed	 RGB
 DLC Certified	 Wattage Adjustable	 Dimmable
 120 Volts of AC Power		



Linear Lighting

High Density, High Power Indoor



Ideal for display cabinets needing high illumination.
Can be used as a wall grazer offering great vertical illumination.


FEATURES

- 1 Bin
- 2 Step MacAdam Ellipse
- 3oz PCB board
- 3M Adhesive
- 50,000 hours life
- High brightness 3528 Epistar LEDs
- Field cuttable
- Low power consumption
- Available in 16' (5m) and 100' (30.48m) spools (custom cuts available)
- 16' spools come with 6Ft pre-soldered power feeds
- Safe, 24V class 2 power supplies (sold separately)
- Fully dimmable with dimmable power supplies (sold separately)
- 6 years limited warranty

APPLICATIONS

- Aisle and stairway lighting
- Cabinet and cove lighting
- Back lighting
- Showcase lighting
- Linear decorative lighting

SPECIFICATIONS		
Product Code		LTP-XX-YY-HD-H90 (XX: Length in feet; YY: Color temperature)
Electrical	Input Voltage	24V DC
	Power Consumption	5.8W/Ft
Specs	Color Temperature	2700/3000/4000/6500K
	CRI	90+
	Lumen Output	450 Lumens per ft 3000K; 468 Lumens per ft 4000K; 514 Lumens per ft 6500K
	Efficacy	77 LPW 3000K; 80 LPW 4000K; 88 LPW 6500K
	Dimmable	Yes
	Beam Angle	120°
LED	Type	High Brightness 3528 Epistar LEDs
	Life Span	50,000 Hours
	Spacing	1" (25mm)
	# per foot (304mm)	72
Design	Dimensions (Inches)	.39" W
	Dimensions (Millimeters)	10mm W
	Max Single Run Length	16Ft
	Custom Cuttable	1" (25mm)
	Approved Location	Indoor
Warranty		6 years
Approvals		cETLus




PRODUCT CODES

XX: Length in feet; YY: Color temperature

16Ft spools LTP - 16 - YY - HD - H90	100Ft spools LTP - 100 - YY - HD - H90	Custom cuts LTP - XX - YY - HD - H90
LED Color 2700K 3000K 4000K 6500K	LED Color 2700K 3000K 4000K 6500K	LED Color 2700K 3000K 4000K 6500K


ACCESSORIES



LTP-001-HD-HP-6
72" Power feed connector for high density indoor



LMSII-001
Terminal block and junction box for connection to additional lengths of power cable if needed



LTP-010-S
Clear PVC mounting "U" channel



LV-SPIR-1CH-LV
PIR Motion Sensor, 1 Channel, 24V DC
NOTE: To be used with non dimmable drivers only

NOTE: See page 36-37 for the complete range of aluminum extrusions.

INDOOR/OUTDOOR DIMMABLE DRIVERS


- TRE24L40DC**
Max recommended load 36W or 6' LED Strip, min 8W or 2' LED Strip
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)
- TRE24L96DC**
Max recommended load 90W or 16' LED Strip, min 8W or 2' LED Strip
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

NON DIMMABLE DRIVERS

- LEDDR-24-120W**
Indoor/Outdoor driver
Max. recommended load 90W or 20' (6.1m) per single tap, 120W or 27' (8.23m) combined two secondary taps.
120W hardwire
Input: 100 - 240V AC
Output: 24V DC
10" x 3 3/8" x 3 3/16" (254 x 85.7 x 80.9mm)

High Density, Low Power Indoor

Suitable for display cabinets and applications needing lower but even illumination.




FEATURES

- 1 Bin
- 2 Step MacAdam Ellipse
- 3oz PCB board
- 3M Adhesive
- 50,000 hours life
- High brightness 5060 SMD LEDs
- Field cuttable
- Low power consumption
- Available in 16' (5m) and 100' (30.48m) spools (custom cuts available)
- Safe, 24V class 2 power supplies (sold separately)
- Fully dimmable with dimmable power supplies (sold separately)
- 16' spools come with 6 ft. pre-soldered power feeds
- 6 year limited warranty

APPLICATIONS

- Aisle and stairway lighting
- Cabinet and cove lighting
- Back lighting
- Showcase lighting
- Linear decorative lighting

SPECIFICATIONS		
Product Code		LTP-XX-YY-HD-LP-H90 (XX: Length in feet; YY: Color temperature)
Electrical	Input Voltage	24V DC
	Power Consumption	2.9W/Ft
Specs	Color Temperature	2700/3000/4000/6500K
	CRI	90+
	Lumen Output	225 Lumens per ft 3000K; 234 Lumens per ft 4000K; 257 Lumens per ft 6500K
	Efficacy	77 LPW 3000K; 80 LPW 4000K; 88 LPW 6500K
	Dimmable	Yes
	Beam Angle	120°
LED	Type	High Brightness 3528 Epistar LEDs
	Life Span	50,000 Hours
	Spacing	8.3mm
	# per foot (304mm)	36
Design	Dimensions (Inches)	31" W
	Dimensions (Millimeters)	0 8mm W
	Max Single Run Length	31Ft
	Custom Cuttable	2" (50mm)
	Approved Location	Indoor
Warranty		6 years
Approvals		cETLus



PRODUCT CODES

XX: Length in feet; YY: Color temperature

16Ft spools
LTP - 16 - YY - HD - LP - H90

LED Color
2700K
3000K
4000K
6500K

100Ft spools
LTP - 100 - YY - HD - LP - H90

LED Color
2700K
3000K
4000K
6500K

Custom cuts
LTP - XX - YY - HD - LP - H90

LED Color
2700K
3000K
4000K
6500K

ACCESSORIES

LTP-001-HD-6
72" Power feed connector for high density indoor

LTP-002-HD
In-line connector for high density indoor

LTP-STP-HD-6IN
6" In-line connector for high density indoor

LMSII-001
Terminal block and junction box for connection to additional lengths of power cable if needed

LTP-010-S
Clear PVC mounting "U" channel

LV-SPIR-1CH-LV
PIR Motion Sensor, 1 Channel, 24V DC
NOTE: To be used with non dimmable drivers only

NOTE: See page 36-37 for the complete range of aluminum extrusions.

INDOOR/OUTDOOR DIMMABLE DRIVERS

TRE24L40DC
Max recommended load 36W or 12' LED Tape, min 8W or 3' LED Tape
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)


TRE24L96DC
Max recommended load 90W or 31' LED Tape, min 8W or 3' LED Tape
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

NON DIMMABLE DRIVERS

LEDDR-24-120W
Indoor/Outdoor driver
Max. recommended load 90W or 31' (9.4m) per single tap, 120W or 41' (12.5m) combined two secondary taps.
120W hardwire
Input: 100 - 240V AC
Output: 24V DC
10" x 3 3/8" x 3 3/16" (254 x 85.7 x 80.9mm)

CCT Indoor

Where applications demand a greater dynamic range within the White Light Spectrum.
Hospitality, retail, residential and commercial.




FEATURES

- 50,000 hours life
- High brightness 3528 SMD LEDs
- Field cuttable
- Low power consumption
- Available in 16' (5M) spools
- 16' spools come with 6 ft. pre-soldered power feeds
- Safe, 24V class 2 power supplies (sold separately)
- Controller sold separately
- 6 year limited warranty

APPLICATIONS

- Aisle and stairway lighting
- Cabinet and cove lighting
- Back lighting
- Showcase lighting
- Linear decorative lighting


SPECIFICATIONS		
Product Code		LTP-16-CCT-H90
Electrical	Input Voltage	24V DC
	Power Consumption	5.8W/Ft
Specs	Color Temperature	2500K-7000K
	CRI	90+
	Lumen Output	261 Lumens per ft 3000K; 383 Lumens per ft 7000K
	Efficacy	77 LPW 3000K, 80 LPW 4000K, 88 LPW 6500K
	Dimmable	No
	Beam Angle	120°
LED	Type	High Brightness 3528 SMD LEDs
	Life Span	50,000 Hours
	Spacing	8.3mm
	# per foot (304mm)	36
Design	Dimensions (Inches)	.39" W
	Dimensions (Millimeters)	10mm W
	Max Single Run Length	16Ft
	Custom Cuttable	2" (50mm)
	Approved Location	Indoor
Warranty	6 years	
Approvals	cETLus	




PRODUCT CODES

16Ft spools
LTP - 16 - CCT - H90

ACCESSORIES




LTP-001-CCT-6
72" Power feed connector for CCT indoor. Add "-O" for opposite end.



LTP-002-CCT
In-line connector for CCT series indoor



LTP-STP-CCT-6IN
6" (15cm) in-line connector for CCT Adjust



LTP-010-S
Clear PVC mounting "U" channel



LT-WIFI-AMP
WiFi Signal Amplifier for RGB, RGBW, CCT



LT-WIFI-CTRL
3 IN 1 LED Strip Controller (WiFi+2.4G)



LT-WIFI-RM
4-Zone RGB+CCT Remote

NOTE: See page 36-37 for the complete range of aluminum extrusions.

NON DIMMABLE DRIVERS

LEDDR-24-120W
Indoor/Outdoor driver
16' (4.88m) per single tap, 20' (6.1m) combined two secondary taps. 120W hardwire
Input: 100 - 240V AC
Output: 24V DC
10" x 3 3/8" x 3 3/16" (254 x 85.7 x 80.9mm)

COB Indoor

The COB indoor lights are designed for optimal performance, delivering uniform lighting ideal for a variety of settings including commercial spaces, retail environments, and homes.




FEATURES

- 1 Bin
 - 2 Step MacAdam Ellipse
 - 3oz PCB board
 - 3M Adhesive
 - Field cuttable every 50mm (2")
 - Low power consumption
 - Smooth luminance - no hot spots
 - Available in 20' (6.1m) and 100' (30.48m) spools (custom cuts available)
- 20' spools come with 6Ft pre-soldered power feeds
 - Safe, 24V DC operation
 - Fully dimmable with dimmable power supplies (sold separately)
 - 6 years limited warranty

APPLICATIONS

- Aisle and stairway lighting
- Cabinet and cove lighting
- Back lighting
- Showcase lighting
- Linear decorative lighting

SPECIFICATIONS		
Product Code		LTP-XX-YY-COB-H90 and LTP-XX-YY-COB (XX: Length in feet; YY: Color temperature)
Electrical	Input Voltage	24V DC
	Power Consumption	4.2W/Ft
Specs	Color Temperature	2700/3000/3500/4000/6500K
	CRI	90+ for white color temperatures
	Lumen Output	315 Lumens per ft 2700K; 319 Lumens per ft 3000K; 328 Lumens per ft 3500K;
		336 Lumens per ft 4000K; 374 Lumens per ft 6500K
	Efficacy	75 LPW 2700K; 76 LPW 3000K; 78 LPW 3500K; 80 LPW 4000K; 89 PLW 6500K
	Dimmable	Yes
	Beam Angle	120°
LED	Type	Chip on Board
	Life Span	50,000 Hours
	Spacing	2mm
	# per foot (304mm)	91
Design	Dimensions (Inches)	.39" W
	Dimensions (Millimeters)	10mm W
	Max Single Run Length	20Ft
	Custom Cuttable	2" (50mm)
	Approved Location	Indoor
Warranty		6 years
Approvals		cETLus




PRODUCT CODES

XX: Length in feet; YY: Color temperature




ACCESSORIES



LTP-001-HD-HP-6
72" Power feed connector for CCT indoor. Add "-O" for opposite end.



LMSII-001
Terminal block and junction box for connection to additional lengths of power cable if needed



LTP-010-S
Clear PVC mounting "U" channel



LV-SPIR-1CH-LV
PIR Motion Sensor, 1 Channel, 24V DC
NOTE: To be used with non dimmable drivers only

NOTE: See page 36-37 for the complete range of aluminum extrusions.

INDOOR/OUTDOOR DIMMABLE DRIVERS

NON DIMMABLE DRIVERS

TRE24L40DC
Max 8.6' (2.6m)
Min 8 Watts, 1.9'(0.57M) LED COB Strip
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

TRE24L96DC
Max 21.4' (6.5m)
Min 8 Watts, 1.9'(0.57m) LED COB Strip
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

LEDDR-24-120W
Indoor/Outdoor driver
Max 21.4' (6.5m) per single tap
Max 28' (8.5m) combined 2 secondary taps
Input: 100 - 240V AC
Output: 24V DC
10" x 3 3/8" x 3 3/16" (254 x 85.7 x 80.9mm)

Dim to Warm

Suitable for both hospitality and residential applications creating an inviting atmosphere.




FEATURES

- 1 Bin
- 2 Step MacAdam Ellipse
- 3oz PCB board
- 3M Adhesive
- 50,000 hours life
- Field cuttable every 50mm (2")
- Low power consumption
- Auto Warm-dim technology
- Available in 16' (5m) and 100' (30.48m) spools (custom cuts available)
- 16' spools come with 6Ft pre-soldered power feeds
- Safe, 24V DC operation
- Dim-to-warm: 1800k to 3000K
- No special controllers required
- 6 years limited warranty

APPLICATIONS

- Aisle and stairway lighting
- Cabinet and cove lighting
- Back lighting
- Showcase lighting
- Linear decorative lighting

SPECIFICATIONS		
Product Code		LTP-XX-WW-DIM-H90 (XX: Length in feet; WW: Warm white)
Electrical	Input Voltage	24V DC
	Power Consumption	5.5W/Ft
Specs	Color Temperature	1800-3000K
	CRI	90+
	Lumen Output	449LM/Ft
	Efficacy	82 LPW
	Dimmable	Yes
	Beam Angle	120°
LED	Type	2835 LEDs
	Life Span	50,000 Hours
	Spacing	2mm
	# per foot (304mm)	240
Design	Dimensions (Inches)	.39" W
	Dimensions (Millimeters)	10mm W
	Max Single Run Length	16Ft
	Custom Cuttable	2" (50mm)
	Approved Location	Indoor
Warranty		6 years
Approvals		cETLus



PRODUCT CODES

XX: Length in feet; WW: Warm white

16Ft spools

LTP - 16 - WW - DIM - H90


100Ft spools

LTP - 100 - WW - DIM - H90

Custom cuts

LTP - XX - WW - DIM - H90

ACCESSORIES




LTP-001-HD-HP-6

72" Power feed connector for high density indoor



LMSII-001

Terminal block and junction box for connection to additional lengths of power cable if needed



LTP-010-S

Clear PVC mounting "U" channel

NOTE: See page 36-37 for the complete range of aluminum extrusions.

INDOOR/OUTDOOR DIMMABLE DRIVERS

TRE24L40DC


Max 6.5' (1.98m)
Min 8 Watts, 1.45' (0.44m)
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

TRE24L96DC

Max 16' (5m)
Min 8 Watts, 1.45' (0.44m)
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

High Efficacy Indoor

One of the highest lumen output solutions, for those applications needing high illumination and great color rendering.




FEATURES

- 1 Bin
- 2 Step MacAdam Ellipse
- 3oz PCB board
- 3M Adhesive
- 50,000 hours life
- Field cuttable every 1.3"
- Low power consumption
- Available in 16' (5m) and 100' (30.48m) spools (custom cuts available)
- 16' spools come with 6Ft pre-soldered power feeds
- Safe, 24V DC operation
- Fully dimmable with dimmable power supplies (sold separately)
- 6 years limited warranty

APPLICATIONS

- Aisle and stairway lighting
- Cabinet and cove lighting
- Back lighting
- Showcase lighting
- Linear decorative lighting

SPECIFICATIONS		
Product Code		LTP-XX-YY-HE-H90 (XX: Length in feet; YY: Color temperature)
Electrical	Input Voltage	24V DC
	Power Consumption	5.1W/Ft
Specs	Color Temperature	2700/3000/3500/4000/6500K
	CRI	90+
	Lumen Output	508 Lumens per ft 2700K; 512 Lumens per ft 3000K; 527 Lumens per ft 3500K; 540 Lumens per ft 4000K; 586 Lumens per ft 6500K
	Efficacy	100 LPW 2700K; 100 LPW 3000K; 103 LPW 3500K; 106 LPW 4000K; 115 LPW 6500K
	Dimmable	Yes
	Beam Angle	120°
LED	Type	High Brightness 2835 LEDs
	Life Span	50,000 Hours
	Spacing	4mm
	# per foot (304mm)	73
Design	Dimensions (Inches)	.4" W
	Dimensions (Millimeters)	10mm W
	Max Single Run Length	16Ft
	Custom Cuttable	1.3" (33mm)
	Approved Location	Indoor
Warranty		6 years
Approvals		cETLus



PRODUCT CODES

XX: Length in feet; YY: Color temperature

16Ft spools

LTP - 16 - YY - HE - H90

LED TAPE LIGHT
High Efficacy,
Indoor

LED Color
2700K
3000K
3500K
4000K
6500K

100Ft spools

LTP - 100 - YY - HE - H90

LED TAPE LIGHT
High Efficacy,
Indoor

LED Color
2700K
3000K
3500K
4000K
6500K


Custom Cut

LTP - XX - YY - HE - H90

LED TAPE LIGHT
High Efficacy,
Indoor

LED Color
2700K
3000K
3500K
4000K
6500K

ACCESSORIES



LTP-001-HD-HP-6
72" Power feed connector
for high density indoor



LMSII-001
Terminal block and junction
box for connection to
additional lengths of power
cable if needed



LTP-010-S
Clear PVC mounting
"U" channel



LV-SPIR-1CH-LV
PIR Motion Sensor, 1
Channel, 24V DC
NOTE: To be used with non
dimmable drivers only

NOTE: See page 36-37 for the complete range of aluminum extrusions.

INDOOR/OUTDOOR DIMMABLE DRIVERS

NON DIMMABLE DRIVERS

TRE24L40DC

Max 7' (2.1m)
Min 8 Watts, 1.5'(0.45M) LED High Efficacy Strip
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

TRE24L96DC

Max 17.6' (5.3m)
Min 8 Watts, 1.5'(0.45m) LED High Efficacy Strip
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

LEDDR-24-120W

Indoor/Outdoor driver
Max 17.6 (5.3m) per single tap
Max 23' (7m) combined 2 secondary taps
Input: 100 - 240V AC
Output: 24V DC
10" x 3 3/8" x 3 3/16" (254 x 85.7 x 80.9mm)

High Power Indoor

Suitable for high ceiling coves or areas that require higher illumination. Commercial, retail, hospitality and residential applications.



FEATURES

- 1 Bin
- 2 Step MacAdam Ellipse
- 3oz PCB board
- 3M Adhesive
- 50,000 hours life
- High brightness 5060 SMD LEDs
- Field cuttable
- Low power consumption
- Available in 20' (6.1m) and 100' (30.48m) spools (custom cuts available)
- Safe, 24V class 2 power supplies (sold separately)
- Fully dimmable with dimmable power supplies (sold separately)
- 20' spools come with 6 ft. pre-soldered power feeds
- 6 years limited warranty



APPLICATIONS

- Aisle and stairway lighting
- Cabinet and cove lighting
- Back lighting
- Showcase lighting
- Linear decorative lighting


SPECIFICATIONS		
Product Code		LTP-XX-YY-H90 and LTP-XX-YY (XX: Length in feet; YY: Color temperature)
Electrical	Input Voltage	24V DC
	Power Consumption	4.3W/Ft
Specs	Color Temperature	2700/3000/3500/4000/6500K
	CRI	90+ [Note: For LTP-XX-YY series, the CRI is 80]
	Lumen Output	280 Lumens per ft 2700K; 285 Lumens per ft 3000K; 293 Lumens per ft 3500K; 300 Lumens per ft 4000K; 325 Lumens per ft 6500K
	Efficacy	65 LPW 2700K; 66 LPW 3000K; 68 LPW 3500K; 70 LPW 4000K; 75 LPW 6500K
	Dimmable	Yes
	Beam Angle	120°
LED	Type	High Brightness 5060 SMD LEDs
	Life Span	50,000 Hours
	Spacing	16mm
	# per foot (304mm)	18
Design	Dimensions (Inches)	.39" W
	Dimensions (Millimeters)	10mm W
	Max Single Run Length	20Ft
	Custom Cuttable	1.3" (33mm)
	Approved Location	Indoor
Warranty		6 years
Approvals		cETLus

PRODUCT CODES

XX: Length in feet; YY: Color temperature



ACCESSORIES



LTP-001-6R
72" Power feed connector for single color indoor. Add "-L" to code for opposite end, add "-CM" for through wall connections.



LTP-002
In-line connector for CCT series indoor



LTP-010-S
Clear PVC mounting "U" channel



LTP-001-12R
12' (144") Power feed connector for single color indoor




LTP-STP-6IN
5.9" (15cm)
LTP-STP-2IN
2"(5cm)



LMSII-001
Terminal block and junction box for connection to additional lengths of power cable if needed



LTP-003-6DC
DC connector for LED strip series with 6" wire and DC connector



LTP-STP-2
2'(61cm)
LTP-STP-12
12'(3.65m)



LV-SPIR-1CH-LV
PIR Motion Sensor, 1 Channel, 24V DC
NOTE: To be used with non dimmable drivers only

NOTE: See page 36-37 for the complete range of aluminum extrusions.

DIMMABLE DRIVERS

TRE24L40DC
Max recommended load 36W or 8' LED Strip, min 8W or 2' LED Strip
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

TRE24L96DC
Max recommended load 90W or 20' LED Strip, min 8W or 2' LED Strip
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

NON DIMMABLE DRIVERS

LEDDR-24-120W
Indoor/Outdoor driver
Max. recommended load 90W or 20' (6.1m) per single tap, 120W or 27' (8.23m) combined two secondary taps.
120W hardwire
Input: 100 - 240V AC
Output: 24V DC
10" x 3 3/8" x 3 3/16" (254 x 85.7 x 80.9mm)

High Power Outdoor

Exterior rated suitable for those commercial, retail and hospitality applications requiring higher illumination.



FEATURES


- 1 Bin
- 2 Step MacAdam Ellipse
- 3oz PCB board
- 3M Adhesive
- 50,000 hours life
- High brightness 5060 SMD LEDs
- Field cuttable
- Low power consumption
- Available in 20' (6.1m) spools
- Safe, 24V class 2 power supplies (sold separately)
- Fully dimmable with dimmable power supplies (sold separately)
- 6 years limited warranty

APPLICATIONS

- Aisle and stairway lighting
- Cabinet and cove lighting
- Back lighting
- Showcase lighting
- Linear decorative lighting


SPECIFICATIONS		
Product Code		LTP-OD-20-YY-H90 (YY: Color temperature)
Electrical	Input Voltage	24V DC
	Power Consumption	4.3W/Ft
Specs	Color Temperature	2700/3000/3500/4000/6500K
	CRI	90+
	Lumen Output	280 Lumens per ft 2700K; 285 Lumens per ft 3000K; 293 Lumens per ft 3500K; 300 Lumens per ft 4000K; 325 Lumens per ft 6500K
	Efficacy	65 LPW 2700K; 66 LPW 3000K; 68 LPW 3500K; 70 LPW 4000K; 75 LPW 6500K
	Dimmable	Yes
	Beam Angle	120°
LED	Type	High Brightness 5060 SMD LEDs
	Life Span	50,000 Hours
	Spacing	16mm
	# per foot (304mm)	18
Design	Dimensions (Inches)	.39" W
	Dimensions (Millimeters)	10mm W
	Max Single Run Length	20Ft
	Custom Cuttable	4"
	Approved Location	Outdoor
Warranty		6 years
Approvals		cETLus

NOTE: Outdoor TAPE LIGHT comes with liquid-tight connectors pre-installed on both ends, so it is necessary to make the cuts starting from extremities. Cut pieces can be terminated, but not joined together.



PRODUCT CODES

YY: Color temperature




ACCESSORIES




LTP-001-OD-6FT
72" Power feed connector
for single color outdoor



LV-FS-MC-004
Mounting clips



LV-FS-EC-001
End caps



LTP-010-S
Clear PVC mounting
"U" channel

NOTE: See page 36-37 for the complete range of aluminum extrusions.

INDOOR/OUTDOOR DIMMABLE DRIVERS

NON DIMMABLE DRIVERS

TRE24L40DC
Max recommended load 36W or 8' LED Tape,
min 8W or 2' LED Tape
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

TRE24L96DC
Max recommended load 90W or 20' LED Tape,
min 8W or 2' LED Tape
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

NOTE: For outdoor installations, please add E-KO-SR strain relief (2pcs/driver).

LEDDR-24-120W
Indoor/Outdoor driver
Max. recommended load 90W or 20' (6.1m) per single tap,
120W or 27' (8.23m) combined two secondary taps.
120W hardwire
Input: 100 - 240V AC
Output: 24V DC
10" x 3 3/8" x 3 3/16" (254 x 85.7 x 80.9mm)

High Power, RGB Indoor

Excellent choice for dynamic environments such as cinemas, retail and hospitality needing higher illumination.




FEATURES

- 50,000 hours life
- High brightness 5060 SMD LEDs
- Field cuttable
- Low power consumption
- Available in 20' (6.1m) and 100' (30.48m) spools (custom cuts available)
- 20' spools come with 6 ft. pre-soldered power feeds
- Safe, 24V class 2 power supplies (sold separately)
- Controllers sold separately
- 6 years limited warranty

APPLICATIONS

- Aisle and stairway lighting
- Cabinet and cove lighting
- Back lighting
- Showcase lighting
- Linear decorative lighting

SPECIFICATIONS		
Product Code		LTP-XX-RGB (XX: Length in feet)
Electrical	Input Voltage	24V DC
	Power Consumption	4.3W/Ft
Specs	Color Temperature	RGB
	CRI	80+
	Dimmable	Yes
	Beam Angle	120°
LED	Type	High Brightness 5060 SMD LEDs
	Life Span	50,000 Hours
	Spacing	16mm
	# per foot (304mm)	18
Design	Dimensions (Inches)	.39" W
	Dimensions (Millimeters)	10mm W
	Max Single Run Length	20Ft
	Custom Cuttable	4"
	Approved Location	Indoor
Warranty	6 years	
Approvals	cETLus	



PRODUCT CODES ————— XX: Length in feet; YY: Color temperature

20Ft spools	100Ft spools	Custom cuts
LTP - 20 - RGB	LTP - 100 - RGB	LTP - XX - RGB


ACCESSORIES



LTP-001-RGB-6R
72" Power feed connector for RGB indoor. Add "-L" for opposite end.



LTP-002-RGB
In-line connector for RGB indoor



LTP-010-S
Clear PVC mounting "U" channel



LTP-001-RGB-6IN
6" In-line connector for RGB indoor



LT-WIFI-RM
4-Zone RGB+CCT Remote



LT-WIFI-CTRL
3 IN 1 LED Strip Controller (WiFi+2.4G)



LT-WIFI-AMP
WiFi Signal Amplifier for RGB, RGBW, CCT

LTP-001-RGB-2IN
2" In-line connector for RGB indoor

NOTE: See page 36-37 for the complete range of aluminum extrusions.

NON DIMMABLE DRIVERS

LEDDR-24-120W
Indoor/Outdoor driver
Max. recommended load 90W or 20' (6.1m) per single tap, 120W or 27' (8.23m) combined two secondary taps.
120W hardwire
Input: 100 - 240V AC
Output: 24V DC
10" x 3 3/8" x 3 3/16" (254 x 85.7 x 80.9mm)

High Power, RGB Outdoor

Great for enhancing outdoor spaces with a dynamic look. Suitable for hospitality, retail and commercial environments.



FEATURES


- 50,000 hours life
- High brightness 5060 SMD LEDs
- Field cuttable
- Low power consumption
- Available in 20' (6.1m) spools
- Safe, 24V class 2 power supplies (sold separately)
- 6 years limited warranty

APPLICATIONS

- Aisle and stairway lighting
- Cabinet and cove lighting
- Back lighting
- Showcase lighting
- Linear decorative lighting

SPECIFICATIONS		
Product Code		LTP-OD-20-RGB
Electrical	Input Voltage	24V DC
	Power Consumption	4.3W/Ft
Specs	Color Temperature	RGB
	CRI	80+
	Dimmable	Yes
	Beam Angle	120°
LED	Type	High Brightness 5060 SMD LEDs
	Life Span	50,000 Hours
	Spacing	16mm
	# per foot (304mm)	18
Design	Dimensions (Inches)	.39" W
	Dimensions (Millimeters)	10mm W
	Max Single Run Length	20Ft
	Custom Cuttable	4"
	Approved Location	Outdoor
Warranty	6 years	
Approvals	cETLus	

NOTE: Outdoor TAPE LIGHT comes with liquid-tight connectors pre-installed on both ends, so it is necessary to make the cuts starting from extremities. Cut pieces can be terminated, but not joined together.



PRODUCT CODES

20Ft spools
LTP - OD - 20 - RGB


ACCESSORIES



LTP-RGB-001-OD-6FT
72" Power feed connector for RGB outdoor



LV-FS-MC-004
Mounting clips



LV-FS-EC-001
End caps



LTP-010-S
Clear PVC mounting "U" channel



LT-WIFI-RM
4-Zone RGB+CCT Remote



LT-WIFI-CTRL
3 IN 1 LED Strip Controller (WiFi+2.4G)



LT-WIFI-AMP
WiFi Signal Amplifier for RGB, RGBW, CCT

NOTE: See page 36-37 for the complete range of aluminum extrusions.

NON DIMMABLE DRIVERS

LEDDR-24-120W
Indoor/Outdoor driver
Max. recommended load 90W or 20' (6.1m) per single tap, 120W or 27' (8.23m) combined two secondary taps.
120W hardwire
Input: 100 - 240V AC
Output: 24V DC
10" x 3 3/8" x 3 3/16" (254 x 85.7 x 80.9mm)

High Power, RGBW Indoor

Offers dynamic range of color and dedicated white for greater versatility suitable for all market segments.




FEATURES

- 50,000 hours life
- High brightness 5050 SMD LEDs
- Field cuttable
- Low power consumption
- Available in 20' (6.1m) and 100' (30.48m) spools (customcuts available)
- RGB color change plus 3000K, 4000K and 6500K color temperatures
- 20' spools come with 6 ft. pre-soldered power feeds
- Safe, 24V class 2 power supplies (sold separately)

APPLICATIONS

- Aisle and stairway lighting
- Cabinet and cove lighting
- Back lighting
- Showcase lighting
- Linear decorative lighting

SPECIFICATIONS		
Product Code		LTP-XX-RGBYY-H90 (XX: Length in feet; YY: Color temperature)
Electrical	Input Voltage	24V DC
	Power Consumption	4.3W/Ft
Specs	Color Temperature	RGBW
	CRI	90+
	Beam Angle	120°
LED	Type	High Brightness 5050 SMD LEDs
	Life Span	50,000 Hours
	Spacing	16mm
	# per foot (304mm)	18
Design	Dimensions (Inches)	.47" W
	Dimensions (Millimeters)	12mm W
	Max Single Run Length	20Ft
	Custom Cuttable	4"
	Approved Location	Indoor
Warranty	6 years	
Approvals	cETLus	



PRODUCT CODES ————— XX: Length in feet; YY: Color temperature

20Ft spools
LTP - 20 - RGBYY - H90

LED Color
3000K
4000K
6500K

100Ft spools
LTP - 100 - RGBYY - H90

LED Color
3000K
4000K
6500K

Custom Cut
LTP - XX - RGBYY - H90

LED Color
3000K
4000K
6500K

ACCESSORIES

LTP-001-RGBW-6
72" Power feed connector for RGBW indoor

LTP-002-RGBW
In-line connector for RGBW indoor

LTP-001-RGBW-6IN
6" In-line connector for RGBW indoor

LT-WIFI-RM
4-Zone RGB+CCT Remote

LT-WIFI-CTRL
3 IN 1 LED Strip Controller (WiFi+2.4G)

LT-WIFI-AMP
WiFi Signal Amplifier for RGB, RGBW, CCT

LT-490A
Signal Amplifier for RGBW

NOTE: See page 36-37 for the complete range of aluminum extrusions.

NON DIMMABLE DRIVERS

LEDDR-24-120W
Indoor/Outdoor driver
Max 17.6 (5.3m) per single tap
Max 23' (7m) combined 2 secondary taps
Input: 100 - 240V AC
Output: 24V DC
10" x 3 3/8" x 3 3/16" (254 x 85.7 x 80.9mm)

Low Power Indoor

Great choice for under cabinet and coves offering subtle lighting effects.



FEATURES

- 1 Bin
- 2 Step MacAdam Ellipse
- 3oz PCB board
- 3M Adhesive
- 50,000 hours life
- High brightness 5060 SMD LEDs
- Field cuttable
- Low power consumption
- Available in 20' (6.1m) and 100' (30.48m) spools (custom cuts available)
- Safe, 24V class 2 power supplies (sold separately)
- Fully dimmable with dimmable power supplies (sold separately)
- 20' spools come with 6 ft. pre-soldered power feeds
- 6 years limited warranty



APPLICATIONS

- Aisle and stairway lighting
- Cabinet and cove lighting
- Back lighting
- Showcase lighting
- Linear decorative lighting


SPECIFICATIONS

Product Code		LTP-XX-YY-H90-LP and LTP-XX-YY-LP (XX: Length in feet; YY: Color temperature)	
Electrical	Input Voltage	24V DC	
	Power Consumption	2.2W/Ft	
Specs	Color Temperature	2700/3000/3500/4000/6500K	
	CRI	90+ [Note: For LTP-XX-YY-LP series, the CRI is 80]	
	Lumen Output	143 Lumens per ft 2700K; 145 Lumens per ft 3000K; 148 Lumens per ft 3500K;	
		150 Lumens per ft 4000K; 165 Lumens per ft 6500K	
	Efficacy	65 LPW 2700K, 66 LPW 3000K, 68 LPW 3500K 70 LPW 4000K, 75 LPW 6500K	
	Dimmable	Yes	
Beam Angle	120°		
LED	Type	High Brightness 5060 SMD LEDs	
	Life Span	50,000 Hours	
	Spacing	32mm	
	# per foot (304mm)	9	
Design	Dimensions (Inches)	.39" W	
	Dimensions (Millimeters)	10mm W	
	Max Single Run Length	90Ft	
	Custom Cuttable	1.3" (33mm)	
	Approved Location	Indoor	
Warranty	6 years		
Approvals	cETLus		

PRODUCT CODES




ACCESSORIES



LTP-001-6R
72" Power feed connector for single color indoor. Add "-L" to code for opposite end, add "-CM" for through wall connections.



LTP-002
In-line connector for CCT series indoor



LTP-010-S
Clear PVC mounting "U" channel



LTP-001-12R
12' (144") Power feed connector for single color indoor.

LTP-STP-6IN
5.9" (15cm)
LTP-STP-2IN
2" (5cm)



LMSII-001
Terminal block and junction box for connection to additional lengths of power cable if needed



LTP-003-6DC
DC connector for LED strip series with 6" wire and DC connector

LTP-STP-2
2' (61cm)
LTP-STP-12
12' (3.65m)

In-line connector for single color indoor



LV-SPIR-1CH-LV
PIR Motion Sensor, 1 Channel, 24V DC
NOTE: To be used with non dimmable drivers only

DIMMABLE DRIVERS

TRE24L40DC

Max recommended load 36W or 16' LED
Strip, min 8W or 4' LED Strip
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

TRE24L96DC

Max recommended load 90W or 40' LED
Strip, min 8W or 4' LED Strip
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

NON DIMMABLE DRIVERS

LEDDR-24-120W

Indoor/Outdoor driver
Max. recommended load 90W or 40' (12.1m) per single tap, 120W or 54' (16.46m) combined two secondary taps.
120W hardware
Input: 100 - 240V AC
Output: 24V DC
10" x 3 3/8" x 3 3/16" (254 x 85.7 x 80.9mm)

Low Power Outdoor

This exterior rated tape offers more subtle illumination approach for commercial, hospitality and residential usage.



LOW POWER SINGLE COLOR LTP-OD-LP SERIES

FEATURES


- 1 Bin
- 2 Step MacAdam Ellipse
- 3oz PCB board
- 3M Adhesive
- 50,000 hours life
- High brightness 5060 SMD LEDs
- Field cuttable
- Low power consumption
- Available in 20' (6.1m) spools
- Safe, 24V class 2 power supplies (sold separately)
- Fully dimmable with dimmable power supplies (sold separately)
- 6 year limited warranty

APPLICATIONS


- Aisle and stairway lighting
- Cabinet and cove lighting
- Back lighting
- Showcase lighting
- Linear decorative lighting

SPECIFICATIONS		
Product Code		LTP-OD-20-YY-H90-LP
Electrical	Input Voltage	24V DC
	Power Consumption	2.2W/Ft
Specs	Color Temperature	2700/3000/3500/4000/6500K
	CRI	90+
	Lumen Output	143 Lumens per ft 2700K; 145 Lumens per ft 3000K; 148 Lumens per ft 3500K; 150 Lumens per ft 4000K; 165 Lumens per ft 6500K
	Efficacy	65 LPW 2700K, 66 LPW 3000K, 68 LPW 3500K 70 LPW 4000K, 75 LPW 6500K
	Dimmable	Yes
	Beam Angle	120°
LED	Type	High Brightness 5060 SMD LEDs
	Life Span	50,000 Hours
	Spacing	1.26" (32mm)
	# per foot (304mm)	9
Design	Dimensions (Inches)	.39" W
	Dimensions (Millimeters)	10mm W
	Max Single Run Length	90Ft
	Custom Cuttable	6.5" (165mm)
	Approved Location	Outdoor
Warranty		6 years
Approvals		cETLus

NOTE: Outdoor TAPE LIGHT comes with liquid-tight connectors pre-installed on both ends, so it is necessary to make the cuts starting from extremities. Cut pieces can be terminated, but not joined together.



PRODUCT CODES




ACCESSORIES



LTP-001-OD-6FT
72" Power feed connector for single color outdoor



LV-FS-MC-004
Mounting clips



LV-FS-EC-001
End caps



LTP-010-S
Clear PVC mounting "U" channel

NOTE: See page 36-37 for the complete range of aluminum extrusions.

INDOOR/OUTDOOR DIMMABLE DRIVERS

TRE24L40DC
Max 7' (2.1m)
Min 8 Watts, 1.5' (0.45M) LED High Efficacy Strip
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

TRE24L96DC
Max recommended load 90W or 16' LED Strip, min 8W or 2' LED Strip
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

NOTE: For outdoor installations, please add E-KO-SR strain relief (2pcs/driver).

NON DIMMABLE DRIVERS

LEDDR-24-120W
Indoor/Outdoor driver
Max. recommended load 90W or 40' (12.1m) per single tap, 120W or 54' (16.46m) combined two secondary taps.
120W hardwire
Input: 100 - 240V AC
Output: 24V DC
10" x 3 3/8" x 3 3/16" (254 x 85.7 x 80.9mm)

Low Power, RGB Indoor

For more subtle approaches within entertainment venues and restaurants.



FEATURES


- 50,000 hours life
- High brightness 5060 SMD LEDs
- Field cuttable
- Low power consumption
- Available in 20' (6.1m) and 100' (30.48m) spools (custom cuts available)
- 20' spools come with 6 ft. pre-soldered power feeds
- Safe, 24V class 2 power supplies (sold separately)
- 6 years limited warranty

APPLICATIONS

- Aisle and stairway lighting
- Cabinet and cove lighting
- Back lighting
- Showcase lighting
- Linear decorative lighting

SPECIFICATIONS

SPECIFICATIONS		
Product Code		LTP-XX-RGB-LP (XX: Length in feet)
Electrical	Input Voltage	24V DC
	Power Consumption	2.2W/Ft
Specs	Color Temperature	RGB
	Dimmable	Yes
	Beam Angle	120°
LED	Type	High Brightness 5060 SMD LEDs
	Life Span	50,000 Hours
	Spacing	32mm
	# per foot (304mm)	9
Design	Dimensions (Inches)	.39" W
	Dimensions (Millimeters)	10mm W
	Max Single Run Length	90Ft
	Custom Cuttable	6.5"
	Approved Location	Indoor
Warranty	6 years	
Approvals	cETLus	



PRODUCT CODES

XX: Length in feet

20Ft spools

LTP - 20 - RGB - LP

100Ft spools

LTP - 100 - RGB - LP

Custom Cuts

LTP - XX - RGB - LP


ACCESSORIES



LTP-001-RGB-6R
72" Power feed connector for RGB indoor. Add "-L" for opposite end.



LTP-002-RGB
In-line connector for RGB indoor



LTP-010-S
Clear PVC mounting "U" channel



LTP-001-RGB-6IN
6" In-line connector for RGB indoor



LT-WIFI-AMP
WiFi Signal Amplifier for RGB, RGBW, CCT



LT-WIFI-RM
4-Zone RGB+CCT Remote



LT-WIFI-CTRL
3 IN 1 LED Strip Controller (WiFi+2.4G)

LTP-001-RGB-2IN
2" In-line connector for RGB indoor

NOTE: See page 36-37 for the complete range of aluminum extrusions.

NON DIMMABLE DRIVERS

LEDDR-24-120W
Indoor/Outdoor driver
Max 17.6 (5.3m) per single tap
Max 23' (7m) combined 2 secondary taps
Input: 100 - 240V AC
Output: 24V DC
10" x 3 3/8" x 3 3/16" (254 x 85.7 x 80.9mm)

Low Power, RGB Outdoor

For those exterior applications requiring a dynamic but subtle approach. Suitable for residential, hospitality, commercial and retail.



FEATURES


- 50,000 hours life
- High brightness 5060 SMD LEDs
- Field cuttable
- Low power consumption
- Available in 20' (6.1m) spools
- Safe, 24V class 2 power supplies (sold separately)
- 6 years limited warranty

APPLICATIONS

- Aisle and stairway lighting
- Cabinet and cove lighting
- Back lighting
- Showcase lighting
- Linear decorative lighting

SPECIFICATIONS		
Product Code		LTP-OD-20-RGB-LP
Electrical	Input Voltage	24V DC
	Power Consumption	2.2W/Ft
Specs	Color Temperature	RGB
	Dimmable	Yes
	Beam Angle	120°
LED	Type	High Brightness 5060 SMD LEDs
	Life Span	50,000 Hours
	Spacing	32mm
	# per foot (304mm)	9
Design	Dimensions (Inches)	.39" W
	Dimensions (Millimeters)	10mm W
	Max Single Run Length	90Ft
	Custom Cuttable	6.5"
	Approved Location	Outdoor
Warranty	6 years	
Approvals	cETLus	

NOTE: Outdoor TAPE LIGHT comes with liquid-tight connectors pre-installed on both ends, so it is necessary to make the cuts starting from extremities. Cut pieces can be terminated, but not joined together.



PRODUCT CODES

20Ft spools
LTP - OD - 20 - RGB - LP


ACCESSORIES




LTP-RGB-001-OD-6FT
72" Power feed connector for RGB outdoor



LV-FS-MC-004
Mounting clips



LV-FS-EC-001
End caps



LTP-010-S
Clear PVC mounting "U" channel



LT-WIFI-RM
4-Zone RGB+CCT Remote



LT-WIFI-CTRL
3 IN 1 LED Strip Controller (WiFi+2.4G)



LT-WIFI-AMP
WiFi Signal Amplifier for RGB, RGBW, CCT

NOTE: See page 36-37 for the complete range of aluminum extrusions.

NON DIMMABLE DRIVERS

LEDDR-24-120W
Indoor/Outdoor driver
Max. recommended load 90W or 40' (12.1m) per single tap, 120W or 54' (16.46m) combined two secondary taps.
120W hardwire
Input: 100 - 240V AC
Output: 24V DC
10" x 3 3/8" x 3 3/16" (254 x 85.7 x 80.9mm)

Extrusions


These are designed to house and protect LED strip lights, enhancing durability and providing a sleek, professional finish. They also help to diffuse light evenly, preventing hotspots and creating a more aesthetically pleasing lighting effect..

LV-ALP2208

Surface mount aluminum extrusion and frosted PC cover




- Product Codes**
LV-ALP2208
LV-ALP2208-2M
- End Caps**
LV-ALP2208-EC (2/bag)
LV-ALP2208-EC-WF (2/bag)
- Mounting Clips**
LV-ALP2208-MC (2/bag)




NOTE: Available in 1m (39") and 2m (78") lengths.

LV-LB-V3-FR

Corner surface mounted aluminum extrusion and frosted PC cover



- Product Code**
LV-LB-V3-FR
- End Caps**
LV-V1/V3-EC (2/bag)
LV-V1/V3-EC-WF (2/bag)
- Mounting Clips**
LV-V1/V3-MC (6/bag)




NOTE: Available in 1m (39").

LV-ALP007

Surface mount aluminum extrusion and frosted PC cover




- Product Codes**
LV-ALP2207
LV-ALP2207-2M
- End Caps**
LV-ALP007-EC (2/bag)
LV-ALP007-EC-WF (2/bag)
- Mounting Clips**
LV-ALP007-MC (6/bag)




NOTE: Available in 1m (39") and 2m (78") lengths.

LV-RD54

Surface mount aluminum extrusion



- Product Codes**
LV-RD54-1M
LV-RD54-2M
- End Caps**
LV-RD54/55-EC (2/bag)
LV-RD54/55-EC-WF (2/bag)
- Mounting Clips**
LV-RD54/55-EC-MC (6/bag)




NOTE: Available in 1m (39") and 2m (78") lengths.

LV-RD55

Recessed aluminum extrusion



- Product Codes**
LV-RD55-1M
LV-RD55-2M
- End Caps**
LV-RD54/55-EC (2/bag)
LV-RD54/55-EC-WF (2/bag)
- Mounting Clips**
LV-RD54/55-EC-MC (6/bag)




NOTE: Available in 1m (39") and 2m (78") lengths.

LV-ALP2908

Recessed aluminum extrusion and frosted PC cover




- Product Codes**
LV-ALP2908
LV-ALP2908-2M
- End Caps**
LV-ALP2908-EC (2/bag)
LV-ALP2908-EC-WF (2/bag)
- Mounting Clips**
LV-ALP2908-MC (2/bag)



NOTE: Available in 1M (39") and 2M (78") lengths.

LV-1401

Closet aluminum extrusion with mounting brackets and frosted PC cover



NOTE: 1M (39") extrusion ships complete with two mounting end caps and one support

120V AC eStrip

An ideal solution for accent lighting in residential, commercial and retail applications, the 120V AC LED eStrip can be easily installed without the need of any additional driver, in indoor and outdoor applications.




FEATURES

- Field cuttable; 120V AC input voltage
- High light efficiency, high PF and high lumens
- Constant current design, overvoltage protection
- Drop current when over temperature to protect product (Max. ambient working temperature: 55°C, light up for no more than 6 hours)
- Dimmable: TRIAC
- No need of a transformer box to change AC to DC; connect with line voltage directly
- Ambient Working Temperature: -20 ~ 42°C (-4 ~ 107°F)
- IP65 PVC extrusion process
- Min.section 4 inch; Max.run 164FT
- With bared power cords on one side, it's more convenient for connecting
- ETL certified
- 5 years warranty indoor use; 3 years warranty outdoor use

APPLICATIONS

- Building outlines
- Signage
- Decks
- Architectural features

SPECIFICATIONS				
Product Code		ES-120V-27K-164FT	ES-120V-30K-164FT	ES-120V-40K-164FT
Electrical	Input Voltage	120V AC		
	Power Consumption	4W/Ft		
Specs	Color Temperature	2700K	3000K	4000K
	Lumen Output	280LM/Ft	300LM/Ft	340LM/Ft
	CRI	90+		
	Dimmable	Yes		
LED	Type	SMD2835		
	Life Span	30,000 Hours		
	Spacing	N/A		
	# per foot (304mm)	18 LEDs		
Design	Dimensions (Inches)	.79" W		
	Dimensions (Millimeters)	20mm W		
	Max Single Run Length	50M (164Ft)		
	Custom Cuttable	Cuttable every 10CM (3 15/16")		
	Approved Location	Indoor/Outdoor		
Warranty	5 years warranty indoor use; 3 years warranty outdoor use			
Approvals	cETLus			



PRODUCT CODES

XX: Length in feet; YY: Color temperature

164 Ft spools
ES - 120V - YY - 164FT

Custom cuts
ES - 120V - YY - XX


LED Color
2700K
3000K
4000K

LED Color
2700K
3000K
4000K

ACCESSORIES



ES-120V-EC
End cap (Indoor & Outdoor)



ES-120V-EXT
4ft Aluminum extrusion




ES-120V-MC
Mounting clips (Bag of 10)



ES-120V-PC
8Ft Power cord



ES-120V-PC-PL
5Ft Power cord with plug



ES-120V-JC-1FT
Jumper, 1Ft

ES-120V-JC-3FT
Jumper, 3Ft

ES-120V-JC-6FT
Jumper, 6Ft

ES-120V-JC-6IN
Jumper, 6"

Low Power eStrip

The Low Power LED eStrip, equipped with 3014 type LEDs, is a versatile linear lighting solution that offers improved brightness and performance



FEATURES

- 40,000 hours life
- Safe low voltage (24V)
- Virtually maintenance free
- Ultra low power consumption
- Available in 40' spools (custom cuts available)
- Crushproof to 100psi
- Field cuttable
- Inter-connectable
- Highly flexible (min. bend radius 1.5")
- Indoor/outdoor use
- Impact resistant
- Dimmable
- 2 years limited warranty

APPLICATIONS

- Building outlines
- Coves
- Stairway and aisle lighting
- Signage
- Backlit panels
- Decks
- Edgelit glow
- Emergency lighting
- Pathway lighting
- Billboards
- Highlighting architectural features
- Over/Under cabinets

SPECIFICATIONS

SPECIFICATIONS		
Product Code		LES-XX-YY (XX: Length in feet; YY: Color temperature)
Electrical	Input Voltage	24V DC
	Power Consumption	0.96W/Ft
Specs	Color Temperature	3000/5800K
	Lumen Output	61 Lumens per ft. 5800K; 55 Lumens per ft. 3000K
	LED Colors	Amber, Red, Blue, Pure Green, 5800K, 3000K
	PVC Body Color	Clear
	Min/Max Surface Temp for Mounting	-40°C - 40°C (-40°F - 104°F)
	Dimmable	Yes
	Beam Angle	120°
LED	Type	N/A
	Life Span	40,000 Hours
	Spacing	1" (25.4mm)
	# per foot (304mm)	12
Design	Dimensions (Inches)	.25 x .5"
	Dimensions (Millimeters)	6 x 12mm
	Max Single Run Length	90Ft
	Custom Cuttable	6" (152.4mm)
Warranty	Approved Location	Indoor/Outdoor
		2 years
Approvals		cETLus

PRODUCT CODES

XX: Length in feet; YY: Color temperature

90Ft spools

LES - 90 - YY

LED eStrip

LED Color

3000K, 5800K, AM - Amber, BL - Blue, PG - Pure Green, RD - Red


Custom cuts

LES - XX - YY

LED eStrip

LED Color

3000K, 5800K, AM - Amber, BL - Blue, PG - Pure Green, RD - Red



ACCESSORIES



LES-001-6BR

Outdoor 6' Power connector for burial connections, 1/4" x 1/2" (6mm x 12mm). Comes with end cap



LES-001-12BR

Outdoor Power connector, with SJTW-2 12 ft wires for burial connections 1/4" x 1/2" (6mm x 12mm) Comes with end cap



LES-STP-2BR

Outdoor 2' Step cord for burial connections



LES-STP-12BR

Outdoor 12' Step cord (shown) for burial connections



LES-FLEX-BR

Outdoor Step cord for burial connections

LES-001-6CL

Indoor 6' Power connector for through wall connections

LES-001-12CL

Indoor 12' Power connector for through wall connections

LES-STP-2CL

Indoor 2' Step cord (shown) for through wall connections

LES-STP-12CL

Indoor 12' Step cord for through wall connections

LES-FLEX-CL

Indoor Step cord (shown) for through wall connections



LMSII-001

Terminal block and junction box for connection to additional lengths of power cable if needed



LES-BFLN

L type connector, 1/4" X 1/2" (6mm x 12mm)



LES-002

In-Line connector set, male and female, 1/4" X 1/2" (6mm x 12mm)



LES-BFTD

T type connector, 1/4" X 1/2" (6 x 12mm), male connector in bottom




LES-003-2

Cutting end cap, 0.25" X 0.5" (6mm x 12mm)



LES-BFTR

T type connector, 1/4" X 1/2" (6 x 12mm), male connector in right or left



LES-005

Wood nail clips, 1/4" X 1/2" (6mm x 12mm)



LES-008

Tie wrap and mounting saddle




LES-BFXN

X type connector, 1/4" X 1/2" (6mm x 12mm)



LES-BFDN

6 x 12mm splice kit (pins, pad and shrink tube)



LES-010


4' plastic mounting channel, indoor use

LES-010-S

Predrilled with screws

LES-010-T

With double sided tape



NN-C10-POLY

For outdoor use

INDOOR/OUTDOOR DIMMABLE DRIVERS

TRE24L40DC

Max 37.5' (11.4m)
Min 8 Watts, 9' LED eStrip (2.7m)
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

TRE24L96DC

Max 90' (27.4m)
Min 8 Watts, 9' LED eStrip (2.7m)
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

NOTE: For outdoor installations, please add E-KO-SR strain relief (2pcs/driver).

NON DIMMABLE DRIVERS

LEDDR-24-120W (Indoor/Outdoor driver)

Max 90' (27.4m) per single tap
Max 120' (36.5m) combined 2 secondary taps
Input: 100 - 240V AC, Output: 24V DC
10" x 3 3/8" x 3 3/16" (254 x 85.7 x 80.9mm)

LES-24-65W

Indoor Plug In Driver
Input: 100-240V AC
Output: 24V DC

High Power eStrip

The High Power LED eStrip is an advanced version that delivers twice the lumen output compared to the standard eSTRIP, enhancing illumination capabilities.



FEATURES

- 40,000 hours life
- Safe low voltage (24V)
- Virtually maintenance free
- Ultra low power consumption
- Available in 40' spools (custom cuts available)
- Crushproof to 100psi
- Field cuttable
- Inter-connectable
- Highly flexible (min. bend radius 1.5")
- Indoor/outdoor use
- Impact resistant
- Dimmable
- 2 years limited warranty

APPLICATIONS

- Building outlines
- Coves
- Stairway and aisle lighting
- Signage
- Backlit panels
- Decks
- Edgelit glow
- Emergency lighting
- Pathway lighting
- Billboards
- Highlighting architectural features
- Over/Under cabinets

SPECIFICATIONS		
Product Code		LES-XX-RGB (XX: Length in feet)
Electrical	Input Voltage	24V DC
	Power Consumption	2.2W/Ft
Specs	Color Temperature	RGB
	Lumen Output	Clear
	LED Colors	-40°C - 40°C (-40°F - 104°F)
	PVC Body Color	Yes
	Min/Max Surface Temp for Mounting	120°
	Dimmable	N/A
	Beam Angle	40,000 Hours
LED	Type	1.3" (33mm)
	Life Span	9
	Spacing	.3" x .6"
	# per foot (304mm)	7.6 x 15mm
Design	Dimensions (Inches)	40Ft
	Dimensions (Millimeters)	8" (198mm)
	Max Single Run Length	Indoor/Outdoor
	Custom Cuttable	6" (152.4mm)
	Approved Location	Indoor/Outdoor
Warranty	2 years	
Approvals	cETLus	

PRODUCT CODES

XX: Length in feet

40Ft spools

LESHP - 40 - YY

HIGH POWER
LED eStrip


LED Color
3000K
5800K

Custom Cuts

LESHP - XX - YY

HIGH POWER
LED eStrip

LED Color
3000K
5800K



ACCESSORIES



LES-001-6BR

Outdoor 6' Power connector for burial connections, 1/4" x 1/2" (6mm x 12mm). Comes with end cap



LES-001-12BR

Outdoor Power connector, with SJTW-2 12 ft wires for burial connections 1/4" x 1/2" (6mm x 12mm) Comes with end cap



LES-STP-2BR

Outdoor 2' Step cord for burial connections



LES-STP-12BR

Outdoor 12' Step cord (shown) for burial connections



LES-FLEX-BR

Outdoor Step cord for burial connections

LES-001-6CL

Indoor 6' Power connector for through wall connections

LES-001-12CL

Indoor 12' Power connector for through wall connections



LMSII-001

Terminal block and junction box for connection to additional lengths of power cable if needed



LES-BFLN

L type connector, 1/4" X 1/2" (6mm x 12mm)



LES-002

In-Line connector set, male and female, 1/4" X 1/2" (6mm x 12mm)



LES-BFTD

T type connector, 1/4" X 1/2" (6 x 12mm), male connector in bottom



LES-003-2

Cutting end cap, 0.25" X 0.5" (6mm x 12mm)




LES-BFTR

T type connector, 1/4" X 1/2" (6 x 12mm), male connector in right or left



LES-005

Wood nail clips, 1/4" X 1/2" (6mm x 12mm)



LES-008

Tie wrap and mounting saddle




LES-BFXN

X type connector, 1/4" X 1/2" (6mm x 12mm)



LES-BFDN

6 x 12mm splice kit (pins, pad and shrink tube)



LES-010


4' plastic mounting channel, indoor use

LES-010-S

Predrilled with screws

LES-010-T

With double sided tape



NN-C10-POLY

For outdoor use

INDOOR/OUTDOOR DIMMABLE DRIVERS

TRE24L40DC

Max 7' (2.1m)
Min 8 Watts, 1.5'(0.45M) LED High Efficacy Strip
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

TRE24L96DC

Max recommended load 90W or 16' LED Strip,
min 8W or 2' LED Strip
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

NOTE: For outdoor installations, please add E-KO-SR strain relief (2pcs/driver).

NON DIMMABLE DRIVERS

LEDDR-24-120W (Indoor/Outdoor driver)

Max 40' (12m) per single tap
Max 54' (16.4m) combined 2 secondary taps
Input: 100 - 240V AC, Output: 24V DC
10" x 3 3/8" x 3 3/16" (254 x 85.7 x 80.9mm)

LES-24-65W

Indoor Plug In Driver
Input: 100-240V AC
Output: 24V DC
4.7" x 2" x 1.3" (119.4 x 50.8 x 33mm)

RGB eStrip

The RGB eSTRIP, featuring RGB LEDs, enables the creation of dramatic color change effects, suitable for building outlines and architectural highlights.



FEATURES

- 40,000 hours life
- Safe low voltage (24V)
- Virtually maintenance free
- Ultra low power consumption
- Available in 40' spools (custom cuts available)
- Crushproof to 100psi
- Field cuttable
- Inter-connectable
- Highly flexible (min. bend radius 1.5")
- Indoor/outdoor use
- Impact resistant
- Dimmable
- 2 years limited warranty

APPLICATIONS

- Building outlines
- Coves
- Stairway and aisle lighting
- Signage
- Backlit panels
- Decks
- Edgelit glow
- Emergency lighting
- Pathway lighting
- Billboards
- Highlighting architectural features
- Over/Under cabinets


SPECIFICATIONS

SPECIFICATIONS		
Product Code		LES-XX-RGB (XX: Length in feet)
Electrical	Input Voltage	24V DC
	Power Consumption	2.2W/Ft
Specs	Color Temperature	RGB
	PVC Body Color	Clear
	Min/Max Surface Temp for Mounting	-40°C - 40°C (-40°F - 104°F)
	Dimmable	Yes
	Beam Angle	120°
LED	Type	N/A
	Life Span	40,000 Hours
	Spacing	1.3" (33mm)
	# per foot (304mm)	9
Design	Dimensions (Inches)	.3" x .6"
	Dimensions (Millimeters)	7.6 x 15mm
	Max Single Run Length	40Ft
	Custom Cuttable	8" (198mm)
	Approved Location	Indoor/Outdoor
Warranty	2 years	
Approvals	cETLus	

PRODUCT CODES ——— XX: Length in feet

40Ft spools
LES - 40 - RGB

Custom cuts
LES - XX - RGB



ACCESSORIES



LES-BTFN
Female connector



LES-BTMN
Male connector



LES-BTSN
In line connector



LES-BTMCJ-1.5
1.5' Power connector



LES-BTMCJ-6
6' Power connector



LES-BTMC-G4-SI
Signal in connector for RGB eStrip connection to outdoor signal amplifier



LES-BTMC-G4-SO
Signal out connector for RGB eStrip connection to outdoor signal amplifier



LTP-001-OD-6FT
Power feed connector for connection to outdoor signal amplifier



LES-STCN
Cutting end cap



LES-STFN
Female end cap



LES-STPV-T
Clear PVC mounting "U" channel (1M)



LES-SNPT
Wood nail clips, 1/4" X 1/2" (6mm x 12mm)



LES-C-6
Tie wrap



LES-MX-1
Allen key



TCJ-E06
6' (1.8m) Extension cord

TCJ-E30
30' (9.1m) Extension cord 1/4" x



LES-TCJ-EI6-N
LED RGB eStrip 6" Flex Connector



LT-WIFI-RM
4-Zone RGB+CCT Remote



LT-WIFI-CTRL
3 IN 1 LED Strip Controller (WiFi+24G)



LT-WIFI-AMP
WiFi Signal Amplifier for RGB, RGBW, CCT


NON DIMMABLE DRIVERS

LEDDR-24-120W

Indoor/Outdoor driver
Max 40' (12.1m) per single tap
Max 54' (16.46m) combined 2 secondary taps
Input: 100 - 240V AC, Output: 24V DC
10" x 3 3/8" x 3 3/16" (254 x 85.7 x 80.9mm)

Neon Flex

LED Neon Flex is a flexible lighting solution designed to accentuate architectural and design elements, adding color and vibrancy to building exteriors.



FEATURES

- Virtually maintenance free
 - Low power consumption
 - Safe 24V DC operation
 - cETLus certified
 - Dimmable
 - Inter-connectable
 - Field cuttable (every 4" single color, every 12" RGB)
- Custom cuts available
 - Available in seven brilliant colors, and RGB
 - Highly flexible, with neon look
 - Indoor/outdoor use
 - 30,000 hour life
 - 3 years limited warranty

APPLICATIONS

- Building outlines
- Stairway and aisle lighting
- Signs
- Decks
- Pathway lighting
- Billboards
- Highlighting architectural features


SPECIFICATIONS		
Product Code		NFLX-XX-YY
Electrical	Input Voltage	24V DC
	Power Consumption	2.44 W/Ft (8W/M)
Specs	Color Temperature	3000K, 4000K, 6000K, Red, Green, Blue, Amber, RGB
	CRI	80+
	Lumen Output	300 Lumens/Ft (900 Lumens/M) (In white)
	Efficacy	25 LPW
	PVC Body Color	Clear
	Operating Temperature	-20°C - 40°C
	Dimmable	Yes
	Beam Angle	120°
LED	Type	N/A
	Life Span	30,000 Hours
	# per foot (304mm)	N/A
Design	Dimensions (Inches)	1.04 x 0.6"
	Dimensions (Millimeters)	26.5 x 15mm
	Max Single Run Length	40Ft
	Custom Cuttable	4" Single Color, 12" RGB
	Approved Location	Indoor/Outdoor
Warranty	3 years	
Approvals	cETLus	

PRODUCT CODES ——— XX: Length in feet; YY: Color temperature

NFLX - 40 - XX
NFLX - XX - YY

LED Neon Flex Length Color

3000K, 4000K, 6000K, RD - Red, GR - Green, BL - Blue, AM - Amber, RGB - RGB



ACCESSORIES (SINGLE COLOR)

NFLX-CONKIT-6FT
Power feed connector, 6FT

NFLX-JUMP
Jumper connector, 15CM [6in]

NFLX-PINS
Single color pins

NFLX-SPLICE
In-line splice connector

NFLX-L-SPLICE
L splice connector

NFLX-T-SPLICE
T splice connector

NFLX-ENDS
End cap

NFLX-CLIPS
Mounting clips

NFLX-CHANNEL
Aluminum mounting channel 1M [3.28FT]

NFLX-GLUE
Silicone Glue

ACCESSORIES (RGB)

NFLX-RGB-CONTROL
RGB controller

NFLX-RGB-AMP
RGB signal amplifier

NFLX-RGB-CONKIT-6FT
RGB power feed connector, 6FT

NFLX-RGB-CONKIT-6FT-O
RGB power feed connector, 6FT, opposite

NFLX-RGB-JUMP
RGB Jumper connector, 15cm (6 Inches)

LT-WIFI-RM
4-Zone RGB+CCT Remote

LT-WIFI-CTRL
3 IN 1 LED Strip Controller (WiFi+2.4G)

NFLX-PINS
Single color pins

NFLX-ENDS
End cap

NFLX-CLIPS
Mounting clips

NFLX-RGB-CHANNEL
Aluminum mounting channel 1M [3.28FT]

NFLX-GLUE
Silicone Glue

LT-WIFI-AMP
WiFi Signal Amplifier for RGB, RGBW, CCT

INDOOR/OUTDOOR DIMMABLE DRIVERS

MLDRE-40-24-DM
Max 14.5' (4.4m)
Min 8 Watts, 3.3'(1M) LED Neon Flex
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

MLDRE-96-24-DM
Max 40' (12m)
Min 8 Watts, 3.3'(1m) LED Neon Flex
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

NON DIMMABLE DRIVERS

MLDR-120-24
Indoor/Outdoor driver
Max 40' (12m) per single tap
Max 48' (14.6m) combined 2 secondary taps
Input: 100 - 240V AC
Output: 24V DC
10" x 3 3/8" x 3 3/16" (254 x 85.7 x 80.9mm)

MLDR-20-24JB
Indoor driver
Max recommended load 18W 7.3'(2.2m)
LED Neon Flex
Input: 100 - 240V AC
Output: 24V DC
20 Watts
4 1/8" x 4 1/8" x 1 1/2" (104.8 x 104.8 x 38.1mm)

NOTE: For outdoor installations, please add E-KO-SR strain relief (2pcs/driver).

Globe Light

The LED Globe Light, characterized by its marquee-style design, serves as a decorative lighting option equipped to endure extreme weather conditions, offering durability and longevity for both indoor and outdoor use.

FEATURES

- 50,000 hours life
 - Low power consumption
 - Safe class 2, 24V power supply
 - Field cuttable
 - Multiple lamp spacings available
- Durable construction for indoor and outdoor use
 - 2 years limited warranty




APPLICATIONS

- Building outlines
- String across patios, walk ways, streets and public areas
- Under soffits
- Bridges
- Architectural features
- Window decorations
- Decks and patios


SPECIFICATIONS		
Product Code		MGST-12-Y (Y: Color temperature)
Electrical	Input Voltage	24V DC
	Power Consumption	.5W/Bulb
Specs	Color Temperature	2700/6000K
	CRI	80+
	Lumen Output	50 Lumens/Bulb
	LED Colors	2700K, 6000K, Red, Blue, Green, Amber (Upon request)
	Efficacy	100 Lumens per watt
	Wiring	Directly wired to class 2, 24V power supply
	Dimmable	Yes
	Cable	PVC black SPT2, 16AWG outdoor rated
	Life Span	50,000 Hours
	Spacing	12"
	# per foot (304mm)	1
Design	Dimensions (Inches)	1.77 x 2.76"
	Dimensions (Millimeters)	45 x 70mm
	Finish	Black
	Max Single Run Length	150' (45.6M) Not to exceed 180 lamps
	Operating Temperature	-25°C to 65°C
	Approved Location	Indoor/Outdoor
Warranty	2 years	
Approvals	cETLus	

PRODUCT CODES

Y: Color temperature



OUTDOOR RATED CABLE: **ST16W**
For attaching Globe Light Lamp Assemblies.



ACCESSORIES

MGNC
Wood nail mounting clip

MGEC
End cap for wire (Bag of 10)

MGWC
Tie wrap for mounting to wire

ST16W
Outdoor rated cable for DIY mounting of LED Globe Light

MGTP
Double sided tape (Bag of 50 pieces)

MGST-XX-LAMP
Replacement lamp (XX: 2700K, 6000K, R (Red), BL (Blue), G (Green), AM (Amber))

INDOOR/OUTDOOR DIMMABLE DRIVERS

TRE24L40DC
Min 8 Watts, 16 Globes
Max number of Globes = 80
40 Watts
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

TRE24L96DC
Min 8 Watts, 16 Globes
Max number of Globes = 180
96 Watts
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

NON DIMMABLE DRIVERS

LEDDR-24-120W
Indoor/Outdoor driver
Max number of Globes = 180*
120W hardwire
Input: 100 - 240V AC
Output: 24V DC
120 Watts
10" x 3 3/8" x 3 3/16" (254 x 85.7 x 80.9mm)

* 180 on a single tap or 200 combined two secondary taps.

Wedge Light

The LED Wedge Light is designed as a durable lighting solution for all weather conditions, making it suitable for outlining buildings and various decorative lighting projects. Its robust construction ensures reliable performance in diverse environments.

FEATURES

- 50,000 hours life
 - Low power consumption
 - Safe class 2, 12V power supply
 - Field cuttable
 - Multiple lamp spacings available
 - Durable construction for indoor and outdoor use
- Available in Cool White and Warm White
 - Optional Red, Blue, Green & Amber LEDs are also available
 - 2 years limited warranty

APPLICATIONS



- Building outlines
- Under soffits
- Bridges
- Architectural features
- Coves
- Window decorations
- Decks and patios



SPECIFICATIONS		
Product Code		MGST-12-Y (Y: Color temperature)
Electrical	Input Voltage	12V DC
	Power Consumption	.25W/Bulb
Specs	Color Temperature	2700/6000K
	CRI	80+
	Lumen Output	15 Lumens/Bulb
	LED Colors	2700K, 6000K, Red, Blue, Green, Amber (Upon request)
	Efficacy	60 Lumens per watt
	Wiring	Directly wired to class 2, 24V power supply
	Dimmable	Yes
	Cable	PVC black SPT2, 16AWG outdoor rated
	Life Span	50,000 Hours
	Spacing	6"
	# per foot (304mm)	2
Design	Dimensions (Inches)	1.02" x 1.46"
	Dimensions (Millimeters)	26 x 37mm
	Finish	Black
	Max Single Run Length	100' (45.6M) Not to exceed 200 lamps
	Operating Temperature	-25°C to 65°C
	Approved Location	Indoor/Outdoor
Warranty	2 years	
Approvals	cETLus	

PRODUCT CODES

Y: Color temperature



ACCESSORIES

MGNC
Wood nail mounting clip

MGEC
End cap for wire (Bag of 10)

MGWC
Tie wrap for mounting to wire

ST16W
Outdoor rated cable for DIY mounting of LED Wedge Light

MGTP
Double sided tape (Bag of 50 pieces)

MGWL-XX-LAMP
Replacement lamp (XX: 2700K, 6000K, R (Red), BL (Blue), G (Green), AM (Amber))

INDOOR/OUTDOOR DIMMABLE DRIVERS

TRE12L20DC
Min 8 Watts, 32 Wedges
Max number of Wedges = 80
20 Watts
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

TRE12L60DC
Min 8 Watts, 32 Wedges
Max number of Wedges = 200
60 Watts
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

NOTE: For outdoor installations, please add E-KO-SR strain relief (2pcs/driver).

NON DIMMABLE DRIVERS

LEDDR-12-60W
Indoor/Outdoor driver
Max number of Wedges = 200
60W hardwire
Input: 100 - 240V AC
Output: 12V DC
9 11/16" x 2 9/16" x 2 1/16" (246 x 65 x 52mm)

24V Wall Washer

The 24V LED Wall Washer is engineered for illuminating architectural features, signage, and landscapes with its advanced lighting capabilities. It provides a versatile solution for both indoor and outdoor spaces, combining functionality with aesthetic enhancement.



FEATURES


- Safe 24V DC operation (Requires our 24V driver)
- Low power consumption: 5.8W/FT
- Suitable for indoor and outdoor use
- Beam angle: 30°
- Available in 2700K, 3000K, 4000K color temperatures
- Long life 30, 000 hours
- Dimmable with dimmable drivers
- Field cuttable every 6" (Maximum run is 16ft.)
- Sold in 33 Rolls
- cULus certified for wet locations
- 3 years limited warranty

APPLICATIONS

- Architectural lighting
- Signage
- Landscape lighting
- Exterior/interior commercial

SPECIFICATIONS				
Product Code		ES-LS2835-27K-42-24-30	ES-LS2835-30K-42-24-30	ES-LS2835-40K-42-24-30
Electrical	Input Voltage	24V DC		
	Power Consumption	5.8W/Ft		
Specs	Color Temperature	2700K	3000K	4000K
	Efficacy	100LM/W	105LM/W	110LM/W
	Luminous Flux	580LM/FT	610LM/FT	640LM/FT
	CRI	90+		
	Dimmable	Yes		
	Beam Angle	30°		
LED	Type	SMD2835		
	Life Span	30,000 Hours		
	Spacing	N/A		
	# per foot (304mm)	14		
Design	Dimensions	8mm (5/16”) x 15mm (9/16”)		
	Max Single Run Length	16Ft		
	Custom Cuttable	Every 6”		
	Approved Location	Indoor/Outdoor		
	Mounting	Ceiling, floor		
Warranty	3 years			
Approvals	cULus for wet locations			

NOTE: For field cuttability you will need power supply cap, End cap and potentially jumper cables. All termination points must be glued with our NFLX-GLUE. Please reach out if you have any questions, we would be happy to help.



PRODUCT CODES

ES - LS2835 - 27K - 42 - 24 - 30

ES - LS2835 - 30K - 42 - 24 - 30

ES - LS2835 - 40K - 42 - 24 - 30

ACCESSORIES



NFLX-GLUE
Glue



ES-EC
End Cap



ES-MC
Mounting Clips
(4pcs/bag)




ES-WB
Wall Washer Wall Bracket Set
(2 pieces)



ES-PFC-6FT
Power Feed Connector



ES-JC-6IN 6IN,
ES-JC-12IN 12IN,
ES-JC-3FT 3FT,
ES-JC-6FT 6FT
Jumper Cable



ES-EXT
ES-EXT Aluminum
extrusion (8FT), anodized
black, for ceiling or
floor mounting. For wall
mounting, please see the
wall mounting brackets.



Three wall mounting brackets
available to enhance the wall
washing effect (2 pieces):

ES-MB-2IN 2IN
ES-MB-4IN 4IN
ES-MB-6IN 6IN
Wall Mounting Bracket

INDOOR/OUTDOOR DIMMABLE DRIVERS

TRE24L40DC
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

TRE24L96DC
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

NON DIMMABLE DRIVERS

LEDDR-24-120W (Indoor/Outdoor)
120W hardwire
Input: 100 - 240V AC
Output: 24V DC
10" x 3 3/8" x 3 3/16" (254 x 85.7 x 80.9mm)

Wall Washer 4’ Enclosed

This a type of lighting fixture designed to evenly distribute light over a wall or vertical surface. Enclosed within a 4-foot-long casing, this wall washer is designed for durability and protection against dust, moisture, and other environmental factors.



FEATURES

- Safe 24V DC operation (Requires our 24V driver)
- Low power consumption: 5.8W/FT
- Suitable for indoor and outdoor use
- Beam angle: 30°
- Available in 2700K, 3000K, 4000K color temperatures
- Long life 30, 000 hours
- Dimmable with dimmable drivers
- Sold in 33 Rolls
- cULus certified for wet locations
- 3 years limited warranty

APPLICATIONS

- Architectural lighting
- Signage
- Landscape lighting
- Exterior/interior commercial

SPECIFICATIONS		
Product Code		ES-LS2835-30-WH-24-4FT
Electrical	Input Voltage	24V DC
	Power Consumption	5.8W/Ft
Specs	Color Temperature	3000K
	CRI	90+
	Efficacy	105LM/W
	Luminous Flux	610LM/FT
	Dimmable	Yes
	Beam Angle	30°
LED	Type	SMD2835
	Life Span	30,000 Hours
	Spacing	N/A
	# per foot (304mm)	14
Design	Dimensions (Inches)	5/16' x 9/16"
	Dimensions (Millimeters)	8 x 15mm
	Max Single Run Length	N/A
	Custom Cuttable	N/A
	Approved Location	Indoor/Outdoor
	Mounting	Ceiling, floor
Warranty	6 years	
Approvals	cULus for wet locations	

PRODUCT CODES

ES - LS2835 - 30 - WH - 24 - 4FT

ACCESSORIES



ES-WB
Wall bracket set



ES-ADJ-BR
Adjustable bracket (Rotatable)

INDOOR/OUTDOOR DIMMABLE DRIVERS

MLDRE-40-24-DM
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

MLDRE-96-24-DM
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

NON DIMMABLE DRIVERS

MLDR-120-24 (Indoor/Outdoor)
120W hardwire
Input: 100 - 240V AC
Output: 24V DC
10" x 3 3/8" x 3 3/16" (254 x 85.7 x 80.9mm)

A modern bathroom interior featuring a long white vanity with a wooden-grain cabinet and under-cabinet lighting. A large mirror is mounted above the vanity. In the background, a glass-enclosed shower area is visible. To the right, a white bathtub is partially shown. The walls are covered in light-colored stone tiles, and the floor is made of large, light-colored tiles. Two yellow circles are overlaid on the image: one in the top right corner containing the text 'Under Cabinet Lighting' and another in the bottom center.

Under Cabinet Lighting

5CCT LED Task Bar

For those seeking high performance LED under cabinet lighting fixture, the 5CCT LED Task Bar offers customizable lighting, true color representation, energy efficiency, easy installation, versatility, and durability.



FEATURES

- Available in white finish
 - Life: 35,000 Hours
 - Plug and hardwire power cords available (sold separately)
 - Easy installation
 - 5 position switch for color temperature adjustment
- Slim profile
 - Dimmable with TRIAC dimmers
 - Linkable up to 200W using end to end connectors or jumper cords
 - Jumper cords available (sold separately)

APPLICATIONS


- Under cabinet task light
- Over cabinet accent light
- Display cases and exhibits
- Merchandising
- Wall units and bars
- Office work stations

SPECIFICATIONS							
		10"	12"	18"	24"	36"	48"
Product code	LEDLB-5CCT-XX	LEDLB-5CCT-10	LEDLB-5CCT-12	LEDLB-5CCT-18	LEDLB-5CCT-24	LEDLB-5CCT-36	LEDLB-5CCT-48
Electrical	Input Voltage	120V AC					
	Power Consumption	3.5W	5W	8W	12W	16W	20W
	Max Wattage per run	200W					
Specs	Color Temperature	2700/3000/3500/4000/5000K					
	CRI	90					
	Lumen Output	290	443-541	652-771	966-1134	1199-1393	1599-1892
	Efficacy (lm/W)	82.8	98.4	88.75	82.5	81.25	87.5
	Dimmable	Yes, with TRIAC dimmers					
	Beam Angle	110°					
	LED						
LED	Type	SMD2835					
	Life Span	35,000 Hours					
	Spacing	N/A					
	# per foot / unit	N/A					
Design	Dimensions Inches (l;h;w)	9 3/4; 1 5/16; 13/16"	12 3/8; 1 5/16; 13/16"	17 1/2; 1 5/16; 13/16"	22 5/8; 1 5/16; 13/16"	34 7/16; 1 5/16; 13/16"	46 1/4; 1 5/16; 13/16"
	Dimensions mm (l/h/w)	247 / 33 / 20mm	315 / 33 / 20mm	445 / 33 / 20mm	575 / 33 / 20mm	875 / 33 / 20mm	1175 / 33 / 20mm
	Finish Color / trims	White					
	Product Material	Aluminum and acrylic					
	Max Single Run Length	40Ft					
	Custom Cuttable	N/A					
	Operating Temperature	-20°C to 40°C					
	Approved Location	Damp					
	Mounting	Via included brackets					
Warranty		5 years					
Approvals		cETLus for indoor use					

NOTE: Only LEDLB-5CCT-18, LEDLB-5CCT-24, LEDLB-5CCT-36, and LEDLB-5CCT-48 have on/off switch.



DIAGRAM



PRODUCT CODES

LEDLB - 5CCT - XX

SIZE (INCHES)
10, 12, 18, 24, 36, 48

ACCESSORIES




LEDLB-J-12
12" Jumper Cable

LEDLB-J-18
18" Jumper Cable

LEDLB-J-24
24" Jumper Cable

LEDLB-J-32
32" Jumper Cable



LTSPRO-PC-72
72" power cord and plug

LTSPRO-HW-72
72" power cord for hardwire



LTSPRO-JB
Hardwire junction box With ON/OFF switch

Gen II LED Hard Strip

Gen II LED Hard Strip is a new and improved energy efficient linkable strip, that provides a smooth, even lighting, eliminating any hot spots. Encased in an aluminum casing, the LED's are cool to the touch and provide 120° beam spread.



FEATURES

- 50,000 hours life
- Use high brightness 0.5W Epistar LEDs as lighting source
- Even light distribution with 120° viewing angle
- Available in 4 sizes
- Convenient connector
- between two strips
- Diffused frosted lens to reduce glare


APPLICATIONS

- Under counter
- Display cases
- Cabinet interiors
- Work stations
- Interior decorative lighting



SPECIFICATIONS					
		300mm	500mm	1000mm	1200mm
Product code	LV-HS-PD20-24V-YY-XX	LV-HS-PD20-24V-30-XX*	LV-HS-PD20-24V-50-XX*	LV-HS-PD20-24V-100-XX*	LV-HS-PD20-24V-120-XX*
Electrical	Input Voltage	24V DC			
	Power Consumption	4W	7W	13W	16W
Specs	Color Temp: Neutral White	4200K +/- 200K			
	Color Temp: Warm White	3000K +/- 200K			
	Lumens (LM): Neutral White	400	664	1066	1150
	Lumens (LM): Warm White	380	621	1036	1100
	Viewing Angle	120°			
LED	Life Span	50,000 Hours			
	Qty. per strip	36	60	132	156
Design	Size	11.8" (300mm)	19.7" (500mm)	39.4" (1000mm)	47.3" (1200mm)
	Product Material	Aluminum			
	Operating Temperature	-35°C to 50°C			
	Mounting	2 pieces of 0° mounting clips and one end cap			
Warranty		3 years limited			
Approvals		cETLus for indoor use			

*XX = LED color: WW = 3000K, NW = 4200K | NOTE: Each Hard Strip bar ships with 2pcs of 0° mounting clips and one end cap.

MOUNTING OPTIONS



PRODUCT CODES



ACCESSORIES

LV-HS-PD20-PF1-12
12" Power Feed for LED Hard Strip single color, Bar - DC plug power supply

LV-HS-PD20-PF1-39
39" Power Feed for LED Hard Strip single color, Bar - DC plug power supply

LV-HS-PD20-PF1-HW
39" Power Feed for LED Hard Strip single color, Bar - Hard wire power supply

LV-HS-PD20-PC1-12
12" Power Connector for LED Hard Strip single color, Bar - Bar

LV-HS-PD20-PC1-39
39" Power Connector for LED Hard Strip single color, Bar - Bar

LV-HS-PD20-PC1-3
3" Power Connector for LED Hard Strip Single Color, Bar - Bar

LV-HS-CN-3DC
Connector for Hard Strip, with 12" wire lead and 3 DC connectors

LV-HS-CN-2DC
Connector for Hard Strip, with 12" wire lead and 2 DC connectors

LV-HS-EC
End Cap for LED Hard Strip

LV-HS-MC0
Mounting clip (2pk)

LV-HS-MC30
Mounting clip 30° (2pk)

LV-HS-MC45
Mounting clip 45° (2pk)

LV-HS-MCTR
Rotary Mounting clip (2pk)

NON DIMMABLE

LEDDR-24-120W
Indoor/Outdoor driver
Max. recommended load 90W per single tap, 120W combined two secondary taps.
120W hardwire
Input: 100 - 240V AC
Output: 24V DC
10" x 3 3/8" x 3 3/16" (254 x 85.7 x 80.9mm)

INDOOR/OUTDOOR DIMMABLE DRIVERS

TRE24L40DC
Max recommended load 36W, min. 8W LED Hard Strip
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

TRE24L96DC
Max recommended load 90W, min. 8W LED Hard Strip
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

Switchex®
LED DRIVER + DIMMER IN ONE
A dimmer with an integrated driver that converts 120VAC to either 12VDC or 24VDC.

Gen II 3-Color Change LED Task Star

Craft the perfect ambiance with Gen II LED Task Star’s color temperature control, easy-to-install features, and a 5-year warranty.



FEATURES

- NEW: 1/2” Knockouts for easy installation
- 3 position switch for color temperature adjustment (3000K/4000K/5000K)
- Available in 5 lengths for multiple applications
- Dimmable with most ELV dimmers.
- Captive mounting screws
- Continuous dimming with a 5%-100% dimming range
- Easy installation
- High Low switch
- 5 years limited warranty
- Available in white, black, bronze and aluminum finish


APPLICATIONS

- Under counter
- Display cases
- Cabinet interiors
- Work stations
- Interior decorative lighting


SPECIFICATIONS						
		9.5"	17.5"	26"	34.5"	43"
Product code	LTS-II-Y-HW/XX	LTS-II-1-HW/XX*	LTS-II-2-HW/XX*	LTS-II-3-HW/XX*	LTS-II-4-HW/XX*	LTS-II-5-HW/XX*
Electrical	Input Voltage	120V AC				
	Power Consumption	5W	10W	15W	20W	25W
Specs	Color Temp	3000/4000/5000K				
	CRI	90+				
	Lumens (Output)	310LM	650LM	1000LM	1300LM	1500LM
	Dimmable	Most ELV dimmers - continous dimming with a 5%-10% dimming range				
LED	Type	0.5W Epistar				
	Life Span	50,000 Hours				
Design	Dimensions (Inches)	9.5 x 4.47 x 1.54"	17.5 x 4.47 x 1.54"	26 x 4.47 x 1.54"	34.5 x 4.47 x 1.54"	43 x 4.47 x 1.54"
	Dimensions (Millimeters)	240 x 113.5 x 39mm	443.5 x 113.5 x 39mm	659.2 x 113.5 x 39	874.9 x 113.5 x 39mm	1090 x 113.5 x 39mm
	Lens	Frosted glass				
	Finish	BK-Black, BZ-Bronze, AL-Aluminum, WH-White				
	Mounting	N/A				
Warranty	5 years limited					
Approvals	cETLus and Energy Star					

*XX = Trim Finish (see below)

PRODUCT CODES



DIAGRAM



LED Task Star PRO

LTSPRO is constructed with aluminum housing and a matte polycarbonate diffuser. This sleek fixture features edge lit technology which means no hot spots on the polished marble or granite counter top.



FEATURES

- Long lasting 50,000 hours life
- Comes with High / Low Switch
- Low power consumption
- Edge Lit technology eliminates hot spots
- Fast and easy installation – quick connects, captive mounting holes
- Comes with cord and plug as well as knockouts for hardwire
- 3/8” connector provided
- Shallow profile conceals fixture
- Linkable up to 400 watts. Each fixture ships with 8” jumper cable and end-to-end connector
- cETLus and Energy Star listed
- 3 years limited warranty


APPLICATIONS

- Under cabinet task light
- Over cabinet accent light
- Display cases and exhibits
- Merchandising
- Indirect accent light
- Wall units and bars


SPECIFICATIONS							
		9"	12"	18"	24"	32"	40"
Product Code	LTSPRO- XX-YY	LTSPRO- 9-YY*	LTSPRO- 12-YY*	LTSPRO- 18-YY*	LTSPRO- 24-YY*	LTSPRO- 32-YY*	LTSPRO- 40-YY*
Electrical	Input Voltage	120V AC					
	Power Consumption	3W	5W	8W	12W	16W	20W
Specs	Color Temp	2700/3300/4000K					
	CRI	90+					
	Lumens (Output)	200LM	300LM	450LM	700LM	900LM	1000LM
	Dimmable	Yes					
LED	Type	Epistar					
	Life Span	50,000 Hours					
Design	Dimensions (Inches)	9 x 3.5 x 1"	12 x 3.5 x 1"	18 x 3.5 x 1"	24 x 3.5 x 1"	32 x 3.5 x 1"	40 x 3.5 x 1"
	Dimensions (MM)	22.9 x 8.9 x 2.5mm	30.5 x 8.9 x 2.5mm	45.7 x 8.9 x 2.5mm	61 x 8.9 x 2.5mm	81.3 x 8.9 x 2.5mm	101.6 x 8.9 x 2.5mm
	Lens	Matte white polycarbonate					
	Body	Extruded aluminum housing					
	Finish	BK-Black, BZ-Bronze, SN-Satin Nickel, WH-White					
Warranty	5 years limited						
Approvals	cETLus and Energy Star						

*YY = Trim Finish (see below)

PRODUCT CODES



DIAGRAM



ACCESSORIES



LTSPRO-J-12*

12” jumper cable

LTSPRO-J-18*

18” jumper cable

LTSPRO-J-24*

24” jumper cable

LTSPRO-J-32*

32” jumper cable



LTSPRO-PC-72*

72” replacement power cord and plug



LTSPRO-JB

Hardwire junction box for LTSPRO fixtures - allows for direct wiring installation, eliminating the visible household wire. Add (-BK) at the end of part number for black finish.



RC-01

3/8” Romex connectorr

REPLACEMENT PARTS

LTSPRO-SW-BK

CCT Slider Switch Cover, Black

LTSPRO-SW-WH

CCT Slider Switch Cover, White

LED Edgelit Puck Lights

The Edge Lit Puck Lights are sleek and powerful surface mount lighting fixtures, combining the easy installation with high performance LED's. Featuring strong internal magnets, they can be installed on metal surfaces, without screws or mounting holes.



FEATURES

- 30,000 hours life
- Edgelit design with smooth light output
- Safe 24V low voltage operation
- Operating temperature: -30°C to 40°C
- Durable die-cast aluminum housing suitable for dry location
- Strong magnet and stamped steel plate for surface mounting
- 72 inch pre-installed lead wire
- 3-year limited warranty

APPLICATIONS

- Under cabinets
- Over cabinets
- Indirect lighting
- Display cases
- Furniture
- Shelf lighting

SPECIFICATIONS			
Product Code		EPL - SR - WW - XX (ROUND)	EPL - SS - WW - XX (SQUARE)
Electrical	Input Voltage	24V DC	
	Power Consumption	4W	
Specs	Color Temperature	3000K	
	CRI	90+	
	Lumens	200LM	
	Efficacy (LM/W)	50	
	Dimmable	Yes	
	Beam Angle	24/36/60° (Replacable)	
LED	Type	5630 SMD LEDs	
	Life Span	30,000 Hours	
Design	Dimensions (Inches)	3 x 0.5"	3 x 0.5"
	Dimensions (Millimeters)	76 x 12.7mm	76 x 12.7mm
	Finish	White, Black, Bronze	
	Material	Die-cast aluminum	
	Operating Temperature	-20 to 40°C	
	Approved Location	Indoor	
Warranty	Mounting	Surface mount	
	Warranty	3 years	
Approvals		cETLus	

PRODUCT CODE

ROUND

EPL - SR - WW - XX

LED
Edgelit
Puck
Light

LED
Color
3000K

FINISH
WH - White
BK - Black
BZ - Bronze

SQUARE


EPL - SS - WW - XX

LED
Edgelit
Puck
Light

LED
Color
3000K

FINISH
WH - White
BK - Black
BZ - Bronze

DIAGRAM



ACCESSORIES



LMSII-001

Terminal block and junction box for connection to additional lengths of power cable if needed.

DIMMABLE DRIVERS

TRE24L40DC

Max recommended load 36W or 9 Edge Lit Puck Lights, min 8W or 2 Edge Lit Puck Lights 6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

TRE24L96DC

Max recommended load 92W or 23 Edge Lit Puck Lights, min 8W or 2 Edge Lit Puck Lights 6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

NON-DIMMABLE DRIVERS

LEDDR-24-120W

Indoor/Outdoor driver
Max. recommended load 96W or 24 Edge Lit Puck Lights per single tap, 120W or 30 Edge Lit Puck Lights combined two secondary taps.
120W hardwire
Input: 100 - 240V AC
Output: 24V DC
10" x 3 3/8" x 3 3/16" (254 x 85.7 x 80.9mm)



Landscape Lighting

Uplight (Wattage Adjustable)

Engineered for durability and flexibility, this LED Uplight achieves up to 900 lumens of brightness with adjustable wattage, complemented by a choice of three beam spreads.



FEATURES


- Adjustable wattage control
 - High lumen output
 - Durable die-cast aluminum
 - Versatile beam spread
 - Sleek black finish
 - Wide voltage compatibility
- Warm light temperature
 - Easy installation design
 - Weather-resistant coating
 - Long-lasting, 15 years warranty

APPLICATIONS

- Garden lighting
- Facade lighting
- Pathway safety
- Security lighting
- Sign lighting
- Patio ambiance

SPECIFICATIONS		
Product Code	UP-01-12V-BLK	
Electrical	Input Voltage	9-17V AC/DC
	Power Consumption	0-12W (Adjustable)
Specs	Colour Temperature	3000K
	CRI	85
	Lumen Output	900LM Max.
	Efficacy (LM/W)	83
	Dimmable	No, but wattage adjustable
	IP Rating	IP65
	Beam Angle	24/36/60° (Replacable)
LED	Life Span	50,000 Hours
Design	Dimensions (Inches)	6.4 x 6.7 x 2.9"
	Dimensions (Millimeters)	161 x 177 x 73mm
	Finish	Black powder coating
	Material	Die-cast aluminum
	Operating Temperature	-20 to 40°C
	Approved Location	Outdoor
	Mounting	Via Stake
Warranty	15 years	
Approvals	cETLus	

DIAGRAM



NOTE: Comes with a mounting stake to ensure a hassle-free installation.

ACCESSORIES



ACC-3R-BLK
3 Inch Riser Black

- 3 inches long
- 1 Male and 1 Female end
- ½ inch NPSM thread
- Cast brass
- Black Finish



ACC-7R-BLK
7 Inch Riser Black

- 7 inches long
- 1 Male and 1 Female end
- ½ inch NPSM thread
- Cast brass
- Black Finish



ACC-12G-2C-BUR
Landscape burial wire, 12G, 2C - 500ft spool

ACC-12G-2C-BUR-XX
Landscape burial wire, 12G, 2C - custom cuts

NOTE: A transformer is required. See page 106 to 109.

Uplight (RGBW)

Elevate your ambiance with the RGBW Uplight, capable of shining in a myriad of colors at up to 500 lumens, featuring smart app connectivity for easy adjustments, and built with a robust die-cast aluminum body.



FEATURES

- Adjustable wattage control
 - Multiple RGBW colors
 - 24/36/60° beam angles
 - Durable aluminum construction
 - Smart app control
- WIFI/Bluetooth enabled
 - 9-17V AC/DC compatible
 - Sleek black finish
 - Long-lasting, 15 years warranty


APPLICATIONS

- Accent lighting
- Path illumination
- Garden highlights
- Security lights
- Art spotlights
- Event lighting

SPECIFICATIONS		
Product Code	UP-02-12V-BLK	
Electrical	Input Voltage	9-17V AC/DC
	Power Consumption	0-8W (Adjustable)
Specs	Colour Temperature	RGB
	CRI	85
	Lumen Output	500LM Max.
	Efficacy (LM/W)	70
	Dimmable	No, but wattage adjustable
	IP Rating	IP65
	Beam Angle	24/36/60° (Replacable)
LED	Life Span	50,000 Hours
Design	Dimensions (Inches)	6.4 x 6.7 x 2.9"
	Dimensions (Millimeters)	161 x 177 x 73mm
	Finish	Black powder coating
	Material	Die-cast aluminum
	Operating Temperature	-20 to 40°C
	Approved Location	Outdoor
	Mounting	Via Stake
Warranty	15 years	
Approvals	cETLus	



DIAGRAM



NOTE: Comes with a mounting stake to ensure a hassle-free installation.

ACCESSORIES



ACC-3R-BLK
3 Inch Riser Black

- 3 inches long
- 1 Male and 1 Female end
- ½ inch NPSM thread
- Cast brass
- Black Finish



ACC-7R-BLK
7 Inch Riser Black

- 7 inches long
- 1 Male and 1 Female end
- ½ inch NPSM thread
- Cast brass
- Black Finish



ACC-12G-2C-BUR
Landscape burial wire, 12G, 2C - 500ft spool

ACC-12G-2C-BUR-XX
Landscape burial wire, 12G, 2C - custom cuts

NOTE: A transformer is required. See page 106 to 109.

12V Mini Flood Light

This compact yet powerful 12V Mini Flood light, with a customizable wattage between 1 and 5 watts, provides a luminous output of 80-400 lumens, encased in a durable cast brass housing.



FEATURES

- Adjustable wattage control
 - 80-400 lumen output
 - Integrated 12V LED
 - Cast brass housing
 - 3000K warm light
 - Black or bronze finish
- Spike mounting option
 - Wide beam angle
 - Long-lasting, 15 years warranty
 - Smart control compatibility


APPLICATIONS

- Path illumination
- Outdoor accents
- Security lighting
- Architectural highlights
- Event ambiance
- Patio glow

SPECIFICATIONS		
Product Code	FL-01-12V-BLK	
Electrical	Input Voltage	12V AC/DC
	Power Consumption	1-5W
Specs	Colour Temperature	2700K, 3000K
	CRI	85
	Lumen Output	400LM
	Efficacy (LM/W)	80
	Dimmable	No, wattage adjustable
	Beam Angle	120°
LED	Life Span	50,000 Hours
Design	Dimensions (Inches)	4 x 3.9 x 2.5"
	Dimensions (Millimeters)	101.5 x 100 x 63mm
	Finish	Black
	Material	Solid Brass Casting
	Operating Temperature	-20 to 40°C
	Approved Location	Outdoor
Warranty	15 years	
	cETLus	



DIAGRAM



NOTE: Comes with a mounting stake to ensure a hassle-free installation.

ACCESSORIES



ACC-3R-BLK
3 Inch Riser Black

- 3 inches long
- 1 Male and 1 Female end
- ½ inch NPSM thread
- Cast brass
- Black Finish



ACC-7R-BLK
7 Inch Riser Black

- 7 inches long
- 1 Male and 1 Female end
- ½ inch NPSM thread
- Cast brass
- Black Finish



ACC-12G-2C-BUR
Landscape burial wire, 12G, 2C - 500ft spool

ACC-12G-2C-BUR-XX
Landscape burial wire, 12G, 2C - custom cuts

NOTE: A transformer is required. See page 106 to 109.

120V Mini Flood Light (CCT)

Achieve perfect outdoor lighting for any occasion with CCT Adjust Mini Flood Lights, featuring adjustable CCTs for versatile illumination. Their compact size and high efficiency make them a smart choice for diverse landscape applications.




FEATURES

- Adjustable CCT (3000K/4000K/5000K)
- High lumen output
- Easy installation
- Wide beam angle
- Long lifespan (50,000 hours)
- Instant start, no flicker
- Wattage options (15W, 30W, 50W)
- Wet location rated
- 5 years warranty

APPLICATIONS

- Facade accenting
- Garden highlights
- Outdoor art display
- Parking areas
- Entryway illumination
- Commercial exteriors


SPECIFICATIONS				
Product Code	FL-15-CT		FL-30-CT	FL-50-CT
Electrical	Input Voltage	100 -277V AC		
	Power Consumption	15W	30W	50W
Specs	Colour Temperature	3000/4000/5000K		
	CRI	80+		
	Lumen Output	3000K: 1725-1950LM	3000K: 3450-3900LM	3000K: 5750-6500LM
		4000K: 2025-2250LM	4000K: 4050-4500LM	4000K: 6750-7500LM
		5000K: 1875-2100LM	5000K: 3750-4200LM	5000K: 6250-7000LM
	Efficacy (LM/W)	Up to 150		
	Dimmable	No, but wattage adjustable		
Beam Angle	150° x 120° (7H6V)			
LED	Type	SMD3030 (1W)		
	Life Span	50,000 Hours		
Design	Dimensions (Inches)	6 5/8 x 8 x 1 3/4"	6 5/8 x 8 x 1 3/4"	7 5/16 x 9 7/16 x 1 15/16"
	Dimensions (Millimeters)	168.3 x 204 x 43.7 mm	168.3 x 204 x 43.7 mm	201 x 239 x 49 mm
	Finish	Black		
	Material	N/A		
	Operating Temperature	-20 to 50°C		
	Approved Location	Wet		
	Mounting	Via Stake		
Warranty	5 years			
Approvals	cULus listed for wet locations			




Change the colour temperature, with a push of a button

DIAGRAM


15W and 30W



50W



MOUNTING ACCESSORIES




FL-TR
Trunnion mount bracket
To use for wall and ground mount




FL-Y-15/30/50
Yoke mount bracket
To use for wall and ground mount



FL-SH-15/30/50
Glare shield



FL-WG-15/30/50
Wire guard



FL-ADM-15/30/50
Universal mount bracket
For use on poles

Modern Pathway Light

Designed for the modern landscape, this L-shaped Pathway Light offers an adjustable light output of 80-240 lumens and a warm 3000K temperature, creating a welcoming atmosphere for any outdoor setting.



FEATURES

- L-shaped contemporary design
- Adjustable 1-3W wattage
- Integrated 9-17V LED
- Warm 3000K temperature
- Durable cast aluminum
- Frosted lens diffusion
- Easy spike mounting
- 18/2 wire pigtail
- Full/half light mode
- Serviceable LED module
- Wet location listed
- Long-lasting, 15 years warranty

APPLICATIONS

- Pathway illumination
- Garden lighting
- Outdoor accent
- Entryway paths
- Architectural highlights
- Safety lighting

SPECIFICATIONS		
Product Code	WF-01-12V-BLK	
Electrical	Input Voltage	9-17V AC/DC
	Power Consumption	1-3W
Specs	Colour Temperature	3000K
	CRI	85
	Lumen Output	80-240LM
	Efficacy (LM/W)	77
	Dimmable	No, but wattage adjustable
	IP Rating	IP65
	Beam Angle	150° (Replacable)
LED	Life Span	50,000 Hours
Design	Dimensions (Inches)	21 1/4 x 6 1/8 x 7/8"
	Dimensions (Millimeters)	540.2 x 154 x 22mm
	Finish	Black
	Material	Aluminum
	Operating Temperature	-40 to 40°C
	Approved Location	Outdoor
Warranty	Mounting	Via Stake
	Warranty	15 years
Approvals	cETLus	



DIAGRAM



NOTE: Comes with a mounting stake to ensure a hassle-free installation.

ACCESSORIES



ACC-12G-2C-BUR

Landscape burial wire, 12G, 2C - 500ft spool

ACC-12G-2C-BUR-XX

Landscape burial wire, 12G, 2C - custom cuts

NOTE: A transformer is required. See page 108 to 111.

Round Tea-Hat Pathway Light

The Round Tea-Hat Light redefines pathway illumination with its unique round hat design, offering an energy-efficient solution to brighten outdoor settings, backed by a durable construction..



FEATURES

- Wattage adjustable
- Broad lumen range
- Low-voltage efficiency
- Warm color temperature
- Durable cast aluminum construction
- Hastle-free installation
- Spike-mounted for stability
- Sleek black finish
- Easy-connect 18/2 wire pigtail
- Long-lasting, 15 years warranty


APPLICATIONS

- Pathway lighting
- Landscape accent
- Garden paths
- Entrance lighting
- Recreational areas

SPECIFICATIONS		
Product Code	WF-03-12V-BLK	
Electrical	Input Voltage	9-17V AC/DC
	Power Consumption	1-3W
Specs	Colour Temperature	3000K
	CRI	85
	Lumen Output	80-240LM
	Efficacy (LM/W)	80
	Dimmable	No, but wattage adjustable
	IP Rating	IP65
	Beam Angle	150°
LED	Life Span	50,000 Hours
Design	Dimensions (Inches)	23 1/2 x 3 5/8 x 1"
	Dimensions (Millimeters)	597 x 93 x 26mm
	Finish	Black
	Material	Aluminum
	Operating Temperature	-40 to 40°C
	Approved Location	Outdoor
	Mounting	Via Stake
Warranty	15 years	
Approvals	cETLus	



DIAGRAM



NOTE: Comes with a mounting stake to ensure a hassle-free installation.

ACCESSORIES



ACC-12G-2C-BUR

Landscape burial wire, 12G, 2C - 500ft spool

ACC-12G-2C-BUR-XX

Landscape burial wire, 12G, 2C - custom cuts

NOTE: A transformer is required. See page 106 to 109.

Heavy Duty Classic Pathway Light

Upgrade outdoor spaces with the Classic Top Pathway Light, blending traditional aesthetics with energy-saving LED in a durable brass fixture.

FEATURES

- Heavy cast brass construction
- Integrated 3000K LED chip
- 12V energy-saving operation
- Spike mounting simplicity
- Reliable 18/2 wire connection
- Classic design, modern tech
- Easy integration into landscapes
- Weather-resistant for outdoor use
- Long-lasting, 15 years warranty

APPLICATIONS

- Pathway lighting
- Garden enhancement
- Architectural accents
- Decorative outdoor
- Entrance highlighting
- Driveway borders



SPECIFICATIONS		
Product Code	WF-04-12V-BLK	
Electrical	Input Voltage	12V AC/DC
	Power Consumption	5W
Specs	Colour Temperature	2700K, 3000K
	CRI	85
	Lumen Output	400LM
	Efficacy (LM/W)	80
	Dimmable	No
	IP Rating	IP65
	Beam Angle	150°
LED	Life Span	50,000 Hours
Design	Dimensions (Inches)	14.96 x 6.6"
	Dimensions (Millimeters)	380 x 168mm
	Finish	Black
	Material	Die-cast brass
	Operating Temperature	-20 to 40°C
	Approved Location	Outdoor
	Mounting	Via Stake
Warranty	15 years	
Approvals	cETLus	

DIAGRAM



NOTE: Comes with a mounting stake to ensure a hassle-free installation.

ACCESSORIES



ACC-12G-2C-BUR

Landscape burial wire, 12G, 2C - 500ft spool

ACC-12G-2C-BUR-XX

Landscape burial wire, 12G, 2C - custom cuts

NOTE: A transformer is required. See page 108 to 111.

Commercial Bollards

Engineered for outdoor resilience, bollard lights provide efficient, low-glare lighting, perfect for enhancing visibility and ambiance in landscape areas.




- FEATURES

 - 3 base heights and 2 head options
 - Input voltage range: 120-347V AC
 - High efficiency: >92% power efficiency
 - Dimmable: 0-10V dimming
 - Surge protection: 4KV/6KV
 - Tunable CCT: 3000/4000/5000K
- APPLICATIONS


 - Wide beam angle: 110°×105°
 - Durable build: IP65 rating, die-cast aluminum housing
 - Long lifespan: >50,000 hours
 - Certifications: ETL/DLC 5.1 premium
 - Warranty: 5 years
 - Pathways and walkways
 - Gardens and flower beds
 - Driveways and entrances
 - Outdoor seating areas
 - Pool decks and water features
 - Perimeter and boundary lighting

SPECIFICATIONS				
Product Code	Head	WF-CB-MV-H-RMW (Round)		WF-CB-MV-H-FMW (Flat)
	Body	WF-CB-MV-BD1050	WF-CB-MV-BD670	WF-CB-MV-BD400
Electrical	Input Voltage	120-347V AC		
	Power Consumption	25/20/15/8W		
Specs	Colour Temperature	3000/4000/5000K (TUNABLE)		
	CRI	70+		
	Lumen Output	3,125/2,500/1,875/1,000LM		
	Efficacy	125 LM/W		
	Dimmable	0-10V		
	Beam Angle	110° × 105°		
LED	Type	3030		
	Life Span	>50,000 Hours		
Design	Dimensions (Inches)	R: H= 41.34" F: H = 39.49"	R: H= 26.4" F: H = 24.53"	R: H= 15.75" F: H = 13.90"
		W= 5.91"		
	Dimensions (Millimeters)	R: H= 1050mm F: H = 1003mm	R: H= 670mm F: H = 623mm	R: H= 400mm F: H = 353mm
		W= 150mm		
	Finish	Black		
	Material	Die-cast Aluminum		
	Operating Temperature	-40°F to 104°F (-40°C to 40°C)		
Warranty	Approved Location	Outdoor		
	Mounting	Via base, refer to instructions for details		
Warranty		5 years		


NOTE: Fixture Head (Round or Flat) and Body are to be ordered seperately.



- ACCESSORIES



WF-CB-SP
Surge Protector



WF-CB-MT
Anchor Bolt Carrier

Surface Mount Deck/Riser Light

Create a welcoming atmosphere on decks and pathways with a light that adjusts to your preferences; easy installation for immediate impact.



FEATURES

- Adjustable wattage from 1W to 3W with a dip switch
- 70° beam spread
- 85 CRI
- Warm glow (3000K)
- Sleek black finish
- Quick setup with 18/2 wire pigtail
- Cast aluminum housing
- Wet location listed
- Long-lasting, 15 years warranty

APPLICATIONS


- Pathway illumination
- Deck lighting
- Step safety
- Garden ambiance
- Entrance highlighting
- Fence lighting



SPECIFICATIONS

SPECIFICATIONS		
Product Code	WF-02-12V-BLK	
Electrical	Input Voltage	12/24V AC/DC
	Power Consumption	0-3W (Adjustable)
Specs	Colour Temperature	3000K
	CRI	85
	Lumen Output	60-180LM
	Efficacy (LM/W)	60
	Dimmable	No, but wattage adjustable
	IP Rating	IP65
	Beam Angle	70°
LED	Life Span	50,000 Hours
Design	Dimensions (Inches)	4 x 2 5/8"
	Dimensions (Millimeters)	101.6 x 66.67 mm
	Finish	Black
	Material	Aluminum
	Operating Temperature	-40 to 40°C
	Approved Location	Outdoor
Warranty	Mounting	Via screws to wall
	Warranty	15 years
Approvals	cETLus	

DIAGRAM



ACCESSORIES



ACC-12G-2C-BUR
Landscape burial wire, 12G, 2C - 500ft spool

ACC-12G-2C-BUR-XX
Landscape burial wire, 12G, 2C - custom cuts

Outdoor Wall Sconce

A contemporary style wall sconce suitable for interior and exterior use. Available in three finishes and three interchangeable covers to suit a variety of applications,



FEATURES


- Housing: Rugged aluminum construction
 - 120V - 277V AC input voltage
 - Lumen output 1300LM
 - CRI 80+
 - LED life: 50,000 hours
 - Powder coated finish
- 120° beam angle
 - ADA compliant
 - Finishes: Brown, Black and Silver
 - Three interchangeable covers: Wave, Wing and Scoop
 - cULus listed for wet locations

APPLICATIONS

- Exterior residential & commercial
- Entrance ways
- Hallway lighting
- Patio & deck Lights
- Hotel hallways & restaurants
- Stairways & lobbies

SPECIFICATIONS		
Product Code	TLWMV15XWMZZ	
Electrical	Input Voltage	120V - 277V AC
	Power Consumption	15W
Specs	Colour Temperature	3000/4000K
	CRI	80+
	Lumen Output	1300LM
	Efficacy (LM/W)	60
	Dimmable	No
	Beam Angle	120°
LED	Type	LUMILED 3030
	Life Span	>50,000 Hours
Design	Dimensions (Inches)	8 x 4 3/8 x 2 1/8"
	Dimensions (Millimeters)	203 x 111 x 54mm
	Finish	Powder coated finish
	Material	Aluminum
	Operating Temperature	-20 to +40°C
	Approved Location	Outdoor
Warranty	Mounting	Wall
	Warranty	5 years
Approvals	cULus listed for wet locations	

3 COVER OPTIONS (Sold seperately)



PRODUCT CODES


DIAGRAM

TLWMV15XWMZZ


- LED Outdoor Sconce

COLOUR OF LED
3 - 3000K
4 - 4000K

FINISH
BR - Brown
BK - Black
SV - Silver



DIAGRAMS (COVERS)



Brick Star (Gen II)

LED Brick Star enhances stairs, aisles, and paths with attractive, cost-effective lighting, designed to fit standard brick sizes for easy integration and optimal performances,



FEATURES

- Long-lasting 40,000-hour LED
 - Ultra-low energy use: 5.2 watts
 - High color accuracy: CRI 80+
 - Lens: Frosted tempered glass
 - Standard 120VAC input
 - Supports up to 150 units per tap
- Durable die-cast aluminum build
 - Available in fluorocarbon can with stainless steel louvre cover
 - Standard brick size fit
 - Compatible with TRIAC dimmers
 - 3 years warranty

APPLICATIONS

- Brick walls
 - Exterior steps
 - Interior steps
 - Aisles
 - Halls
 - Paths
- Patio lighting
 - Entry lighting
 - Ceilings
 - Showers

SPECIFICATIONS		
Product Code	LBR-II-X-WH-YY	
Electrical	Input Voltage	120V AC
	Power Consumption	5.2W
Specs	Colour Temperature	3000K
	CRI	80+
	Lumen Output	468LM
	Efficacy (LM/W)	90
	Dimmable	Yes, with TRIAC dimming systems
	Beam Angle	N/A
LED	Life Span	>40,000 Hours
Design	Dimensions (Inches)	3 x 9"
	Dimensions (Millimeters)	76.2 x 226.6mm
	Can Finish	Powder Coated White or Fluorocarbon Lacquer (Stainless Steel)
	Cover Finish	White, Black, Bronze, Aluminum or Stainless Steel finish only available in Louvre cover
	Lens	Frosted tempered glass
	Max Single Run Length	Can be daisy chained up to 150 fixtures per 15A circuit
	Approved Location	Wet and IC locations, concrete pour, shower
Warranty	Mounting	Wall, ceiling
		3 years
Approvals	cETLus listed for wall, ceiling, wet and IC locations	

NOTE: When installing LED Brick Star in harsh environments (such as limestone, salted areas, coastal environments, etc.) please use the stainless steel version to avoid the risk of corrosion to the body of the fixture.



PRODUCT CODES

LBR - II - X - WH - YY			
LED Brick Star	COVER	COLOUR OF LED	COVER FINISH
	P - Prism		WH - White
	S - Scoop	3000K	BK - Black
	L - Louvre		BZ - Bronze
			AL - Aluminum
			SS - Stainless Steel

REPLACEMENT KIT




LBR-II-KIT

- NOTE: Stainless Steel finish available in Louvre cover only.
- Concrete cap for concrete pour installations.
- NOTE: For outdoor installations, a 1/2" liquid tight strain relief is recommended.

CONCRETE CAP

BL-CC

DIAGRAM



Concrete Cap (for concrete pour installations)

- Product Code: **BL-CC**
- **IMPORTANT:** It is recommended that you use Magic Lite / NSL's Concrete Cap for concrete pour installations. These caps assist in providing a proper reveal for flush mount of fixture cover after concrete is dry..

Step Star (Gen II)

LED Step Star offers durable, energy-efficient lighting for stairs and pathways, suitable for both indoor and outdoor use, with a robust cast aluminum build ideal for concrete installations.



FEATURES

- 40,000-hour LED lifespan
- Ultra-low energy use: 5.2 watts
- Color accuracy with CRI 80+
- Lens: Frosted tempered glass
- Supports 120VAC power input
- Up to 150 units per 120VAC circuit
- Durable die-cast aluminum enclosure
- Versatile indoor/outdoor certification (cETLus)
- Compatible with TRIAC dimmers
- 3 years warranty

APPLICATIONS

- Interior stairs
- Exterior stairs
- Aisles
- Hallways
- Paths
- Public areas
- Emergency lighting
- Theaters
- Patios
- Decks

SPECIFICATIONS		
Product Code	LST-II-X-WH-YY	
Electrical	Input Voltage	120V AC
	Power Consumption	5.2W
Specs	Colour Temperature	3000K
	CRI	80+
	Lumen Output	468LM
	Efficacy (LM/W)	90
	Dimmable	Yes, with TRIAC dimmable systems
	Beam Angle	N/A
	Life Span	>40,000 Hours
Design	Dimensions (Inches)	3 x 9"
	Dimensions (Millimeters)	76.2 x 228.6mm
	Can Finish	Powder Coated White
	Cover Finish	White, Black, Bronze, and Aluminum
	Lens	Can be daisy chained up to 150 fixtures per 15A circuit
	Approved Location	Wet and IC locations
	Mounting	Wall, ceiling
Warranty	3 years	
Approvals	cETLus listed for wall, ceiling, wet and IC locations	

Wiring Options: 20V AC hardwire – can be daisy chained up to 150 fixtures per 15A circuit.



PRODUCT CODES

LST - II - X - WH - YY

LED	COVER	COLOUR OF LED	COVER FINISH
Step Star	P - Prism		WH - White
Gen II	S - Scoop	3000K	BK - Black
	L - Louvre		BZ - Bronze
			AL - Aluminum

REPLACEMENT KIT







LST-II-KIT

- Concrete cap for concrete pour installations.
- NOTE: For outdoor installations, a 1/2" liquid tight strain relief is recommended.

CONCRETE CAP

SL-CC

DIAGRAM



Concrete Cap (for concrete pour installations)

- Product Code: **SL-CC**
- IMPORTANT: It is recommended that you use Magic Lite / NSL's Concrete Cap for concrete pour installations. These caps assist in providing a proper reveal for flush mount of fixture cover after concrete is dry..

Switch Star

LED Switch Star is ideal for both indoor and outdoor settings, offering an excellent solution for security or exit lighting. This fixture connects directly to 120V without the need for remote drivers, simplifying installation.




- FEATURES

 - 1.4W power consumption
 - Mounts on 2" x 4" boxes
 - Outdoor/indoor ready
 - Louvre/scoop/prism covers
 - Horizontal/vertical mounting
 - 3 color choices
- APPLICATIONS


 - Hallways, stairways
 - Night light
 - Decks, patios
 - Garages, elevators
 - Commercial/residential exteriors

SPECIFICATIONS		
Product Code	LED-SW-X-Y	
Electrical	Input Voltage	120V AC, .012A
	Power Consumption	1.4W
Specs	Colour Temperature	2700K or Amber
	CRI	80+
	Lumen Output	468LM
	Efficacy (LM/W)	57
	Dimmable	No
LED	Beam Angle	120°
	Type	AC LED
	Life Span	40,000 Hours to 70% Lumen output
Design	Dimensions (Inches)	5.07 x 3.03"
	Dimensions (Millimeters)	129 x 77mm
	Finish	White, Light Almond, Brown Wood Grain
	Material	Polycarbonate (5VA flame rated, F1 UV rated) & Glass
	Operating Temperature	-30°C to 60°C
	Approved Location	Indoor/Outdoor
Warranty	3 years	
Approvals	cETLus listed	


PRODUCT CODES




- Note: Add (-AM) on the part number for Amber LED fixture
- Scoop and Louvre covers are supplied in both horizontal and vertical.



COVER STYLES



COVER DIMENSIONS



Disc Light

Versatile and robust, the LED Disc Light offers powerful illumination for both public and residential areas, whether indoors or outdoors. Durable and certified for wet conditions, it's great for enhancing decks, driveways, and patios with simple concrete pour setup.



FEATURES


- Fully dimmable with dimmable power supply (sold separately)
 - 50,000-Hour LED life
 - Low power consumption: 3 watts per fixture
 - Safe 12 volt, Class 2 power supply (not included)
- Up to 30 fixtures per power supply
 - Lens: Frosted or clear tempered glass
 - cETLus listed
 - Fits 1.5" diameter hole
 - No UV, no infrared, no radiated heat
 - 3 years warranty
- Steps
 - Aisles
 - Paths
 - Driveways
 - Direction lighting
 - Information lighting
 - Decorative lighting
 - Merchandising
 - Landscape accents

APPLICATIONS

SPECIFICATIONS			
Product Code	LEDD-Y-XX (ROUND)		LEDD-Y-XX-SQ (SQUARE)
Electrical	Input Voltage	12V AC	
	Power Consumption	3W	
Specs	Colour Temperature	Cool White 98 lumens @ 5400K; Warm White 95 lumens @ 2900K	
	CRI	80+	
	Lumen Output	900LM Max.	
	Efficacy (LM/W)	83	
	Dimmable	Yes	
	Beam Angle	120	
LED	Type	5050	
	Life Span	50,000 Hours	
Design	Dimensions (Inches)	2.36 x 3.9"	2.36 x 3.94"
	Dimensions (Millimeters)	60 x 99mm	60 x 100mm
	Cover Finish	Stainless steel	
	Barrel Finish	Stainless steel	
	Max Single Run Length	18 fixtures	
	Approved Location	Outdoor	
	Mounting	Recessed	
Warranty	3 years		
Approvals	cETLus listed and labeled for wet, IC, ceiling, wall and direct burial applications		

NOTE: When installing Mini Disc Lights in harsh environments (such as limestone, salted areas, coastal environments, etc.) please use the stainless steel version to avoid the risk of corrosion to the body of the fixture.

DIAGRAM



PRODUCT CODES

ROUND
LEDD-Y-XX

LED Disc Light

TEMPERED GLASS
F - Frosted
C - Clear

COLOUR OF LED
WH - 5500K
WW - 2700K
AM - Amber

SQUARE
LEDD-Y-XX-SQ

LED Disc Light

TEMPERED GLASS
F - Frosted
C - Clear

COLOUR OF LED
WH - 5500K
WW - 2700K
AM - Amber

REPLACEMENT LED MODULES

- LEDD-MOD-WH
LED Disc Light module, 12V, white LED 5500K
- LEDD-MOD-WW
LED Disc Light module, 12V, warm white LED 2700K

INSTALLATION WIRES

- LW-18G-BUR
For outdoor burial connections
- LW-18G-CL2
For indoor through wall connections

NOTE: One of the above wires MUST be used in order to maintain product warranty.

ACCESSORIES



LEDD-CF
LED Disc Light concrete form for concrete pour applications. Fits over most 3/4" conduit junction boxes.

LEDD-CF-SQ
LED Disc Light Square concrete form for concrete pour applications. Fits over most 3/4" conduit junction boxes.

DIMMABLE DRIVERS

TRE12L20DC
20 Watts
Max. recommended load 18 W or 6 LED Disc Lights
Min. recommended load 8 W or 3 LED Disc Lights
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)


TRE12L60DC
60 Watts
Max. recommended load 54 W or 18 LED Disc Lights
Min. recommended load 8 W or 3 LED Disc Lights
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

NON DIMMABLE DRIVERS

LEDDR-12-60W (Indoor/Outdoor)
60W hardwire
Input: 100 - 240V AC; Output: 12V DC
Max. 18 LED Disc Lights
9 11/16" x 2 9/16" x 2 1/16" (246 x 65 x 52mm)


100% LED Light Output Chart

With every foot of lead wire and every light fixture, there is voltage loss. With too much voltage loss all light fixtures will not develop 100% of their potential output. Below is a chart of acceptable voltage loss which will maintain 100% of the potential light output of the LED Disc Light. Simply plot the number of LED Disc Light you wish to place on one lead on the horizontal axis, with the total distance from the LED Driver to the last LED Disc Light on the vertical axis. If the resulting plot is at or below the line shown, you will have acceptable voltage loss and your LED Disc Light will output 100% of their potential.




WARNING: LACK OF DRAINAGE WILL VOID THE WARRANTY


To maintain the warranty, a proper drainage system MUST be installed (drainage material or drainage pipe), when the product is installed in soil or concrete.



Concrete Installation




Paving Stones




Soil Installation


Test drainage prior to installation.
A quantity of water equal to the volume of the mounting hole should drain in 15 minutes or less.



SOFT GROUND



HARD GROUND



Mini Disc Marker Light

Robust and energy-efficient, the LED Mini Disc Light, with its durable construction and low 0.24W consumption, suits a multitude of indoor/outdoor applications. It offers long-lasting illumination in both round and square designs, ensuring compatibility with any décor at an affordable cost.



FEATURES

- Dimmable on the primary power supply side with drivers
 - 50,000 hour durability
 - Ultra-low consumption: 0.24 watts per fixture
 - 12V class 2 safety
 - Up to 100 fixtures per supply
- cETLus certified
 - Fits 1" diameter, 3.5" depth
 - Lens: Frosted Tempered Glass
 - 2 years limited warranty, 3 years on stainless steel


APPLICATIONS

- Steps
 - Aisles
 - Paths
 - Driveways
 - Direction lighting
- Information lighting
 - Decorative lighting
 - Merchandising
 - Landscape accents

SPECIFICATIONS			
Product Code	LEDMD-XX-YY (ROUND)		LEDMD-XX-YY-SQ (SQUARE)
Electrical	Input Voltage	12V DC	
	Power Consumption	0.24W	
Specs	Colour Temperature	Cool White 5400K, Warm White 2900K, Blue, Green, Amber, Red	
	CRI	80+	
	Lumen Output	17	
	Efficacy (LM/W)	70	
	Dimmable	Yes	
	Beam Angle	120	
LED	Life Span	50,000 Hours	
Design	Dimensions (Inches)	3 1/4 x 2"	3 1/4 x 1.97"
	Dimensions (Millimeters)	82.6 x 50.8mm	82.6 x 50mm
	Cover Finish	Aluminum, White, Bronze, Black, Stainless Steel	
	Barrel Finish	Aluminum, White, Bronze, Black, Stainless Steel	
	Material	Both cover and barrel are die cast aluminum	
	Lens	Frosted tempered glass	
	Approved Location	Outdoor	
	Mounting	Recessed	
Warranty	3 years		
Approvals	cETLus listed and labeled for wet, IC, ceiling, wall and direct burial applications		

- **NOTE:** When installing Mini Disc Lights in harsh environments (such as limestone, salted areas, coastal environments, etc.) please use the stainless steel version to avoid the risk of corrosion to the body of the fixture.
- Each LED Driver can power up to 200 LED MiniDisc Lights by parallel wiring ("daisy chain") between fixtures.
- **NOTE:** Use LW-18G-CL2 for all in-wall applications, LW-18G-BUR for all burial applications.

DIAGRAM



PRODUCT CODES

ROUND LEDMD-XX-YY		
LED	COLOUR OF LED	FINISH
MiniDisc Light	CW - 5400K	AL - Aluminum
	WW - 2900K	WH - White
	AM - Amber	BZ - Bronze
	BL - Blue	BK - Black
	GR - Green	SS - Stainless Steel
	RD - Red	
SQUARE LEDMD-XX-YY-SQ		
LED	COLOUR OF LED	FINISH
MiniDisc Light	CW - 5400K	AL - Aluminum
	WW - 2900K	WH - White
	AM - Amber	BZ - Bronze
	BL - Blue	BK - Black
	GR - Green	SS - Stainless Steel
	RD - Red	

REPLACEMENT LED MODULES

- **LCL-LEDMOD-WH**
LED Mini Disc Light module, 12V, white LED 5400K
- **LCL-LEDMOD-WW**
LED Mini Disc Light module, 12V, warm white LED 2900K


INSTALLATION WIRES

- **LW-18G-BUR**
For outdoor burial connections
- **LW-18G-CL2**
For indoor through wall connections

NOTE: One of the above wires **MUST** be used in order to maintain product warranty.


100% LED Light Output Chart

With every foot of lead wire and every light fixture, there is voltage loss. With too much voltage loss all light fixtures will not develop 100% of their potential output. Below is a chart of acceptable voltage loss which will maintain 100% of the potential light output of the LED Disc Light. Simply plot the number of LED Disc Light you wish to place on one lead on the horizontal axis, with the total distance from the LED Driver to the last LED Disc Light on the vertical axis. If the resulting plot is at or below the line shown, you will have acceptable voltage loss and your LED Disc Light will output 100% of their potential.



WARNING: LACK OF DRAINAGE WILL VOID THE WARRANTY

To maintain the warranty, a proper drainage system **MUST** be installed (drainage material or drainage pipe), when the product is installed in soil or concrete.



ACCESSORIES



LEDMD-CF
LED Mini Disc Light concrete form for concrete pour applications. Fits over most 1/2" (12.7mm) conduit junction boxes.

LEDMD-CF-SQ
LED MiniDisc Light Square concrete form for concrete pour applications. Fits over most 1/2" (12.7mm) conduit junction boxes.

DIMMABLE DRIVERS

TRE12L20DC
20 Watts
Max. recommended load 18 W or 75 Mini Disc Lights
Min. recommended load 8 W or 34 Mini Disc Lights
6.77" x 2.67" x 1.26" (171 x 68 x 2mm)

TRE12L60DC
60 Watts
Max. recommended load 54 W or 200 Mini Disc Lights
Min. recommended load 8 W or 34 Mini Disc Lights
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

NON DIMMABLE DRIVERS

LEDDR-12-60W (Indoor/Outdoor)
60W hardwire
Input: 100 - 240V AC
Output: 12V DC
Max. 200 Mini Disc Lights
9 11/16" x 2 9/16" x 2 1/16" (246 x 65 x 52mm)

Mini Disc Light (Scoop)

The LED Mini Disc Scoop directs light precisely, ideal for stair and theater aisle lighting,. It's durable and efficient, offering a 50,000-hour lifespan and low 0.24W consumption, fitting easily into 1" holes. Certified for diverse environments, it ensures safety and versatility with a solid warranty.

FEATURES

- Dimmable on the primary power supply side with drivers
 - 50,000 hour durability
 - Ultra-low consumption: 0.24 watts per fixture
 - 12V class 2 safety
 - Up to 100 fixtures per supply
- cETLus certified
 - Fits 1" diameter, 3.5" depth
 - Lens: Frosted Tempered Glass
 - 2 years limited warranty, 3 years on stainless steel

APPLICATIONS

- Steps
 - Aisles
 - Paths
 - Driveways
 - Direction lighting
- Information lighting
 - Decorative lighting
 - Merchandising
 - Landscape accents




SPECIFICATIONS		
Product Code	LEDMD-S-XX-YY	
Electrical	Input Voltage	12V DC
	Power Consumption	0.24W
Specs	Colour Temperature	Cool White 5400K, Warm White 2900K, Blue, Green, Amber, Red
	CRI	80+
	Lumen Output	17
	Efficacy (LM/W)	70
	Dimmable	Yes
	Beam Angle	No up-light when mounted with scoop on upper half
LED	Life Span	50,000 Hours
Design	Dimensions (Inches)	2 x 3 1/4"
	Dimensions (Millimeters)	50.8 x 82.6mm
	Cover Finish	Aluminum, White, Bronze, Black
	Barrel Finish	Aluminum, White, Bronze, Black
	Lens	Frosted tempered glass
	Max Single Run Length	200 fixtures
	Approved Location	Outdoor
	Mounting	Recessed
Warranty	2 years	
Approvals	cETLus listed and labeled for wet, IC, ceiling, wall and direct burial applications	

- **NOTE:** When installing Mini Disc Scoop in harsh environments (such as limestone, salted areas, coastal environments, etc.) please use the stainless steel version to avoid the risk of corrosion to the body of the fixture.

• Each LED Driver can power up to 200 Mini Disc Lights by parallel wiring ("daisy chain") between fixtures.

• **NOTE:** Use LW-18G-CL2 for all in-wall applications, LW-18G-BUR for all burial applications.

DIAGRAM



PRODUCT CODES

LEDMD-S-XX-YY

LED	COLOUR OF LED	FINISH
Mini Disc Light (Scoop)	CW - 5400K WW - 2900K AM - Amber BL - Blue GR - Green RD - Red	AL - Aluminum WH - White BZ - Bronze BK - Black

REPLACEMENT LED MODULES

- **LCL-LEDMOD-WH**
LED Mini Disc Light module, 12V, white LED 5400K
- **LCL-LEDMOD-WW**
LED Mini Disc Light module, 12V, warm white LED 2900K

INSTALLATION WIRES

- **LW-18G-BUR**
For outdoor burial connections
- **LW-18G-CL2**
For indoor through wall connections

NOTE: One of the above wires **MUST** be used in order to maintain product warranty.

ACCESSORIES



LEDMD-CF
Concrete form for concrete pour applications. Fits over most 1/2" (12.7mm) conduit junction boxes.

DIMMABLE DRIVERS

TRE12L20DC
20 Watts
Max. recommended load 18 W or 75 Mini Disc Lights
Min. recommended load 8 W or 34 Mini Disc Lights
6.77" x 2.67" x 1.26" (171 x 68 x 2mm)

TRE12L60DC
60 Watts
Max. recommended load 54 W or 200 Mini Disc Lights
Min. recommended load 8 W or 34 Mini Disc Lights
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)


NOTE: For outdoor installations, please add E-KO-SR strain relief.

NON DIMMABLE DRIVERS

LEDDR-12-60W (Indoor/Outdoor)
60W hardwire
Input: 100 - 240V AC
Output: 12V DC
Max. 200 Mini Disc Lights
9 11/16" x 2 9/16" x 2 1/16" (246 x 65 x 52mm)


100% LED Light Output Chart

With every foot of lead wire and every light fixture, there is voltage loss. With too much voltage loss all light fixtures will not develop 100% of their potential output. Below is a chart of acceptable voltage loss which will maintain 100% of the potential light output of the LED Disc Light. Simply plot the number of LED Disc Light you wish to place on one lead on the horizontal axis, with the total distance from the LED Driver to the last LED Disc Light on the vertical axis. If the resulting plot is at or below the line shown, you will have acceptable voltage loss and your LED Disc Light will output 100% of their potential.




WARNING: LACK OF DRAINAGE WILL VOID THE WARRANTY


To maintain the warranty, a proper drainage system **MUST** be installed (drainage material or drainage pipe), when the product is installed in soil or concrete.



Concrete Installation




Paving Stones




Soil Installation

Test drainage prior to installation.


A quantity of water equal to the volume of the mounting hole should drain in 15 minutes or less.



SOFT GROUND



HARD GROUND



Disc Light Dome

Stainless Steel Construction

Durable LED marker light with dimming capability, perfect for indoor and outdoor use. Stainless steel construction ensures longevity in any setting.



FEATURES

- Dimmable with dimmable power supplies
- Long life – 50,000 hours
- Low power consumption 3 watts per fixture
- Safe 12 volt, Class 2 power supply (not included)
- Up to 30 fixtures per power supply
- cETLus listed
- Fits in any 1.5” diameter hole, 4” long
- Lens: Clear tempered glass
- Available concrete form for concrete pour applications
- 3 years limited warranty


APPLICATIONS

- Steps
- Aisles
- Paths
- Driveways
- Direction lighting
- Decorative lighting

SPECIFICATIONS		
Product Code	LEDD-C-XX-D	
Electrical	Input Voltage	12V DC
	Power Consumption	3W
Specs	Colour Temperature	Cool White 98 lumens @ 5500K; Warm White 95 lumens @ 2700K
	CRI	80+
	Lumen Output	5500K: 98; 2700K: 95
	Efficacy (LM/W)	33
	Dimmable	Yes
LED	Type	5050
	Life Span	50,000 Hours
Design	Dimensions (Inches)	3.9 x 1.95”
	Dimensions (Millimeters)	99 x 49.6mm
	Cover Finish	Stainless Steel (SUS316)
	Barrel Finish	Stainless Steel (SUS316)
	Max Single Run Length	18 fixtures
	Approved Location	Outdoor
Warranty	Mounting	Burial, wall
		3 years
Approvals	cETLus listed and labeled for wet, IC, ceiling, wall and direct burial applications	

- **Wiring Options:** Fixtures can be parallel wired or “Daisy chained” together with up to 18 fixtures on our largest dimmable driver.
- **NOTE:** Use LW-18G-CL2 for all in-wall applications. Use LW-18G-BUR for all burial applications.

DIAGRAM



PRODUCT CODES

LEDD-C-XX-D

LED Disc Light (Dome)
COLOUR OF LED
WH - 5500K
WW - 2700K

REPLACEMENT LED MODULES

- **LEDD-MOD-WH**
LED Disc Light module, 12V, white LED 5500K
- **LEDD-MOD-WW**
LED Disc Light module, 12V, warm white LED 2700K

INSTALLATION WIRES

- **LW-18G-BUR**
For outdoor burial connections
- **LW-18G-CL2**
For indoor through wall connections

NOTE: One of the above wires **MUST** be used in order to maintain product warranty.

ACCESSORIES



LEDD-CF

Recommended for easy installation in concrete pour applications..

DIMMABLE DRIVERS

TRE12L20DC

20 Watts
Max. recommended load 18 W or 6 LED Disc Lights
Min. recommended load 8 W or 3 LED Disc Lights
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

TRE12L60DC

60 Watts
Max. recommended load 54 W or 18 LED Disc Lights
Min. recommended load 8 W or 3 LED Disc Lights
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

NOTE: For outdoor installations, please add E-KO-SR strain relief.


NON DIMMABLE DRIVERS

LEDDR-12-60W (Indoor/Outdoor)

60W hardwire
Input: 100 - 240V AC; Output: 12V DC
Max. 18 LED Disc Lights
9 11/16" x 2 9/16" x 2 1/16" (246 x 65 x 52mm)

100% LED Light Output Chart




With every foot of lead wire and every light fixture, there is voltage loss. With too much voltage loss all light fixtures will not develop 100% of their potential output. Below is a chart of acceptable voltage loss which will maintain 100% of the potential light output of the LED Disc Light. Simply plot the number of LED Disc Light you wish to place on one lead on the horizontal axis, with the total distance from the LED Driver to the last LED Disc Light on the vertical axis. If the resulting plot is at or below the line shown, you will have acceptable voltage loss and your LED Disc Light will output 100% of their potential.



NOTE: No more than 18 LED Disc Lights per LEDR-12-60W.

WARNING: LACK OF DRAINAGE WILL VOID THE WARRANTY




To maintain the warranty, a proper drainage system **MUST** be installed (drainage material or drainage pipe), when the product is installed in soil or concrete.



Soil Installation

Test drainage prior to installation.

A quantity of water equal to the volume of the mounting hole should drain in 15 minutes or less.



Well Light

Illuminate columns, fences, and trees discreetly with this well light. Designed for flush installation, it features a robust die-cast aluminum housing and a powerful integrated 6-watt LED. Waterproof and backed by a 15-year warranty.



FEATURES

- Low-profile design for discreet lighting
- Robust die-cast aluminum construction
- Silicon filled wirenuts
- IP67 rated
- Wet location listed
- Powerful 6-watt integrated LED
- Weatherproof for outdoor durability
- Bright 580-lumen output
- Stylish black finish for modern appeal
- Effortless installation with included sleeve
- Backed by 15 years warranty


APPLICATIONS

- Column and pillar illumination
- Pathway and boundary lighting
- Tree canopy highlighting
- Garden and seating area visibility
- Water feature enhancement
- Step and stair safety lighting

SPECIFICATIONS			
Product Code	IG-01-12V-36D-BLK		IG-01-12V-60D-BLK
Electrical	Input Voltage	12/24V AC/DC	
	Power Consumption	6W	
Specs	Colour Temperature	3000K	
	CRI	90+	
	Lumen Output	580LM	
	Efficacy (LM/W)	97	
	Dimmable	No	
	IP Rating	IP67	
	Beam Angle	36°	60°
LED	Type	SMD2835	
	Life Span	50,000 Hours	
Design	Dimensions (Inches)	3.03 x 4.02”	
	Dimensions (Millimeters)	76.9 x 102 mm	
	Finish	Black	
	Material	Die-cast Aluminum	
	Cable	Copper	
	Operating Temperature	-20 to 40°C	
	Approved Location	Outdoor	
	Mounting	In-ground	
Warranty	15 years		
Approvals	cETLus		



DIAGRAM



ACCESSORIES



- ACC-12G-2C-BUR**
Landscape burial wire, 12G, 2C - 500ft spool
- ACC-12G-2C-BUR-XX**
Landscape burial wire, 12G, 2C - custom cuts

NOTE: A transformer is required. See page 106 to 109.

12V AC, 100W Transformer

A small transformer for smaller installations. Comes with built in photocell and mechanical timer.




FEATURES

- Composite body
- Built-in mechanical timer
- Built-in photocell
- 12V/100W output, 120V input
- Transparent sliding lid design
- Overload protection
- IP65 weatherproof
- 72"SJT(W) cable, heavy gauge, grounded and water resistant power cord with molded plug
- 50,000 hour life
- 2 comm terminals
- 12V, 15V terminals
- 15 years warranty
- 7.5" by 4.4" by 4.5"

SPECIFICATIONS		
Product Code	ACC-TR-100W	
Electrical	Input Voltage	120V
	Output Voltage	12V AC
	Power	100W
	Max Output Current	8.5A
Specs	Colour Temperature	Cool White 98 lumens @ 5500K; Warm White 95 lumens @ 2700K
	Life Span	50,000 Hours
Design	Dimensions (Inches)	7.5 x 4.33"
	Dimensions (Millimeters)	190 x 110mm
	Finish	Black
	Material	Composite
	Operating Temperature	-20 to 40°C
	Mounting	On Wall
	IP Rating	IP65
Warranty	15 years	
Approvals	cETLus	



DIAGRAM



ACCESSORIES



ACC-12G-2C-BUR

Landscape burial wire, 12G, 2C - 500ft spool

ACC-12G-2C-BUR-XX

Landscape burial wire, 12G, 2C - custom cuts

12-15V AC, 300W Transformer

A 300W transformer, in a stainless-steel case. Enough power to run most landscape light systems. For bigger properties, run 2 units.



FEATURES

- Stainless steel case
 - 300W output, 110V input
 - 1 common terminal, with 12V, 13V, 14V, 15V terminals
 - 6.1" by 5.3" by 11.6" dimensions
 - Quick mount bracket
 - Sealed removable lockable hinged door
- Pre-scored knockout sides and bottom panel
 - Tool-less removable bottom panel
 - Fully encapsulated Toroid Core
 - 304L stainless steel enclosure
 - 15 years warranty

SPECIFICATIONS		
Product Code	ACC-TR-300W	
Electrical	Input Voltage	120V
	Output Voltage	12V, 13V, 14V, 15V AC
	Power	300W
	Max Output Current	8.5A
	Primary Protection	25 AMP breaker
Specs	Colour Temperature	Cool White 98 lumens @ 5500K; Warm White 95 lumens @ 2700K
Design	Life Span	50,000 Hours
	Dimensions (Inches)	11.6 x 6.1"
	Dimensions (Millimeters)	295 x 155mm
	Finish	Black
	Material	Composite
	Operating Temperature	-20 to 40°C
	Mounting	On Wall
Warranty	IP Rating	IP65
Warranty	15 years	
Approvals	cETLus	



DIAGRAM



ACCESSORIES



ACC-DT
Digital Timer



ACC-PC
Photocell



ACC-WIFI
Wi-Fi Controller



ACC-12G-2C-BUR
Landscape burial wire, 12G, 2C - 500ft spool

ACC-12G-2C-BUR-XX
Landscape burial wire, 12G, 2C - custom cuts



Down Lighting

5CCT LED Thin Line Down Light (Round)

Ideal for both commercial and residential settings, this versatile and cost-effective down light offers adjustable 5 color temperatures.



FEATURES

- TRIAC dimmable
 - 120° beam spread
 - Adjustable colour temperature
 - Two spring loaded clips to attach to any ceiling material
 - White finish (interchangeable: brushed nickel, black, bronze trim rings available - sold separately)
- Wet locations listed
 - Temperature rating: -20°C to 45°C
 - No IC can required, for direct contact with insulation and combustible materials
 - Connects directly to 120V power supply
 - Optional 347V Step-Down
 - Transformer (non-dimmable)

APPLICATIONS

- Kitchens & pantries
- Laundry rooms
- Bathrooms
- Lobbies & hallways
- Banquet halls & elevators
- Retail lighting
- Offices & restaurants

SPECIFICATIONS						
Size		3 Inches	4 Inches	6 Inches	8 Inches	10 Inches
Product Code		DL-5CCT-3-WH	DL-5CCT-4-WH	DL-5CCT-6-WH	DL-5CCT-8-WH	DL-5CCT-10-WH
Electrical	Input Voltage	120V AC				
	Power Consumption	6W	9W	12W	15W	20W
Specs	Color Temperature	2700/3000/3500/4000/5000K				
	Lumen Output	420-445	627-684	995-1117	1368-1465	1817-1944
	Efficacy	70LM/W				
	CRI	90				
	Dimmable	Yes (TRIAC)				
	Beam Angle	120°				
LED	Type	Epistar				
	Life Span	50,000 Hours				
Design	Dimensions (Inches)	3.1 x 3.8 x .5"	4 x 4.7 x .5"	6.14 x 6.85 x 0.5"	8 x 8.9 x 0.5"	10 x 10.8 x 0.5"
	Dimensions (Millimeters)	80 x 95.5 x 11.5mm	101 x 120.1 x 11.5mm	150 x 174.5 x 11.5mm	220 x 226 x 11.5mm	254 x 274 x 11.5mm
	Installation Hole Size	3.35" (85mm)	4.33" (110mm)	6.3" (160mm)	8.27" (210mm)	10.16" (258mm)
	Finish	White				
	Trim Finish	BK: Black, BZ: Bronze, BN:Brushed Nickel				
	Operating Temperature	-20°C to 45°C				
	Approved Location	Wet				
	Mounting	Ceiling via spring loaded clips				
Warranty	5 years					
Approvals	cETLus and Energy Star					

PRODUCT CODES

DL-5CCT-YY-WH

5CCT LED
Thin-Line Down
Lights

SIZE
3: 3"
4: 4"
6: 6"
8: 8"
10: 10"


ROUND TRIM RINGS

(Sold Separately)

LVLDL - 03 - TR - XX - L3
LVLDL - 04 - TR - XX - L3
LVLDL - 06 - TR - XX - L3
LVLDL - 08 - TR - XX - L3
LVLDL - 10 - TR - XX - L3

TRIM RING FINISH
BK: Black, BZ: Bronze; BN - Brushed Nickel

DIAGRAM








ACCESSORIES



LVLDL-YY-TR-XX-L3
Trim Rings For 5 CCT LED Thin Line Down Light (sold separately).

CONSTRUCTION PLATES



5CCT LED Thin Line Down Light (Square)

Designed with a sleek square shape, this down light offers versatility, affordability, and adjustable 5 color temperatures.



FEATURES

- TRIAC dimmable
- 120° beam spread
- Adjustable colour temperature
- Two spring loaded clips to attach to any ceiling material
- White finish (interchangeable: brushed nickel, black, bronze trim rings available - sold separately)
- Wet locations listed
- Temperature rating: -20°C to 45°C
- No IC can required, for direct contact with insulation and combustible materials
- Connects directly to 120V power supply
- Optional 347V Step-Down
- Transformer (non-dimmable)

APPLICATIONS

- Kitchens & pantries
- Laundry rooms
- Bathrooms
- Lobbies & hallways
- Banquet halls & elevators
- Retail lighting
- Offices & restaurants

SPECIFICATIONS			
Size		4 Inches	6 Inches
Product Code		DL-5CCT-4S-WH	DL-5CCT-6S-WH
Electrical	Input Voltage	120V AC	
	Power Consumption	9W	12W
Specs	Color Temperature	2700/3000/3500/4000/5000K	
	Lumen Output	630	840
	Efficacy	70LM/W	
	CRI	90	
	Dimmable	Yes (TRIAC)	
	Beam Angle	120°	
LED	Type	Epistar	
	Life Span	50,000 Hours	
Design	Dimensions (Inches)	4.1 x 4.7 x .4"	6.3 x 6.8 x .4"
	Dimensions (Millimeters)	103 x 120 x 11.3mm	159 x 171.5 x 11.3mm
	Installation Hole Size	4.33" (110mm)	6.30" (160mm)
	Finish	White	
	Trim Finish	BK: Black, BZ: Bronze, BN:Brushed Nickel	
	Operating Temperature	-20°C to 45°C	
	Approved Location	Wet	
	Mounting	Ceiling via spring loaded clips	
Warranty	5 years		
Approvals	cETLus and Energy Star		

PRODUCT CODES

DL-5CCT-YY-WH


5CCT LED Thin-Line Down Lights

SIZE (Square)
4S: 4"
6S: 6"


SQUARE TRIM RINGS (Sold Separately)
LVLDL - 04S - TR - XX - L3
LVLDL - 06S - TR - XX - L3

TRIM RING FINISH
BK: Black, BZ: Bronze; BN - Brushed Nickel

DIAGRAM




ACCESSORIES



LVLDL-YY-TR-XX-L3
Square Shaped Trim Rings for 5 CCT LED Thin Line Down Light (sold separately).

CONSTRUCTION PLATES



Regressed Down Light (CCT)

Ideal for both new builds and remodeling projects, these versatile and cost-effective downlights come in two configurations: one allows to easily adjust the color temperature with a slider switch (2700/3000/4000K), while the other offers the flexibility of Bluetooth to select any color temperature from 2700K to 5000K.



FEATURES

- Two convenient options: Slider Switch CCT adjustable and Bluetooth CCT adjustable
- Dimmable: Slider Switch CCT Adjustable with Electronic Low Voltage (ELV) dimmers, and Bluetooth CCT Adjustable through the smartphone app
- Two spring loaded clips to attach to any ceiling material
- White finish; Interchangeable satin nickel, black and bronze trim rings available (sold separately)
- Bluetooth CCT Adjustable linkable up to 100 fixtures, individual and zonal control possible through the smartphone app
- Regressed design to reduce glare
- Suitable for damp locations
- Temperature rating: -20°C to 45°C
- The driver is wired for 120V input
- Optional 347V Step-Down Transformer
- 50,000 hour life
- 3 years limited warranty

APPLICATIONS

- Lobbies
- Hallways
- Banquet halls
- Elevators
- Stairways
- Retail
- Restaurants
- Office lighting
- Under cabinet
- In cabinet
- Wall mount for regress lighting
- Under soffits (outdoor)

SPECIFICATIONS				
Type		CCT Switch Adjustable		CCT Bluetooth Adjustable
Product Code		RGL-4B-9W-SW (4")	RGL-6B-12W-SW (6")	RGL-4B-9W-BT (4") RGL-6B-9W-BT (6")
Electrical	Input Voltage	100-277V AC		
	Power Consumption	9W	12W	9W 12W
Specs	Color Temperature	2700/3000/4000K (Slider Switch CCT Adjustable)		2700-5000K (Bluetooth CCT Adjustable)
	Lumen Output	630LM	840LM	630LM 840LM
	Efficacy	70LM/W		
	CRI	90+		
	Dimmable	Yes		
	Beam Angle	120°		
LED	Life Span	50,000 Hours		
Design	Dimensions (Inches)	.86 x .511"	.86 x .716"	.86 x .511" .86 x .716"
	Dimensions (Millimeters)	22 x 130mm	22 x 182mm	22 x 130mm 22 x 182mm
	Installation Hole Size	4.13" (105mm)	6.18" (157mm)	4.13" (105mm) 6.18" (157mm)
	Finish	White		
	Trim Finish	BK: Black, BZ: Bronze, SN: Satin Nickel		
	Operating Temperature	-20°C to 40°C		
	Approved Location	Indoor		
Warranty	Mounting	Ceiling via spring loaded clips		
	Warranty	3 years		
	Approvals	cETLus listed for damp locations and Energy Star		

PRODUCT CODES

CCT SWITCH ADJUSTABLE
RGL - 4B - 9W - SW
RGL - 6B - 12W - SW

CCT BLUETOOTH ADJUSTABLE
RGL - 4B - 9W - BT
RGL - 6B - 12W - BT

TRIM RINGS
(Sold Separately)
RGL - 4 - TR - XX
RGL - 6 - TR - XX


TRIM RING FINISH
BK - Black
BZ - Bronze
SN - Satin Nickel

STEP-DOWN TRANSFORMERS
DLT-347
Step-down transformer 347/120V AC 25VA (non-dimmable)



DLT-60-347
Step-down transformer 347/120V AC 60VA (non-dimmable)

DLT-100-347
Step-down transformer 347/120V AC 100VA (non-dimmable)

DIAGRAM



CONSTRUCTION PLATES



ACCESSORIES



RGL-4-TR-XX
RGL-6-TR-XX [XX= (Black), BZ=(Bronze), SN=(Satin Nickel)]
Trim Rings For 5 CCT LED Thin Line Down Light (sold separately).

5CCT LED Gimbal Down Light

Ideal for directional lighting in both remodels and new constructions, 5CCT LED Gimbal Down Lights provide a flexible and cost-effective option across a broad range of uses.



FEATURES

- 120V AC input voltage
- TRIAC dimmable
- Low power consumption: 8/ 14/18W
- Available in 3", 4" and 6"
- Luminous flux: 600-650LM/ 950-1000LM/ 1150-1200LM
- CCT adjustable: 2700/ 3000/ 3500/4000/ 5000K
- 30,000 hour life
- 360° rotation
- Beam angle: 38°
- Tilting angle: 90°
- 90CRI
- cETLus, Energy Star certified
- 5 years limited warranty
- Airtight

APPLICATIONS


- RESIDENTIAL

 - Kitchens
 - Pantries
 - Laundry rooms
 - Bathrooms
- COMMERCIAL


 - Lobbies
 - Hallways
 - Elevators
 - Stairways
 - Retail
 - Restaurants
 - Office lighting

SPECIFICATIONS				
Size		3 Inches	4 Inches	6 Inches
Product Code		GDL-3-8W-38-CCT-WH	GDL-4-14W-38-CCT-WH	GDL-6-18W-38-CCT-WH
Electrical	Input Voltage	120V AC		
	Power Consumption	8W	14W	18W
Specs	Color Temperature	2700/3000/3500/4000/5000K		
	Luminous Flux	600-650LM	950-1000LM	1150-1200LM
	CRI	90+		
	Dimmable	Yes, TRIAC dimmable		
	Beam Angle	38°		
	Rotation	360°		
	Tilting Angle	90°		
LED	Type	High Brightness COB LED		
	Life Span	30,000 Hours		
Design	Dimensions (Inches)	1.3 x 3.35'	1.42 x 4.41"	2.09 x 6.02"
	Dimensions (Millimeters)	33 x 85mm	36 x 112mm	53 x 153mm
	Installation Hole Size	3 3/8" (85mm)	4 7/16" (112mm)	6" (153mm)
	Finish	White		
	Operating Temperature	-20°C to 40°C		
	Approved Location	Indoor/Outdoor		
	Mounting	Ceiling via spring loaded clips		
Warranty	5 years			
Approvals	cETLus and Energy Star			


PRODUCT CODES




DIAGRAM



DIMENSIONS



CONSTRUCTION PLATES



Surface Mount Down Lights

(ROUND)

The LED Surface Mount Down Light offers a streamlined solution for efficient lighting. Built-in Driver on Board (DOB) technology allows for easy ceiling installation without an external driver. Perfect for enhancing any residential or commercial space.



FEATURES

- DOB technology provides a 120V alternating currentsource and eliminates the need for traditional LED driver
- Quick & easy to install on standard junction box, ceiling mount with mounting plate
- Temperature rating: -20° to 40°C
- Die-cast aluminum housing
- Smooth and continuous dimming with most ELV dimmers
- Rated for 50,000 hours
- No light bulbs to replace or dispose
- Instant full brightness (including in sub-zero temperatures)
- 80+ CRI
- cETLus listed for wet locations
- 5 years limited warranty

APPLICATIONS

- RESIDENTIAL**
 - Kitchens
 - Pantries
 - Laundry rooms
 - Under cabinet
 - In cabinet
 - Under soffits (Outdoor)
- COMMERCIAL**
 - Lobbies & hallways
 - Banquet halls
 - Elevators & stairways
 - Retail & restaurants
 - Under cabinet
 - In cabinet
 - Wall mount for regress lighting

SPECIFICATIONS					
Size		6 Inches	8 Inches	10 Inches	12 Inches
Product Code		LVLDL-SR-06-XX-WH-L	LVLDL-SR-08-XX-WH-L	LVLDL-SR-10-XX-WH-L	LVLDL-SR-12-XX-WH-L
Electrical	Input Voltage	120V AC			
	Power Consumption	11W	14W	17W	22W
Specs	Color Temperature	3000/4000K			
	Lumen Output	880WW, 900NW	1000WW, 1050NW	1200WW, 1250NW	1800WW, 1850NW
	Efficacy	80WW, 82NW	71WW, 75NW	70WW, 73NW	82WW, 84NW
	CRI	80+			
	Dimmable	Yes (with most ELV dimmers)			
	Beam Angle	120°			
LED	Type	Epistar			
	Life Span	50,000 Hours			
Design	Dimensions (Inches)	6" D x 1" H	8" D x 1" H	10" D x 1" H	12" D x 1" H
	Dimensions (Millimeters)	152mm D x 25mm H	203mm D x 25mm H	254mm D x 25mm H	305mm D x 25mm H
	Product Material	Die-cast aluminum housing			
	Trim Finish	BK: Black, BZ: Bronze, BN:Brushed Nickel			
	Operating Temperature	-20°C to 40°C			
	Approved Location	Kitchens, pantries, laundry areas, and under soffits (outdoors)			
	Mounting	Surface via screw-fixed mounting plate			
Warranty	5 years				
Approvals	cETLus listed for wet locations and Energy Star				

PRODUCT CODES

LVLDL - SR - YY - XX - WH - L

Round LED Surface Mount Down Light


SIZE
06 - 6"
08 - 8"
10 - 10"
12 - 12"

LED Colour
WW: 3000K
NW: 4000K

ROUND TRIM RINGS (Sold Separately)
LVLDL - SR - 06 - TR - XX - L
LVLDL - SR - 08 - TR - XX - L
LVLDL - SR - 10 - TR - XX - L
LVLDL - SR - 12 - TR - XX - L

TRIM RING FINISH
BK: Black, BZ: Bronze, SN: Satin Nickel

DIAGRAM



Surface Mount Down Lights (SQUARE)

The Square LED Surface Mount Down Light, with its compact, square design and DOB technology, requires no external driver for ceiling mounting. Directly fits into 4” junction boxes, suitable for widespread lighting in residential or commercial spaces.



FEATURES

- DOB technology provides a 120V alternating currentsource and eliminates the need for traditional LED driver
- Quick & easy to install on standard junction box, ceiling mount with mounting plate
- Temperature rating: -20° to 40°C
- Die-cast aluminum housing
- Smooth and continuous dimming with most ELV dimmers
- Rated for 50,000 hours
- No light bulbs to replace or dispose
- Instant full brightness (including in sub-zero temperatures)
- 80+ CRI
- cETLus listed for wet locations
- 5 years limited warranty

APPLICATIONS

- RESIDENTIAL**
 - Kitchens
 - Pantries
 - Laundry rooms
 - Under cabinet
 - In cabinet
 - Under soffits (Outdoor)
- COMMERCIAL**
 - Lobbies & hallways
 - Banquet halls
 - Elevators & stairways
 - Retail & restaurants
 - Under cabinet
 - In cabinet
 - Wall mount for regress lighting

SPECIFICATIONS					
Size		6 Inches	8 Inches	10 Inches	12 Inches
Product Code		LVLDL-SS-06-XX-WH-L	LVLDL-SS-08-XX-WH-L	LVLDL-SS-10-XX-WH-L	LVLDL-SS-12-XX-WH-L
Electrical	Input Voltage	120V AC			
	Power Consumption	11W	14W	17W	22W
Specs	Color Temperature	3000/4000K			
	Lumen Output	880WW, 900NW	1000WW, 1050NW	1200WW, 1250NW	1800WW, 1850NW
	Efficacy	80WW, 82NW	71WW, 75NW	70WW, 73NW	82WW, 84NW
	CRI	80+			
	Dimmable	Yes (with most ELV dimmers)			
	Beam Angle	120°			
LED	Type	Epistar			
	Life Span	50,000 Hours			
Design	Dimensions (Inches)	6" D x 1" H	8" D x 1" H	10" D x 1" H	12" D x 1" H
	Dimensions (Millimeters)	152mm D x 25mm H	203mm D x 25mm H	254mm D x 25mm H	305mm D x 25mm H
	Product Material	Die-cast aluminum housing			
	Trim Finish	BK: Black, BZ: Bronze, BN:Brushed Nickel			
	Operating Temperature	-20°C to 40°C			
	Approved Location	Kitchens, pantries, laundry areas, and under soffits (outdoors)			
	Mounting	Surface via screw-fixed mounting plate			
Warranty	5 years				
Approvals	cETLus listed for wet locations and Energy Star				

PRODUCT CODES

LVLDL - SS - YY - XX - WH - L

Square LED Surface Mount Down Light


SIZE
06 - 6"
08 - 8"
10 - 10"
12 - 12"

LED Colour
WW: 3000K
NW: 4000K

ROUND TRIM RINGS (Sold Separately)
LVLDL - SS - 06 - TR - XX - L
LVLDL - SS - 08 - TR - XX - L
LVLDL - SS - 10 - TR - XX - L
LVLDL - SS - 12 - TR - XX - L

TRIM RING FINISH
BK: Black, BZ: Bronze, SN: Satin Nickel

DIAGRAM



Ceiling Lights

Ceiling lights are versatile, designed to fit any interior, whether at home or in a business. They serve as direct replacements for traditional ceiling fixtures, offering both aesthetic appeal and energy efficiency.



FEATURES

- Elegant and energy efficient design
- Available in brushed nickel trim
- Suitable for damp location
- Input voltage: 120VAC
- Dimmable with most ELV dimmers
- 50,000 hours life
- cETLus listed
- Easy installation
- Maintenance free
- Even light distribution
- 5 year warranty


APPLICATIONS

- RESIDENTIAL**
 - Kitchens
 - Pantries
 - Laundry rooms
 - Bathrooms
- COMMERCIAL**
 - Lobbies
 - Hallways
 - Elevators
 - Stairways
 - Retail & restaurants


SPECIFICATIONS		
Product Code	CLD-1625-XXK-BN	
Electrical	Input Voltage	120V AC
	Power Consumption	25W
Specs	Colour Temperature	3000K
	CRI	80
	Lumen Output	1875LM
	Dimmable	Yes (with most ELV dimmers)
	Beam Angle	120°
LED	Life Span	50,000 Hours
Design	Dimensions (Inches)	18.87 x 3.65"
	Dimensions (Millimeters)	403 x 93mm
	Finish Colour / Trims	Brushed Nickel
	Product Material	Metal/Acrylic
	Approved Location	Indoor
	Mounting	Ceiling
Warranty	5 years	
Approvals	cETLus and Energy Star	

NOTE: MOQ may apply.

PRODUCT CODES




DIAGRAM



Wall Sconce

Beautifully designed, elegant and a great addition to any decor, Wall Sconces will compliment any designer look. These fixtures can replace any existing indoor accent lighting, creating tremendous energy savings, at an extremely affordable price.



FEATURES

- Elegant and energy efficient design
- Brushed nickel trim finish
- Input voltage 120V AC
- Dimmable with most ELV dimmers
- 50,000 hours life
- Suitable for damp location
- cETLus listed
- Easy installation
- Maintenance free
- Even light distribution
- 5 years warranty

APPLICATIONS

- Hallways
- Lobbies
- Banquet halls
- Retail
- Restaurants

SPECIFICATIONS		
Product Code	WSL-15-XXK-BN	
Electrical	Input Voltage	120V AC
	Power Consumption	15W
Specs	Colour Temperature	3000K
	CRI	80+
	Lumen Output	1600LM
	Dimmable	Yes (with most ELV dimmers)
	Beam Angle	180°
LED	Life Span	50,000 Hours
Design	Dimensions (Inches)	9.45 x 10.63"
	Dimensions (Millimeters)	240.03 x 270mm
	Finish Colour / Trims	Brushed Nickel
	Product Material	Metal/acrylic
	Approved Location	Indoor
	Mounting	Wall
Warranty	5 years	
Approvals	cETLus and Energy Star	

PRODUCT CODES

WSL - 15 - XXK - BN

Wall
Sconce
Light


WATT

15W

CCT

30: 3000K

DIAGRAM



T-Edge Lights (5CCT)

An innovative lighting solution, ideal for general and accent lighting in offices, hallways, and commercial applications. Its edge-lit design and 5CCT feature ensure versatile illumination, moving beyond traditional flat panels and troffers.



FEATURES

- Ideal replacement for traditional flat panel and troffers
- Non-flicker, no dark spots
- IP Rating: IP40
- cETLus and DLC premium listed
- Dry locations
- 5 year limited warranty

APPLICATIONS

- RESIDENTIAL**
 - Kitchens
 - Bathrooms
 - Laundry rooms
 - Pantries
 - Rec rooms
- COMMERCIAL**
 - Retail
 - Offices
 - Hallways
 - Elevators
 - Banquet halls
 - Restaurants


SPECIFICATIONS			
Product Code		TLE-2X2-K40-3065	TLE-2X4-K60-3065
Electrical	Input Voltage	100-277V AC	
	Power Consumption	20/30/40W Adjustable	40/50/60W Adjustable
Specs	Colour Temperature	3000/3500/4000/5000/6500K	
	CRI	80+	
	Lumen Output	2500-5000LM	5000-7500LM
	Efficacy (LM/W)	130	
	Dimmable	0-10V Dimming	
	Beam Angle	120°	
	Life Span	50,000 Hours	
Design	Dimensions (Inches)	23.74 x 23.74 x 0.59"	23.74 x 47.76 x 0.59"
	Dimensions (Millimeters)	603 x 603 x 15mm	603 x 1213 x 15mm
	Finish	White	
	Housing Material	6063-T5	
	Operating Temperature	-20° to 45°C	
	Approved Location	Dry	
	Mounting	Ceiling (placed upon t-bar or hung with wire)	
Warranty	5 years		
Approvals	cETLus and DLC Premium		

PRODUCT CODES

TLE - 2X2 - K40 - 3065
TLE - 2X4 - K60 - 3065

SIZE WATTS

DIAGRAM



ACCESSORIES



TLE-DM
Driver mount bracket (for mounting the bracket to the T-BAR)



TLE-MC
Mounting clips (for fixture wire suspension)



ELP14-2060-UNV
Emergency Driver (sold separately)

NOTES:

- TLE-EX-CCT-10: T-LED CCT Edge Light Extension Cord. 10ft is available.
- Driver mount bracket (TLE-DM), and mounting clips (TLE-MC) are available (sold separately). Please check your local building codes, if these accessories.

5CCT Fire Rated Thin Line

Designed to seamlessly merge into any environment, these fixtures combine sleek aesthetics with top-tier fire-resistant materials, ensuring not only captivating illumination but also adherence to stringent safety standards. Illuminate spaces with confidence, knowing you've chosen the best in style and safety.



FEATURES

- 2 hour fire rated:
UL 263, ASTM E119 & CAN/ULC S101-14
- Two spring loaded clips to attach to any ceiling material
- White finish (interchangeable brushed nickel, black, oil-rubbed bronze, and copper trim rings available – sold separately)
- Wet locations listed
- No IC can required, for direct contact with insulation and combustible materials
- Optional 347V step-down
- 5 year limited warranty
- Airtight
- cETLus and Energy Star listed
- Comes with mounting brackets and end-to-end connector


APPLICATIONS

- Kitchens & pantries
- Laundry rooms
- Bathrooms
- Lobbies & hallways
- Banquet halls
- Elevators
- Retail lighting
- Offices & restaurants

SPECIFICATIONS			
Product Codes		DL-FR-5CCT-4-WH	DL-FR-5CCT-6-WH
Electrical	Input Voltage	120V AC	
	Output Power (W)	12W	15W
Specs	Colour Temperature	5-position switch for colour temperature adjustment: 2700/3000/3500/4000/5000K	
	CRI	90+	
	Lumens	800LM	1100LM
	Efficacy (LM/W)	73	
	Dimmable	Yes, with TRIAC dimmers	
	Beam Angle	120°	
LED	Type	Epistar	
	Life Span	50,000 Hours	
Design	Dimensions (Inches)	D1=3", D2=5", H=1/2"	D1=5", D2=7", H=1/2"
	Dimensions (Millimeters)	D1=81mm, D2=127mm, H=11.5mm	D1=126mm, D2=175mm, H=11.5mm
	Finish	White finish	
	Trim Ring (Finish)	Brushed nickel, black, oil-rubbed bronze, and copper trim rings – Sold separately	
	Operating Temperature	-20° to +45°C	
	Approved Location	Wet	
	Mounting	Ceiling	
Warranty	5 years		
Approvals	cETLus and Energy Star		



DIAGRAM



ACCESSORIES



DL-FR-TR-4-YY
TRIM RINGS
YY=
• BK (Black)
• BZ (Oil Rubbed Bronze)
• BN (Brushed Nickel)
• CP (Copper)



DL-FR-TR-6-YY
TRIM RINGS
YY=
• BK (Black)
• BZ (Oil Rubbed Bronze)
• BN (Brushed Nickel)
• CP (Copper)



DL-FR-BR-4
BEAUTY RINGS



DL-FR-BR-6
BEAUTY RINGS



DL-FR-CP-4
CONSTRUCTION PLATES



DL-FR-CP-6
CONSTRUCTION PLATES



Industrial Lighting

Tri-Proof Lights

Tri-Proof Lights are robust and stylish, designed to withstand impacts, dust, and water, making them suitable for tough environments like factories and garages, as well as residential areas like stairwells and hallways.



FEATURES

- Water-proof (IP66), dust-proof, pressure-proof (IK10)
- Luminous Efficacy (LPW): 110–120
- Available in 4 ft. length / 40W version
- Excellent heat dissipation
- 50,000 hours life
- Energy efficient: Up to 80% energy savings
- Vandal resistant
- cETLus listed
- 5 years limited warranty

APPLICATIONS

- Parking garages
- Tunnels
- Airports
- Exhibition halls
- Railway, bus and subway stations
- Warehouses and factories
- Supermarkets
- Schools

SPECIFICATIONS		
Product Code	SL66-4FT-40W-40	
Electrical	Input Voltage	100–240V/277V
	Power Efficiency	90%
Specs	Colour Temperature	4000K
	CRI	80+
	Efficacy	110–120LM/W
	Dimmable	No
	Beam Angle	120°
LED	Type	High brightness SMD2835
	Life Span	50,000 Hours
Design	Dimensions (Inches)	48 x 3.7 x 2.7"
	Dimensions (Millimeters)	1200 x 94 x 69mm
	Operating Temperature	-22°F to 113°F (-30°C to 45°C)
	Approved Location	Indoor/Outdoor
	Mounting	Ceiling via brackets
Warranty	5 years	
Approvals	cETLus	

NOTE: Each fixture ships with two strain relief connectors.

PRODUCT CODES




SL66 - 4FT - 40W - XX

Tri-Proof Light

LED COLOUR

40: 4000K

DIAGRAM



100W LED Work Light

The LED Work Light is an energy savings, impact resistant long life temporary lighting solution for illuminating workplaces, shops, garages, and warehouses.



FEATURES

- Spring loaded hook
- 10ft power cord with plug
- 6KV/10KV surge protection
- Hidden, built-in hidden socket
- Eye-catching housing
- Stainless steel guard
- Epistar LEDs
- Hollow heat sink
- Silicone gaskets for damp location use
- 5 years limited warranty

APPLICATIONS


- Construction sites
- Machinery illumination
- Automotive garages
- Industrial warehouses
- Repair shops
- Outdoor night projects

SPECIFICATIONS		
Product Code	LWL-100W-50	
Electrical	Input Voltage	120V AC, 50-60Hz
	Power Consumption	60W
Specs	Colour Temperature	5000K
	CRI	80+
	Lumen Output	13,500 Lm
	Efficacy	135 LM/W
	Beam Angle	360°
LED	Type	Epistar 2835
	Life Span	50,000 Hours
	# per foot / unit	408
Design	Dimensions (Inches)	6.5 x 11.5"
	Dimensions (Millimeters)	165 x 292mm
	Finish Colour / Trims	Black, yellow
	Product Material	Stainless steel guard
	Max Single Run Length	10 LED work lights
	Operating Temperature	-20°C to 40°C
	Approved Location	Damp
	Mounting	Optional tripod, floor mount, magnet mount accessories
Warranty	5 years	
Approvals	cULus, listed for damp location	


PRODUCT CODES

LWL - 100W - 50

DIAGRAM



ACCESSORIES



LWL-MM
Magnet mount kit



LWL-FM
Floor mount kit



LWL-TM
Tripod mount kit

60W LED Work Light

The 60W LED Work Light offers energy-saving, impact-resistant, long-life, temporary lighting solutions for illuminating construction sites, shops, garages, and warehouses.



FEATURES

- 5ft power cord with plug
- Lumen output: 7200LM
- Built-in hidden socket
- Up to 10 LED Work Lights per 120V AC tap
- Stainless steel guard
- LED colour: 5000K
- Damp locations
- 5 years limited warranty
- Optional tripod, floor mount and magnet mount accessories

APPLICATIONS


- Construction sites
- Workshops
- Garages
- Warehouses
- Outdoor night projects
- Emergency repair situations

SPECIFICATIONS		
Product Code	LWL-60W-50	
Electrical	Input Voltage	120V AC, 50-60Hz
	Power Consumption	60W
Specs	Colour Temperature	5000K
	CRI	80+
	Lumen Output	7200
	Efficacy	120 LM/W
	Beam Angle	360°
LED	Type	Epistar 2835
	Life Span	50,000 Hours
	# per foot / unit	408
Design	Dimensions (Inches)	5.12"W x 10.4"H
	Dimensions (Millimeters)	130mm x 215mm
	Finish Colour / Trims	Black, yellow
	Product Material	Stainless steel guard
	Max Single Run Length	10 LED work lights
	Operating Temperature	-20°C to 40°C
	Approved Location	Damp
	Mounting	Optional tripod, floor mount, magnet mount accessories
Warranty	5 years	
Approvals	cETLus and DLC	


PRODUCT CODES

LWL - 60W - 50

DIAGRAM



ACCESSORIES



LWL-MM
Magnet mount kit




LWL-FM
Floor mount kit



LWL-TM
Tripod mount kit

LED String Work Light

The LED String Work Light features 5 x 8-watt LED fixtures along a 50Ft string, offering bright, efficient, and portable lighting for construction sites, shops, garages, or warehouses.



FEATURES

- Length: 50ft
 - Lumen output: 5000LM
 - Wet locations
 - LED colour: 5000K
 - 40 Watts per string
 - Up to 10 LED string work lights per 120V AC tap
- Metal wire guard around each fixture
 - Carabiner clip on each fixture
 - 5 years limited warranty

APPLICATIONS


- Construction sites
- Outdoor events
- Workshops
- Garages
- Warehouses
- Marinas

SPECIFICATIONS		
Product Code	SWL-60W-50	
Electrical	Input Voltage	120V AC, 50-60Hz
	Power Consumption	60W
Specs	Colour Temperature	5000K
	CRI	80+
	Lumen Output	7500
	Efficacy	112.5 LM/W
	Beam Angle	180°
LED	Type	Epistar 2835
	Life Span	50,000 Hours
	Spacing	1500mm (59 1/16") at start/finish, 4 x 3000mm (118 7/64")
	# per foot / unit	5
Design	Dimensions (Inches)	4.5" W x 3" H
	Dimensions (Millimeters)	112 x 78mm
	Finish Colour / Trims	Yellow
	Max Single Run Length	50Ft
	Operating Temperature	-20°C to 40°C
	Approved Location	Wet
	Mounting	Carabiner clip
Warranty	5 years	
Approvals	cETLus	

PRODUCT CODES

SWL - 60W - 50

DIAGRAM





Drivers & Controllers

Switchex®

LED DRIVER + DIMMER IN ONE

SWITCHEX® is a dimmer with an integrated driver that converts 120VAC to either 12VDC or 24VDC. This means SWITCHEX® is all you need between your line voltage and low voltage LED lighting. Best of all, it fits in a standard electrical box.

SWITCHEX® solves two of the most common LED lighting challenges:

- Poor dimming performance that often results when a dimmer and LED driver are made by different manufacturers
- Finding a place to fit the LED driver


FEATURES

- First LED Driver + In-Wall Dimmer Switch in one unit
- Simplifies LED installation by eliminating compatibility issues between driver and dimmer
- Fits in a standard recessed electrical box
- 100% - 1% smooth dimming
- No minimum load
- Single pole preset dimmer with on/off push switch
- Adjustable voltage output dial to address voltage drop
- Includes voltage barrier partition to install high and low voltage circuit in same switch box
- No derating required when ganging units
- Power failure memory: If power is interrupted, SWITCHEX will return to setting prior to interruption

APPROVED FIXTURES

- 24V LED Fixtures
- HP strip series
 - eStrip
 - Globe light
 - Hard strip
- 12V LED Fixtures
- Disc light



SPECIFICATIONS			
Product Code		SX-12V-DD-60W	SX-24V-DD-100W
Electrical	Input Voltage	120V AC	
	Output Voltage	12V DC	24V DC
Specs	Max. Load	60W, 5A	100W, 4.2A
	Power Factor	>0.9 @ 120VAC 60Hz max load	
	Efficiency	≥91% @ 120VAC max load	
	Dimmable	Yes	
	Protections	Short circuit, thermal runaway, and over voltage	
	Mounting	Single-Gang Box	
	Connection Type	Hardwire	
Warranty		2 years	
Approvals		cULus, FCC, RoHS	



PRODUCT CODES

SX - XXV - DD - YYW			TRIM PLATE (Sold Separately)	
Switchex	OUTPUT VOLTAGE	WATTAGE	Switchex Trim Plate	FINISH
	12: 12V DC	60: 60W		BR: Glossy Brown
	24: 24V DC	100: 100W		LA: Glossy Light Almond
				WH: Glossy White

DIAGRAM



The Driver Is Inside

SWITCHEX® is all you need between your line voltage and low voltage LED lighting. The integrated driver converts 120VAC to either 12VDC or 24VDC and it fits in a standard electrical box.



Dimmable Driver/Dimmer Compatibility List

Our dimmable LED drivers offer smooth brightness control, letting you adjust your LED lighting from fully lit (100%) to completely off (0%). These drivers are Class 2 certified and built to work with the majority of standard Magnetic Low Voltage (MLV) and Incandescent TRIAC (leading edge) dimmers. Trusted brands like Lutron and Leviton, prevalent in both residential and commercial settings, are compatible with our drivers, ensuring broad availability and ease of integration.

Note: Compatibility list may change without prior notice.

DIMMER COMPATIBILITY LIST				
DIMMER TYPE - LISTED	TRE24L96DC	TRE24L40DC	TRE12L60DC	TRE12L20DC
Lutron Caseta, Wireless PD-6WCL (MLV)	Dims to 0%	Dims to 0%	Dims to 0%	Dims to 0%
Lutron Maestro, Wireless MRF-2-6CL (MLV)	Dims to 1%	Dims to 1%	Dims to 1%	Dims to 1%
Lutron Radio RA2 RRD-6ND (MLV)	Dims to 0%	Dims to 0%	Dims to 0%	Dims to 0%
Lutron Maestro MA-600 (MLV)	Dims to 0%	Dims to 0%	Dims to 0%	Dims to 0%
Leviton Decore Smart DW6HD (MLV)	Dims to 0%	Dims to 0%	Dims to 0%	Dims to 0%
Lutron Nova T NTLV-600 (MLV)	Dims to 1%	Dims to 1%	Dims to 1%	Dims to 1%
Lutron Diva DVLV-600P (MLV)	Dims to 0%	Dims to 0%	Dims to 0%	Dims to 0%
Lutron Diva DVLV-103P (MLV)	Dims to 0%	Dims to 0%	Dims to 0%	Dims to 0%
Lutron Caseta, Wireless PD-10NXD	Dims to 0%	Dims to 0%	Dims to 0%	Dims to 0%
Lutron Maestro MA-PRO (MLV Mode)	Dims to 0%	Dims to 0%	Dims to 0%	Dims to 0%
Lutron Radio RA2 RRD-PRO (MLV Mode)	Dims to 1%	Dims to 1%	Dims to 1%	Dims to 1%
Lutron Caseta, Wireless PD-5NE (MLV Mode)	Dims to 0%	Dims to 0%	Dims to 0%	Dims to 0%
Lutron Caseta , Smart Home Plug-in PD-3PCL	Dims to 0%	Dims to 0%	Dims to 0%	Dims to 0%
Lutron Maestro MACL-153P	Dims to 0%	Dims to 0%	Dims to 0%	Dims to 0%
Lutron Maestro MSC-1000M	Dims to 0%	Dims to 0%	Dims to 0%	Dims to 0%
Lutron Toggle TGCL-153P	Dims to 0%	Dims to 0%	Dims to 0%	Dims to 0%
Lutron Sunnata Touch STCL-153P	Dims to 0%	Dims to 0%	Dims to 0%	Dims to 0%
Leviton Decora Smart DW1KD-1BZ	Dims to 0%	Dims to 0%	Dims to 0%	Dims to 0%
Leviton Decora Digital DDMX1-BLZ	Dims to 1%	Dims to 1%	Dims to 1%	Dims to 1%
Leviton Decora Slide DSM10	Dims to 1%	Dims to 1%	Dims to 1%	Dims to 1%
Leviton Decora Slide DSL06-1LZ	Dims to 0%	Dims to 0%	Dims to 0%	Dims to 0%
GE Z-Wave Plus ZW3005	Dims to 0%	Dims to 0%	Dims to 0%	Dims to 0%
WeMo WiFi F7C059	Dims to 0%	Dims to 0%	Dims to 0%	Dims to 0%
TP-Link Kasa Smart HS220P3	Dims to 0%	Dims to 0%	Dims to 0%	Dims to 0%
Leviton Lumina RF DL1KD-1BZ (MLV)	Dims to 1%	Dims to 1%	Dims to 1%	Dims to 1%

LED Drivers

An LED driver is a specialized electrical device that manages power for an LED or groups of LEDs. Unlike standard power supplies, an LED driver adapts to the LED’s changing requirements, ensuring it receives a consistent power supply as its electrical characteristics vary with temperature.

INDOOR/OUTDOOR NON-DIMMABLE DRIVERS	
LEDDR-12-60W	60W 12V DC, 5A Class 2 LED Driver, outdoor rated
LEDDR-24-120W	LED Driver, 24VDC, 120W, Class 5A, 60W, 2 circuit at 60W each

INDOOR/OUTDOOR DIMMABLE DRIVERS	
TRE12L20DC	Electronic LED Driver 20W, 12V DC, IP rated, dimmable
TRE12L60DC	Electronic LED Driver 60W, 12V DC, IP rated, dimmable
TRE24L40DC	Electronic LED Driver 40W, 24V DC, IP67 rated , dimmable
TRE24L96DC	Electronic LED Driver 96W, 24V DC, IP67 rated , dimmable
E-KO-SR	Wet Location Strain Relief for E Series Drivers, PG7, clamping range dia. 3-6.5mm



LEDDR-12-60W



LEDDR-24-120W



TRE12L20DC
TRE12L60DC



TRE24L40DC
TRE24L96DC



E-KO-SR

LED Drivers Selector Chart

Neon Flex					Strip Series†					Globe Light					Wedge Light									
INDOOR/OUTDOOR NON-DIMMABLE DRIVERS																								
LEDDR-12-60W 12V, 60W, hardwire, outdoor, Max. 60W					-					-					-					Max. 200 Globes				
LEDDR-24-120W 24V, 120W, hardwire, outdoor, Max. 120W					Max 40' (12.1m) per single tap, Max 48'(14.6m) combined two secondary taps					Max. recommended load 90W or 20' (6.1m) per single tap, 120W or 27' (8.53m) combined two secondary taps. CCT series: 16' (4.88m) per single tap, 20'(6.1m) combined two secondary taps					Max. 180 Globes per single tap, max. 120 combined two secondary taps					-				
INDOOR/OUTDOOR DIMMABLE DRIVERS																								
TRE12L20DC†† 12V, 20W, hardwire, outdoor, dimmable, Max. 18W, Min. 10W					-					-					-					Max. 80 Globes				
TRE12L60DC†† 12V, 60W, hardwire, outdoor, dimmable, Max. 54W, Min. 30W					-					-					-					Max. 200 Globes				
TRE24L40DC†† 24V, 40W, hardwire, outdoor, dimmable, Max. 36W, Min. 20W					Max 14.5' (4.4m) Min 8 watts, 3.3' (1m) LED Neon Flex					LED Strip Series: Max. recommended load 36W or 8' (2.44m), Min. 8W or 2' (.61m)					Max. 80 Globes					-				
TRE24L96DC†† 24V, 100W, hardwire, outdoor, dimmable, Max. 90W, Min. 50W					Max 40'(12.1m) Min 8 watts, 3.3' (1m) LED Neon Flex					LED Strip Series: Max. recommended load 90W or 20' (6.1m), Min. 8W or 2' (.61m)					Max. 180 Globes					-				

Hard Strip					eStrip					Disc Light					MiniDisc Light									
INDOOR/OUTDOOR NON-DIMMABLE DRIVERS																								
LEDDR-12-60W 12V, 60W, hardwire, outdoor, Max. 60W					-					-					Max. 18 LEDD					Max. 200 LEDMD				
LEDDR-24-120W 24V, 120W, hardwire, outdoor, Max. 120W					-					Max. 90' (27.43m) per single secondary tap, max. 120' (36.58m) combined two secondary taps. RGB eStrip & HP eStrip: 40' (12.1m) per single secondary tap, 50' (15.24m) combined secondary taps					-					-				
INDOOR/OUTDOOR DIMMABLE DRIVERS																								
TRE12L20DC†† 12V, 20W, hardwire, outdoor, dimmable, Max. 18W, Min. 10W					-					-					Max. recommended load 18W or 6 LEDD Min. recommended load 8W or 3 LED Disc Lights					Max. 75 LEDMD Min. recommended load 8W or 34 LED MiniDisc Lights				
TRE12L60DC†† 12V, 60W, hardwire, outdoor, dimmable, Max. 54W, Min. 30W					-					-					Max. recommended load 54W or 18 LEDD Min. recommended load 8W or 3 LED Disc Lights					Max. 200 LEDMD Min. recommended load 8W or 34 LED MiniDisc Lights				
TRE24L40DC†† 24V, 40W, hardwire, outdoor, dimmable, Max. 36W, Min. 20W					Max. recommended load 36W, Min. 8W LED Hard Strip					LED eStrip: Max. 37.5' (11.43m), Min. 8W, 9' LED eStrip (2.44m). High Power: Max. 18' (5.49m), Min. 4' (1.2m)					-					-				
TRE24L96DC†† 24V, 100W, hardwire, outdoor, dimmable, Max. 90W, Min. 50W					Max. recommended load 90W, min. 8W LED Hard Strip					LED eSTRIP: Max. 90' (27.4m), Min. 8W, 9' LED eStrip (2.44m). High Power: Max. 40' (12.19m), Min. 4' (1.2m)					-					-				

† Note: Above maximum and minimum lengths are for Standard Tape. You may double these when using LP, Low Power Tape.

†† TRE drivers require E-KO-SR for outdoor applications

* Please refer to catalogue for # of LEDs per fixture.

LED Controllers List

The selection includes a PIR Motion Sensor for 12/24V DC systems, facilitating energy-efficient, motion-activated lighting. The lineup features WiFi Signal Amplifiers and Controllers, compatible with RGB, RGBW, and CCT setups, ensuring robust signal strength and versatile light management. Additional offerings include a remote control for the WiFi system, an outdoor-rated RGB signal amplifier, and an RF mini controller with an extension cable for LED Hard Strips. For tactile control, there is an RF Touch Control for RGBW lighting, alongside a Signal Amplifier designed for RGB-W systems, catering to both indoor and outdoor lighting scenarios.

Product	Description
SENSORS	
LV-SPIR-1CH-LV	PIR Motion Sensor, 1 Channel, 12/24V DC
CONTROLLERS & AMPLIFIERS	
LT-WIFI-AMP	WiFi Signal Amplifier for RGB, RGBW, CCT
LT-WIFI-CTRL	WiFi Controller for RGB, RGBW, CCT
LT-WIFI-RM	Remote for LT-WIFI-CTRL
LV-RF103	Wireless RF mini RGB controller 24V, 96W
LV-RF103-HW	Wireless RF Mini RGB controller 24VDC, 96W, Hard Wire
LV-RF103-EXSS	6" Tape Extension connector for LV-RF103 controller
LT-11S-RF	RF Touch Control controller for RGBW
LT-490A	Signal Amplifier for RGB-W 12/24V DC



LV-SPIR-1CH-LV



LT-WIFI-AMP



LT-WIFI-CTRL



LT-WIFI-RM



LV-ZJFFS-3CH-6INW



LV-RF103



LT-11S-RF



LT-490A

Transformers - Magnetic

ETL listed indoor and outdoor.



TR-12-150
10" x 3.1" x 3"
1 circuit at 150 watts for 12V AC



TR-12-240
10" x 4.25" x 3.6"
1 circuit at 240 watts for 12V AC



TR-12-300 or TR-24-300
10" x 4.25" x 3.6"
2 circuits at 150 watts each for 12V AC



TR-24-480
11.1" x 4.75" x 4.25"
1 circuit at 480 watts for 24V AC



TR-24-600
11.1" x 4.75" x 4.25"
2 circuits at 300 watts each for 24V AC




TR-24-960
12.5" x 7.0" x 4.75"
2 circuits at 480 watts each for 24V AC



Transformers - Electronic

UL listed as a component ("RU" Marking).

*NOTE: Check your fixture listing for acceptability. All connections must be made per fixture listing and NEC. 120V AC input/11.6V AC output.



TE-12-75
12 Volt, 75 watt Electronic Transformer



TECLT-12-60
6.5" x 1.5" x 1.5"
Class 2, 1 circuit at 60 watts, for 11.7V AC

Appendix


Linear Lighting	Sub-Category	Lighting Solution	Technical Details	Page
	Tape Light	High Density, High Power Indoor	24V; 5.8W/FT; 3000/4000/6500K; 16' MAX RUN; OUTPUT: 450-514 LM/FT	6
		High Density, Low Power Indoor	24V; 2.9W/FT; 3000/4000/6500K; 31' MAX RUN; OUTPUT: 225-257 LM/FT	8
		CCT Indoor	24V; 5.8W/FT; 2500-7000K. 16' MAX RUN; OUTPUT: 261-383 LM/FT.	10
		COB Indoor	24V; 4.2W/FT; 2700/3000/3500/4000/6500K; 20' MAX RUN; OUTPUT: 315-374 LM/FT	12
		Dim to Warm	24V; 5.5W/FT; 1800-3000K; 16' MAX RUN; OUTPUT: 449LM/FT	14
		High Efficacy Indoor	24V; 5.1W/FT; 2700/3000/3500/4000/6500K; 16' MAX RUN OUTPUT: 508-586 LM/FT	16
		High Power Indoor	24V; 4.3W/FT; 2700/3000/3500/4000/6500K; 20' MAX RUN OUTPUT: 280-325 LM/FT	18
		High Power Outdoor	24V; 4.3W/FT; 2700/3000/3500/4000/6500K; 20' MAX RUN OUTPUT: 280-325 LM/FT	20
		High Power, RGB Indoor	24V; 4.3W/FT; RGB; 20' MAX RUN	22
		High Power, RGB Outdoor	24V; 4.3W/FT; RGB; 20' MAX RUN	24
		High Power, RGBW Indoor	24V; 4.3W/FT; RGB + 3000/4000/6500K; 20' MAX RUN	26
		Low Power Indoor	24V; 2.2W/FT; 2700/3000/3500/4000/6500K; 40' MAX RUN; OUTPUT: 143-165 LM/FT	28
		Low Power Outdoor	24V; 2.2W/FT; 2700/3000/3500/4000/6500K; 40' MAX RUN; OUTPUT: 143-165 LM/FT	30
		Low Power, RGB Indoor	24V; 2.2W/FT; RGB; 40' MAX RUN	32
		Low Power, RGB Outdoor	24V; 2.2W/FT; RGB; 40' MAX RUN	34
		Extrusions	-	36
	120V eStrip	120V eStrip	120V AC; 4W/FT; 2700/3000/4000K; 164' MAX RUN; OUTPUT: 280-340 LM/FT	38
	eStrip	Low Power eStrip	24V; 0.96W/FT; AMBER, RED, PURE GREEN; 3000/5800K. 90'MAX RUN; OUTPUT: 55-61 LM/FT	40
		High Power eStrip	24V; 2.2W/FT; 3000/5800K; 40' MAX RUN; OUTPUT: 137-155 LM/FT	42
		RGB eStrip	24V; 2.2W/FT; RGB; 40' MAX RUN	44
	Neon Flex	Neon Flex	24V; 2.44W/FT; RED, GREEN, BLUE, AMBER; RGB; 3000/4000/6000K; 40' MAX RUN; OUTPUT: 61LM/FT	46
	String Lights	Globe Light	24V; 0.5W; 2700/6000K; RED, GREEN, BLUE, AMBER; 150' MAX RUN; OUTPUT: 50 LM/FIXTURE	48
		Wedge Light	12V; 25W/Ft; AMBER; RED; GREEN; 2700/6000K. 100' MAX RUN; OUTPUT: 55-61 LM/FT	50
	Wall Washer	24V Wall Washer	24V; 5.8W/FT; 2700/3000/4000K; 16' MAX RUN; OUTPUT: 100-110 LM/FT	52
		Wall Washer 4' Enclosed	24V; 23.2W; 2700/3000/4000K; OUTPUT: 400-440LM	54

Under Cabinet Lighting	Sub-Category	Lighting Solution	Technical Details	Page
	-	5CCT LED Task Bar	120V AC. 3.5W-20W; 2700/3000/3500/4000/5000K; OUTPUT: 290-1892LM	58
		Gen II LED Hard Strip	24V; 4W-16W; 3000/4200K; OUTPUT: 380-1150 LM/FIXTURE	60
		Gen II 3-Colour Change LED Task Star	120V AC; 5W-25W; 3000/4000/5000K; OUTPUT: 310-1500LM	62
		LED Task Star Pro	120V AC; 3W-20W; 2700/3300/4000K; OUTPUT: 150-1000LM	64
		LED Edgelit Puck Lights	24V; 4W; 3000K; OUTPUT: 200LM	66
	Flood and Spot Lights	Uplight (Wattage Adjustable)	12V; 0-12W; 3000K; OUTPUT: 900LM	70
		Uplight (RGBW)	12V; 0-8W; RGBW; OUTPUT: 500LM	72
		12V Mini Flood Light	12V; 1-5W; 3000K; OUTPUT: 400LM	74
		120V Mini Flood Light (CCT)	120V AC; 15-50W; 3000/4000/5000K; OUTPUT: 1750-7000LM	76
	Pathway Lights	Modern Pathway Light	12V; 1-3W; 3000K; OUTPUT: 80-240LM	78
		Round Tea-Hat Pathway Light	12V; 1-3W; 3000K; OUTPUT: 80-240LM	80
		HD Classic Pathway Light	12V; 5W; 3000K; OUTPUT: 400LM	82
		Commercial Bollards	120V-347V AC; 8W-25W; 3000/4000/5000K; OUTPUT: 1000-3125LM	84
	Wall and Deck Lights	Surface Mount Deck Light	12V; 1-3W; 3000K; OUTPUT: 60-180LM	86
		Outdoor Wall Sconce	120V-240V AC; 15W; 3000/4000K; OUTPUT: 1300LM	88
		Brick Star (GEN II)	120V AC; 5.2W; 3000K; OUTPUT: 468LM	90
		Step Star (GEN II)	120V AC; 5.2W; 3000K; OUTPUT: 468LM	92
		Switch Star	120V AC; 1.4W; 2700K; OUTPUT: 80LM	94
	In Ground Lights	Disc Light	12V; 3W; 2700/5500K; AMBER; OUTPUT: 95-98LM	96
		Mini Disc Marker Light	12V; 0.24W; 2900/5400K; BLUE, GREEN, AMBER, RED	98
		Mini Disc Light (Scoop)	12V; 0.24W; 2900/5400K; BLUE, GREEN, AMBER, RED	100
		Disc Light Dome	12V; 3W; 2700/5500K; OUTPUT: 95-98LM	102
		Well Light	12V; 6W; 3000K; OUTPUT: 580LM	104
	Transformers & Accessories	100W Transformer	120V; 100W MAX; 12V	106
		300W Transformer	120V; 300W MAX; 12-15V; 13AMP BREAKER ON PRIMARY	108


Appendix (Continued)

	Sub-Category	Lighting Solution	Technical Details	Page
Down Lighting	Thin Lines	5CCT LED Thin Line Down Light (Round)	120V AC; 6-20W; 2700/3000/3500/4000/5000K; OUTPUT: 420-1944LM	112
		5CCT LED Thin Line Down Light (Square)	120V AC; 9/12W; 2700/3000/3500/4000/5000K; OUTPUT: 630/840LM	114
	Regressed	Regressed Down Light (CCT)	120V AC; 9-12W; 2700/3000/4000K; OUTPUT: 630-800LM	116
	Gimbal	5CCT LED Gimbal Down Light	120V AC; 8/14/18W; 2700/3000/3500/4000/5000K; OUTPUT: 650/1000/1200LM	118
	Surface Mount / Decorative	Surface Mount Down Lights (Round)	120V AC; 11-22W; 3000/4000K; OUTPUT: 880-1850LM	120
		Surface Mount Down Lights (Square)	120V AC; 11-22W; 3000/4000K; OUTPUT: 880-1850LM	122
		Ceiling Lights	120V AC; 25W; 3000K; OUTPUT: 1875LM	124
		Wall Sconce	120V AC; 15W; 3000K; OUTPUT: 1500LM	126
	T-Edge Lights	T-LED Edge Light (5CCT)	100-277V AC; 20-60W; 3000/3500/4000/5000/6500K; OUTPUT: 2500-5000LM/ 5000-7500LM	128
	Fire Rated	5CCT Fire Rated Thin Line	120V AC; 12-15W; 2700/3000/3500/4000/5000K.; OUTPUT: 800-1100LM	130
Industrial Lighting	-	Tri-Proof Lights	100-277V AC; 40W; 4000K; OUTPUT: 4400LM	134
		100W LED Work Light	100-277V AC; 100W; 5000K; OUTPUT: 12500LM	136
		60W LED Work Light	120V AC; 60W; 5000K; OUTPUT: 7200LM	138
		LED String Work Light	120V AC; 60W; 5000K; OUTPUT: 7500LM	140
Drivers & Controllers	Switchex®			144
	Dimmable Driver/Dimmer Compatibility List			146
	LED Drivers			147
	LED Drivers Selector Chart			148
	LED Controllers List			150
Transformers	Magnetic & Electronic			152
Appendix	-			154
Logos/Icons	-			157

Logos/Icons




Intertek's ETL Certified




Energy Star Certified




120 Volts of AC Power




cULus Certified




DLC Certified




CCT




Wet Location Listed



RGB



Dimmable



Wattage Adjustable

WARRANTY

NATIONAL SPECIALTY LIGHTING (NSL) warrants this lighting system to be free from defects in material and/or workmanship, under normal use and service, for a period of TWO to SIX YEARS (see specifics on product specifications) from the date of original purchase.

In the event of a defect in material or workmanship during the warranty period, NSL will repair or replace (at its option) your Lighting System under the conditions of warranty. NSL will do this at its expense for the cost of materials but not for shipping. **THIS REMEDY IS THE SOLE AND EXCLUSIVE REMEDY FOR ANY AND ALL CLAIMS RELATING TO ANY BREACH OF WARRANTY BY NSL.**

LIMITATIONS, EXCLUSIONS AND OTHER RIGHTS

- A. Except as provided herein, NSL makes no other warranties express or implied, including but not limited to the implied warranties or merchantability or fitness for a particular purpose, and all such warranties are expressly disclaimed.
- B. In no event shall NSL be liable for indirect, incidental or consequential damages, even if NSL has been advised of the possibility of such damage. This disclaimer applies during and after warranty period.
- C. NSL is not responsible for malfunctions in and/or damage to Lighting Systems where a sale is specifically made without warranty. In such an event the disclaimers of warrant and liability, set forth above, shall continue to apply.
- D. This warranty covers normal consumer use and does not cover damage which occurs during shipment or failure which results from alteration, accident, theft, misuse, abuse, abnormal use, negligent installation, improper maintenance or where adequate care has not been taken to prevent ice or snow damage to the lighting system.
- E. Specifically, when installing mini disc lights in harsh environments such as limestone, salted areas, coastal environments etc. Please use the stainless steel version to avoid the risk of corrosion to body of fixture and voiding warranty.

If you discover a defect or malfunction during the period to which this warranty applies, call or email Magic Lite 2013 Ltd. for information or to receive warranty service.

Note: You must contact our office for a RETURN GOODS AUTHORIZATION number before returning product. After inspection it will be determined whether a credit is due.



Free Shipping

Once a customer has reached a cumulative purchase level of \$3,000.00, they are entitled to free normal UPS ground freight charges within the 48 contiguous states on every order* (residential deliveries excluded) *Minimum \$100.00 order to qualify for free freight. With our prompt delivery pledge National Specialty Lighting offers same day shipping on all non-custom orders placed before 11:30am Eastern Time.



**365 Day
Return Policy**

The 365-day return policy allows customers to take advantage of new National Specialty Lighting products, define new markets and help to build their business. A National Specialty Lighting Stocking Distributor may return any current stock item within 12 months of purchase date for a restocking fee of 50%. The restocking fee will be waived if the distributor places a stock order of equal value or greater than the value of the items being returned. No special catches or exceptions. Items are sent back to National Specialty Lighting prepaid in the original packaging, and merchandise is in resalable condition.



No Minimum Orders

National Specialty Lighting does not have a minimum order requirement, and never will. Some companies require you to purchase large quantities of products or meet a specific spending target. Companies use the excuse that it's the cost to process the order. National Specialty Lighting orders are filled regardless of how large or small they are! If you want to purchase just one item to finish a project, no problem, your order is always treated as a priority.



Tracking Orders

Tracking your order has never been easier; simply provide us with an email address and you will automatically be notified when your order has been shipped. All orders are shipped though UPS. Send an email to nslsales@nslusa.com.

For more FAQs, feel free to visit: <https://www.nslusa.com/resources/faqs>