



CONTROLLERS			
<b>3 in 1 LED Strip Controller</b>	<b>5-Channel High Performance Amplifier</b>	<b>4-Zone RGB+CCT Remote</b>	<b>8 Zone RGB+CCT Wall Panel Remote</b>
CNTRL-RGBCCT	CNTRL-AMP	CNTRL-4Z-RGBCCT-RM	CNTRL-8Z-RGBCCT-WP

ACCESSORIES		
<b>ST-ID-RGB-BWBC-6</b>	<b>Splice</b>	<b>6' power feed</b>
ST-ID-RGB-BWBC-6	ST-ID-RGB-B2BC	ST-ID-RGB-W2BC-72

DRIVERS Non-Dimmable	<b>Plug-in Driver 48W/96W:</b>	<ul style="list-style-type: none"> <li>PGID2448</li> <li>PGID2496</li> </ul>
	<b>Indoor/Outdoor driver:</b>	LEDDR-24-120W

Specifications			
Input Voltage	24V DC	Dimensions (Inches)	.31" W
Power Consumption	4.39W/ft (14.4W/m)	Dimensions (Millimeters)	8mm W
Efficacy	36Lm/w	Max Length	20Ft (6M)
Color Temperature	RGB	Custom Cuttable	1.97" (50mm)
Lumen Output	158Lm/ft (518Lm/m)	Approved Location	Indoor
Beam Angle	120°	Warranty	5 Years
Chip Type	2835	# per meter	120
IP Rating	IP20	Approvals	cULus

**Ordering Code(s)**

- ST-ID-RGB-HP-XX-B8 [XX: Length in feet; B: 2835 LED; 0: 10mm PCB]  
Available in 20 feet: ST-ID-RGB-HP-20-B8

Project		Type	
Date		Contact	
Notes			