

High Power and Low Power Indoor (3000K)

Available in High Power and Low Power models, these indoor LED tape lights deliver smooth, pixel-free illumination and are ideal for a wide range of lighting fixtures. Built with dense 2219 LED chips and engineered for consistent colour output, both options offer reliable, long-lasting performance.




FEATURES

- Dense 2219 LEDs per meter for seamless, uniform lighting.
- 3000K warm white with CRI 90+.
- SDCM <3, 1 BIN selection for uniformity.
- Slim 8mm wide PCB for tight spaces.
- IP40 rated for protected indoor environments.
- cULus listed for safety and quality assurance.
- 5-year product warranty.

APPLICATIONS

- Under Cabinet
- Displays
- Coves
- Wall Grazing
- Architectural Features

| SPECIFICATIONS | | | |
|----------------|--------------------------|--|--|
| Product Code | | SL-ID-30K-LP-XX-A8 [XX: Length in feet; A: 2219 LED; 8: 8mm PCB] Available in 20 or 100 feet; For 20 feet: SL-ID-30K-LP-20-A8; For 100 feet: SL-ID-30K-LP-100-A8 | SL-ID-30K-HP-XX-A8 [XX: Length in feet; A: 2219 LED; 8: 8mm PCB] Available in 20 or 100 feet; For 20 feet: SL-ID-30K-HP-20-A8; For 100 feet: SL-ID-30K-HP-100-A8 |
| Electrical | Input Voltage | 24V DC | |
| | Power Consumption | 2.93W/ft (9.6W/m) | 1.46W/ft (4.8 W/m) |
| | Efficacy | 102Lm/w | 110Lm/w |
| Specs | Colour Temperature | 3000K | |
| | Lumen Output | 300Lm/ft (980Lm/m) | 160Lm/ft (528Lm/m) |
| | Beam Angle | 140° | |
| | Dimmable | Yes (PWM / 0-10V / 1-10V) | |
| LED | Chip Type | 2219 | |
| | CRI | 90 | |
| | # per metre | 288 | |
| | Binning | 1BIN | |
| | SDCM | <3 | |
| | Lifespan | 50,000 Hours | |
| Design | Dimensions (Inches) | .31" W | |
| | Dimensions (Millimeters) | 8mm W | |
| | Max Length | 20Ft (6M) | |
| | Custom Cuttable | 2.19" (55.5mm) | |
| | IP Rating | IP40 | |
| | Approved Location | Indoor | |
| Warranty | | 5 Years | |
| Approvals | | cULus | |



ACCESSORIES



SL-ID-W2BC-72
6' Powerfeed



SL-ID-BWBC-6
6" Jumper



SL-ID-B2BC
Splice



SL-ID-LC
L-shaped Connector



SL-ID-TC
T-shaped Connector

DRIVERS


Dimmable



TRE24L40DC
Max. recommended load:
36W; Min. recommended
load: 8W;
6.77" x 2.67" x 1.26" (171 x
68 x 32mm)



TRE24L96DC
Max. recommended load:
90W; Min. recommended
load: 8W;
6.77" x 2.67" x 1.26" (171 x
68 x 32mm)



SX-24V-DD-100W
Switchex

Non-Dimmable



LEDDR-24-120W
Indoor/Outdoor driver
Max. recommended load:
90W;
10" x 3 3/8" x 3 3/16" (254
x 85.7 x 80.9mm)



**PGID2448/
PGID2496**
Plug-in Driver

CONTROLLERS



CNTRL-0-10V-DIM
0/1~10V Dimming
Controller



CNTRL-4Z-CCT-RM
4 Zone CCT Remote



**CNTRL-4Z-CCT-RWP-WH
OR
CNTRL-4Z-CCT-RWP-BK**
Rotating CCT Scene Remote
(White or Black)